





































# PRICE LIST































☎ ۰۲۱۷۷۷۰۰۷۷  
 WWW.RADIS-CO.COM  
 RADIS.NET

## CVI























SKU (#)	SKU (P)	Items	Description	User Price (با گارانتی پارس ارتباط)	User Price (با گارانتی الماس ایران)
250470	210470	<a href="#">DH-HAC-HFW1500THP-IR-0360B</a>	 SMP HDCVI IR Bullet Camera 1/2.7" Progressive Scan CMOS, 20fps@SMP, 25/30fps@4MP, 3.6mm fixed lens, Aperture: F1.85, DWDR, Day/Night(ICR), AWB, AGC, BLC, HLC, 2DNR, Support Electronic Defog, HD/SD switchable, Max. IR length 80m, Smart IR, IP67, DC12V/30	IRR 18,860,000	IRR 27,300,000
		<a href="#">DH-HAC-HFW1500TP-0360B-S2</a>	 SMP HDCVI IR Bullet Camera. Max. 20fps@SMP - HD and SD output switchable - 3.6mm fixed lens (2.8mm, 6mm optional) - Max. IR length 30m, Smart IR - IP67, DC12V	IRR 24,650,000	IRR 14,800,000
		<a href="#">DH-HAC-HFW1500TP-A-0360B-S2</a>	 > Max 25fps@SMP (16:9 video output) > CVI/CVBS/AHD/TVI switchable > 3.6 mm fixed lens (2.8 mm optional) > Built-in mic(A) > Max. IR length 30 m, Smart IR > IP67, DC12V	IRR 22,570,000	IRR 24,700,000
		<a href="#">HAC-HFW1500DP-0360B-S2</a>	 5Megapixel 1/2.7" CMOS20fps@SMP, 25/30fps@4MP, 25/30fps@1080P3.6mm fixed lens & 6mm Fixed LensDWDR, Day/Night(ICR), AWB, AGC, BLC, HLC, 2DNRHD and SD output switchableSupports OSD MenuMax. IR length 80m, Smart IRIP67, DC12V		
		<a href="#">HAC-HFW1500DP-S2</a>	 SMP HDCVI Starlight IR Bullet Camera Support SMP@25fps (16:9 frame. Please upgrade to the latest XVR version) - Support output standard CVI/CVBS/AHD/TVI Real-time without image delay, minimum light sensitivity 0.005Lux/F1.6, 0Lux IR on, day and night mode(ICR), auto white balance (AWB), auto exposure compensation (AGC), anti-backlight (BLC), Anti-noise (2D-DNR). 80m infrared range with smart infrared technology 3.6mm fixed lens, IP67 waterproof standard, metal case	IRR 26,910,000	IRR 25,500,000
		<a href="#">DH-HAC-HFW1400DP-0360B-S3</a>	 1/3" 4.1Megapixel CMOS 25/30fps@4MP, 25/30fps@1080P, 25/30fps@720P 3.6mm fixed lens, DWDR, Day/Night(ICR), AWB, AGC, BLC, HLC, 2DNR HD and SD output switchable, OSD Menu, Max. IR length 80m, Smart IR, IP67, DC12V	IRR 17,260,000	
250277	210277	<a href="#">DH-HAC-HFW1400DP</a>	 Max 30fps@4MP(2560x1440) - HD and SD output switchable - 3.6mm fixed lens (6mm, 8mm optional) - Max. IR length 80m, Smart IR - IP67, DC12V		
		<a href="#">DH-HAC-HFW1400RP-Z-IRE6</a>	 Max 30fps@4MP(2560x1440) - HD and SD output switchable - 2.7-12mm Motorized lens - Max. IR length 60m, Smart IR - IP67, DC12V		
		<a href="#">DH-HAC-HFW1400CMP</a>	 4MP HDCVI IR Bullet Camera, 1/2.7 inch Progressive CMOS Max 30fps@4MP, 3.6mm fixed lens CVI/TVI/AHD/CVBS Switchable, Support OSD Menu DWDR/E-Defog/BLC/HLC/AWB/AGC/2D DNR/Day-Night Auto ICR Max. IR length 30m, Smart IR, IP67, DC12V	IRR 12,820,000	
		<a href="#">DH-HAC-HDW1400TRQP-A-0280B-S3</a>	 4MP HDCVI Quick-to-install IR Eyeball Camera 1/2.7 inch Progressive CMOS Max 30fps@4MP, 2.8mm fixed lens, Built-in Mic CVI/TVI/AHD/CVBS Switchable, Support OSD Menu DWDR/E-Defog/BLC/HLC/AWB/AGC/2D DNR/Day-Night Auto ICR Max. IR length 25m, Smart IR, IP50, DC12V	IRR 9,620,000	
		<a href="#">DH-HAC-HDW1400TRQP-0280B-S3</a>	 4MP HDCVI Quick-to-install IR Eyeball Camera 1/2.7 inch Progressive CMOS Max 30fps@4MP 2.8mm fixed lens CVI/TVI/AHD/CVBS Switchable, Support OSD Menu DWDR/E-Defog/BLC/HLC/AWB/AGC/2D DNR/Day-Night Auto ICR Max. IR length 25m, Smart IR, IP50, DC12V		
250704		<a href="#">HAC-HDW1500TRQP-A-0280B-S2</a>	 Max 25 fps@SMP (16:9 video output) - Quick-to-install eyeball saves installation time - CVI/CVBS/AHD/TVI switchable - 3.6 mm fixed lens (2.8 mm, 6 mm optional) - Built-in mic(A) - Max. IR length 40 m, Smart IR - IP67, DC12V	IRR 14,280,000	IRR 19,000,000
		<a href="#">DH-HAC-HDW1500TLQP-A-0280B-S2</a>	 - Max 25 fps@SMP (16:9 video output) - CVI/CVBS/AHD/TVI switchable - Quick-to-install eyeball saves installation time - 3.6 mm fixed lens (2.8 mm, 6 mm optional) - Built-in mic - Max. IR length 30 m, Smart IR - IP67, DC12V	IRR 20,870,000	
250674		<a href="#">DH-HAC-HDW1500TMQP-A-0280B-S2</a>	 SMP Starlight HDCVI PoC IR Quick-to-install Eyeball Camera > Max 25 fps@SMP (16:9 video output) > CVI/CVBS/AHD/TVI switchable > Quick-to-install eyeball saves installation time > 3.6 mm fixed lens (2.8 mm, 6 mm optional) > Built-in mic > Max. IR length 60 m, Smart IR > IP67, PoC (only CVI/12V/30% DC	IRR 24,670,000	
		<a href="#">DH-HAC-HDW1500TLMQP-0280B-S2</a>	 SMP Starlight HDCVI PoC IR Quick-to-install Eyeball Camera > Max 25 fps@SMP (16:9 video output) > CVI/CVBS/AHD/TVI switchable > Quick-to-install eyeball saves installation time > 3.6 mm fixed lens (2.8 mm, 6 mm optional) > Max. IR length 50 m, Smart IR > IP67, PoC (only CVI/12V/30% DC	IRR 23,960,000	
		<a href="#">DH-HAC-HDW1500TQP-A(S)</a>	 - Quick-to-install eyeball saves installation time - CVI/CVBS/AHD/TVI switchable - 3.6 mm fixed lens (2.8 mm, 6 mm optional) - Built-in mic(A) - Max. IR length 40 m, Smart IR - IP67, DC12V		
250506	210506	<a href="#">DH-HAC-HFW1209TLMQ-LED-0360B</a>	 2MP Full-color HDCVI Bullet Camera 1/2.8 inch 2MP Progressive CMOS Max. 30fps@1080P 3.6mm Fixed lens, Min. Illumination 0.001 Lux/F1.6, 30IRE, 0 Lux LED on NDRI(29db), Day/Night(ICR), AWB, AGC, BLC, HLC, 2D DNR CVI/CVBS/AHD/TVI switchable, OSD Menu Support, Max. IR length 20m, Smart IR, IP67, DC12V	IRR 11,710,000	IRR 20,000,000


















		<a href="#">DH-HAC-HFW1209TLP-A-LED-0360B-S2</a>		<ul style="list-style-type: none"> <li>2MP Full-color HDCVI Bullet Camera</li> <li>&gt; 24/7 color imaging</li> <li>&gt; 40 m illumination distance</li> <li>&gt; Max. 30fps@1080P</li> <li>&gt; CVI/CVBS/AHD/TVI switcheable</li> <li>&gt; Fixed lens (3.6 mm; 6 mm optional)</li> <li>&gt; Built-in mic</li> <li>&gt; IP67, 12V/30W DC</li> </ul>	IRR 20,590,000	
250441	210441	<a href="#">DH-HAC-HFW1200DP-S5</a>		<ul style="list-style-type: none"> <li>1/2.7" 2Megapixel CMOS</li> <li>25/30fps@1080P, 25/30/50/60fps@720P</li> <li>DWDR, Day/Night(ICR), AWB, AGC, BLC, HLC, 2D-DNR</li> <li>HD and SD output switchable, 3.6mm fixed lens</li> <li>Max. IR LEDs length 80m, Smart IR, IP67, DC12V</li> </ul>	IRR 20,410,000	IRR 18,500,000
250468	210468	<a href="#">HAC-HDW1200EMP-A</a>		<ul style="list-style-type: none"> <li>1/2.7" 2Megapixel CMOS, 25/30fps@1080P, Built-in MIC</li> <li>Day/Night(ICR), AWB, AGC, BLC, 2DNR, DWDR</li> <li>3.6 &amp; 2.8mm fixed lens</li> <li>Max. IR LEDs length 50m, Smart IR, IP67, DC12V</li> </ul>	IRR 17,580,000	IRR 16,600,000
250442	210442	<a href="#">DH-HAC-HDW1200TRQP-A-0280B-S5</a>		<ul style="list-style-type: none"> <li>2MP HDCVI Quick-to-install IR Eyeball Camera</li> <li>1/2.7 inch Progressive CMOS</li> <li>Max 30fps@2MP, 2.8mm fixed lens, Built-in Mic</li> <li>CVI/TVI/AHD/CVBS Switcheable, Support OSD Menu</li> <li>DWDR/E-Defog/BLC/HLC/AWB/AGC/2D-DNR/Day-Night Auto switch by ICR</li> <li>Max. IR length 25m, Smart IR, IP50, DC12V</li> </ul>	IRR 13,140,000	IRR 14,200,000
		<a href="#">DH-HAC-HDW1200TRQP-A-0360B</a>		<ul style="list-style-type: none"> <li>2MP HDCVI Quick-to-install IR Eyeball Camera</li> <li>1/2.7 inch Progressive CMOS</li> <li>Max 30fps@2MP, 3.6mm fixed lens, Built-in Mic</li> <li>CVI/TVI/AHD/CVBS Switcheable, Support OSD Menu</li> <li>DWDR/E-Defog/BLC/HLC/AWB/AGC/2D-DNR/Day-Night Auto switch by ICR</li> <li>Max. IR length 25m, Smart IR, IP50, DC12V</li> </ul>	IRR 14,350,000	IRR 14,200,000
		<a href="#">HAC-HDW1200TMQP-A-0280B-S5</a>		<ul style="list-style-type: none"> <li>2MP HDCVI Quick-to-install IR Eyeball Camera</li> <li>* The parameters and datasheets below can only be applied to 1200-S5 series</li> <li>&gt; Max 30fps@1080P</li> <li>&gt; Quick-to-install eyeball saves installation time</li> <li>&gt; CVI/CVBS/AHD/TVI switcheable</li> <li>&gt; 3.6mm fixed lens (2.8mm, 6mm optional)</li> <li>&gt; Built-in mic(A)</li> <li>&gt; Max. IR length 60m, Smart IR</li> <li>&gt; IP67, DC12V</li> </ul>		IRR 20,750,000
		<a href="#">DH-HAC-HDW1200TMQP-A-0208B</a>		<ul style="list-style-type: none"> <li>Max 30fps@1080P</li> <li>Quick-to-install eyeball saves installation time</li> <li>CVI/CVBS/AHD/TVI switcheable</li> <li>3.6mm fixed lens (2.8mm optional)</li> <li>Built-in mic(A)</li> <li>Max. IR length 30m, Smart IR</li> <li>IP67, DC12V</li> </ul>		IRR 10,150,000
		<a href="#">HAC-HDW1200M-S5</a>		<ul style="list-style-type: none"> <li>1/2.7" 2Megapixel CMOS, 25/30fps@1080P, 50/60fps@720P</li> <li>3.6mm fixed lens HD and SD output switchable, Support OSD Menu</li> <li>Day/Night(ICR), AWB, AGC, BLC, 2D-DNR</li> <li>Max. IR length 30m, Smart IR, IP67, DC12V</li> </ul>	IRR 9,180,000	
250433		<a href="#">DH-HAC-HFW1200TP-0280B-S5</a>		<ul style="list-style-type: none"> <li>1/2.7" 2Megapixel CMOS, Max 30fps@1080P</li> <li>HD and SD output switchable</li> <li>3.6mm Fixed lens (2.8mm, 6mm optional)</li> <li>Max. IR length 30m, Smart IR</li> <li>IP67, DC12V</li> </ul>	IRR 16,220,000	
		<a href="#">DH-HAC-HFW1200CP-0360B-S5</a>		<ul style="list-style-type: none"> <li>Max 30fps@1080P</li> <li>CVI/CVBS/AHD/TVI switcheable</li> <li>3.6mm fixed lens (2.8mm, optional)</li> <li>Max. IR length 30m, Smart IR</li> <li>IP67, DC12V</li> </ul>	IRR 13,470,000	
		<a href="#">DH-HAC-HFW1200CP-A-0280B-S5</a>		<ul style="list-style-type: none"> <li>&gt; CVI/CVBS/AHD/TVI switcheable</li> <li>&gt; 2.8mm fixed lens (2.8mm, optional)</li> <li>&gt; Built-in mic(A)</li> <li>&gt; Max. IR length 30m, Smart IR</li> <li>&gt; IP67, DC12V</li> </ul>	IRR 15,180,000	
		<a href="#">DH-HAC-HFW1200CP-A-0360B-S5</a>		<ul style="list-style-type: none"> <li>&gt; CVI/CVBS/AHD/TVI switcheable</li> <li>&gt; 3.6mm fixed lens (2.8mm, optional)</li> <li>&gt; Built-in mic(A)</li> <li>&gt; Max. IR length 30m, Smart IR</li> <li>&gt; IP67, DC12V</li> </ul>	IRR 15,180,000	
	210445	<a href="#">DH-HAC-HFW1200TLP-0360B-S5</a>		<ul style="list-style-type: none"> <li>1/2.7" 2Megapixel CMOS, 25/30fps@1080P, 50/60fps@720P</li> <li>3.6 &amp; 2.8mm fixed lens</li> <li>HD and SD output switchable, Support OSD Menu</li> <li>DWDR, Day/Night(ICR), AWB, AGC, BLC, HLC, 2D-DNR</li> <li>Max. IR LEDs length 40m, Smart IR, IP67, DC12V</li> </ul>	IRR 15,390,000	
		<a href="#">DH-HAC-HFW1200TLP-0280B-S5</a>		<ul style="list-style-type: none"> <li>1/2.7" 2Megapixel CMOS, 25/30fps@1080P, 50/60fps@720P</li> <li>2.8mm fixed lens</li> <li>HD and SD output switchable, Support OSD Menu</li> <li>DWDR, Day/Night(ICR), AWB, AGC, BLC, HLC, 2D-DNR</li> <li>Max. IR LEDs length 40m, Smart IR, IP67, DC12V</li> </ul>	IRR 15,390,000	
		<a href="#">DH-HAC-HFW1200CMP-A-0280B-S5</a>		<ul style="list-style-type: none"> <li>4 in 1 PRO series bullet camera with 30m Smart IR for outdoor use. CMOS 1/2.7" 2MP. Output 4 in 1 (HDCVI / HDTVI / AHD / 960H) switcheable by OSD or from DAHUA-498 control. Fixed 2.8 mm (101°) optics. 0.02 lux, 100 fsec. OSD, AWB, AGC, BLC, HLC, digital WDR, 2D-NR, digital Defog, Mirror, privacy masks. IP67, 3AXIS, 12V DC</li> </ul>	IRR 21,210,000	
		<a href="#">DH-HAC-HDW1200TRQP-0280B-S5</a>		<ul style="list-style-type: none"> <li>IP security camera. Placement supported: Outdoor. Connectivity technology: Wired.</li> <li>Mounting type: Ceiling, Color of product: White, Form factor: Spherical. Minimum illumination: 0.02 lx, Rotation angle: 360°, Lens angle of view, horizontal: 101°. Sensor type: CMOS</li> </ul>	IRR 12,690,000	
		<a href="#">DH-HAC-HFW1200TP-A-0280B-S5</a>		<ul style="list-style-type: none"> <li>1/2.7" Progressive Scan 2Megapixel CMOS, Max 30fps@1080P</li> <li>HD and SD output switchable</li> <li>Built-in mic</li> <li>2.8mm fixed lens</li> <li>Max. IR length 30m, Smart IR</li> <li>IP67, DC12V</li> </ul>	IRR 17,800,000	
		<a href="#">DH-HAC-HFW1200TP-A-0360B-S5</a>		<ul style="list-style-type: none"> <li>1/2.7" Progressive Scan 2Megapixel CMOS, Max 30fps@1080P</li> <li>HD and SD output switchable</li> <li>Built-in mic</li> <li>3.6mm fixed lens</li> <li>Max. IR length 30m, Smart IR</li> <li>IP67, DC12V</li> </ul>	IRR 17,800,000	
		<a href="#">DH-HAC-HFW1200RP(S)</a>		<ul style="list-style-type: none"> <li>1/2.7" 2Megapixel CMOS, 25/30fps@1080P, 25/30/50/60fps@720P</li> <li>3.6mm fixed lens HD and SD output switchable Day/Night(ICR)</li> <li>AWB, AGC, BLC, 2D-DNR, support OSD Menu</li> <li>Max. IR length 20m, Smart IR</li> <li>IP67</li> </ul>		
		<a href="#">DH-HAC-HFW1200TL-A</a>		<ul style="list-style-type: none"> <li>2MP HDCVI Quick-to-install IR Eyeball Camera</li> <li>CVI/CVBS/AHD/TVI switcheable</li> <li>3.6mm fixed lens (2.8mm, 6mm optional)</li> <li>Built-in mic</li> <li>Max. IR length 30m, Smart IR</li> <li>IP67, DC12V</li> </ul>	IRR 10,900,000	
		<a href="#">DH-HAC-HDW1200TLP-A-0280B-S5</a>		<ul style="list-style-type: none"> <li>1/2.7" 2Megapixel CMOS, 25/30fps@1080P, 50/60fps@720P</li> <li>3.6 &amp; 2.8mm fixed lens - built in mic</li> <li>HD and SD output switchable, Support OSD Menu</li> <li>DWDR, Day/Night(ICR), AWB, AGC, BLC, HLC, 2D-DNR</li> <li>Max. IR LEDs length 40m, Smart IR, IP67, DC12V</li> </ul>	IRR 16,660,000	
		<a href="#">DH-HAC-HDW1200TMQP-A-S5-0280B</a>		<ul style="list-style-type: none"> <li>Max 30fps@1080P</li> <li>Quick-to-install eyeball saves installation time</li> <li>CVI/CVBS/AHD/TVI switcheable</li> <li>2.7-12mm motorized lens</li> <li>Built-in mic(A)</li> <li>Max. IR length 60m, Smart IR</li> </ul>	IRR 20,750,000	
		<a href="#">DH-HAC-ME1500CP</a>		<ul style="list-style-type: none"> <li>SMP HDCVI Active Deterrence Camera</li> <li>&gt; Max 20fps@5MP</li> <li>&gt; HD and SD output switchable</li> <li>&gt; 2.8mm fixed lens (3.6mm optional), &gt; Max. IR length 20m, Smart IR</li> <li>&gt; Built-in PIR, 14.1m/110° detecting range/angle</li> <li>&gt; Active deterrence with white light &amp; siren, &gt; IP67, DC12V</li> </ul>		

		<a href="#">DH-HAC-ME1200EP-LED</a>		<ul style="list-style-type: none"> <li>2MP HDCVI Active Deterrence Camera - Max 30fps@1080P</li> <li>-HD and SD output switchable - 2.8mm/3.6mm fixed lens</li> <li>-10m/110°detecting range/angle</li> <li>-Max. IR length 20m, Smart IR</li> <li>-IP67, DC12V</li> </ul>		
250594		<a href="#">DH-HAC-HDW1200RP</a>		<ul style="list-style-type: none"> <li>2MP HDCVI IR Eyeball Camera</li> <li>- Max 30fps@1080P(1920x1080)</li> <li>-HD and SD output switchable</li> <li>-3.6mm fixed lens (2.8mm optional)</li> <li>-Max. IR length 20m, Smart IR - DC12V</li> </ul>		
		<a href="#">DH-HAC-HFW1200RP(S)</a>		<ul style="list-style-type: none"> <li>1/2.7" 2Megapixel CMOS25/30fps@1080P</li> <li>-25/30/50/60fps@720P</li> <li>3.6mm fixed lens HD and SD output switchableDay/Night(CR)</li> <li>AWB, AGC, BLC, 2D-SNRsupport OSD MenuMax</li> <li>IR length 20m, Smart IR</li> <li>IP67, DC12V , Casing: PlasticOperating</li> </ul>		
250444	210444	<a href="#">DH-HAC-HDW1200MP-0280B-S5</a>		<ul style="list-style-type: none"> <li>2MP HDCVI IR Eyeball Camera</li> <li>- Max 30fps@1080P(1920x1080)</li> <li>-HD and SD output switchable</li> <li>-3.6mm fixed lens (2.8mm, 6mm optional)</li> <li>-Max. IR length 30m, Smart IR - IP67, DC12V</li> </ul>	IRR 14,450,000	IRR 15,100,000
		<a href="#">DH-HAC-HDBW1200EP</a>		<ul style="list-style-type: none"> <li>2MP HDCVI IR Dome Camera</li> <li>-Max 30fps@1080P - IP67, IC11, DC12V</li> <li>-HD and SD output switchable</li> <li>-3.6mm fixed lens (2.8mm optional)</li> <li>-Max. IR length 30m, Smart IR</li> </ul>		
		<a href="#">DH-HAC-HDW1200EMP-A-0280B-S5</a>		<ul style="list-style-type: none"> <li>2MP HDCVI IR Eyeball Camera</li> <li>- Max 30fps@1080P(1920x1080)</li> <li>-HD and SD output switchable</li> <li>-3.6mm fixed lens (2.8mm, 6mm optional)</li> <li>-Max. IR length 50m, Smart IR - IP67, DC12V, Built in mic</li> </ul>	IRR 16,820,000	IRR 16,600,000
250500	210500	<a href="#">DH-HAC-HDW1209TLQP-LED-0360B</a>		<ul style="list-style-type: none"> <li>2MP Full-color Starlight HDCVI Eyeball Camera</li> <li>- Full-color starlight</li> <li>-20 m illumination distance, - Max. 30fps @ 1080P</li> <li>- CVI / CVBS / AHD / TVI switchable</li> <li>- Fixed lens (2.8 mm; 3.6 mm optional)</li> <li>- IP67, 12V ± 30% DC</li> </ul>	IRR 14,440,000	IRR 14,400,000
250581	210581	<a href="#">DH-HAC-HDW1209TLQP-A-LED-0280B</a>		<ul style="list-style-type: none"> <li>2MP Full-color Starlight HDCVI Eyeball Camera</li> <li>-&gt; Full-color starlight</li> <li>-&gt; 20 m illumination distance, - Max. 30fps @ 1080P</li> <li>-&gt; CVI / CVBS / AHD / TVI switchable</li> <li>-&gt; Fixed lens (2.8 mm; 3.6 mm optional)</li> <li>-&gt; IP67, 12V ± 30% DC</li> </ul>	IRR 15,580,000	IRR 15,900,000
		<a href="#">DH-HAC-HDW1230TLP-A</a>		<ul style="list-style-type: none"> <li>2MP Starlight HDCVI IR Eyeball Camera</li> <li>- Max. 30fps@1080P</li> <li>-HD and SD output switchable</li> <li>-3.6mm fixed lens (2.8mm, 6mm optional)</li> <li>-Max. IR length 40m, Smart IR - IP67, DC12V, Built in Mic</li> </ul>		
		<a href="#">DH-HAC-HDW1230EMP-A</a>		<ul style="list-style-type: none"> <li>2MP Starlight HDCVI IR Eyeball Camera</li> <li>- Max. 30fps@1080P</li> <li>-HD and SD output switchable, - Built-in mic</li> <li>-3.6mm fixed lens (2.8mm, 6mm optional)</li> <li>-Max. IR length 50m, Smart IR</li> <li>-IP67, DC12V</li> </ul>		
		<a href="#">DH-HAC-HDW1231TQP-A</a>		<ul style="list-style-type: none"> <li>2MP Starlight HDCVI Quick-to-install IR Eyeball Camera</li> <li>-&gt; Max 30 fps@1080P</li> <li>-&gt; Starlight, 130 dB true WDR, 3D NR</li> <li>-&gt; 3.6 mm fixed lens (2.8 mm, 6 mm optional)</li> <li>-&gt; CVI/CVBS/AHD/TVI switchable</li> <li>-&gt; Super Adapt</li> </ul>		
		<a href="#">DH-HAC-HFW1239TP-A-LED-0280B-S2</a>		<ul style="list-style-type: none"> <li>- Full-color starlight</li> <li>-40m LED distance</li> <li>-Max. 30fps@1080P</li> <li>-CVI/CVBS/AHD/TVI switchable</li> <li>-3.6mm fixed lens (2.8mm Optional)</li> <li>-IP67, 12V±30% DC</li> </ul>	IRR 22,300,000	
		<a href="#">DH-HAC-HFW1239TP-A-LED-0360B-S2</a>		<ul style="list-style-type: none"> <li>- Full-color starlight</li> <li>-40m LED distance</li> <li>-Max. 30fps@1080P</li> <li>- CVI/CVBS/AHD/TVI switchable, - Built-in mic</li> <li>-3.6mm fixed lens (2.8mm Optional)</li> <li>-IP67, 12V±30% DC</li> </ul>	IRR 22,300,000	
		<a href="#">DH-HAC-HDW1239TLQP-A-LED-0360B-S2</a>		<ul style="list-style-type: none"> <li>Dahua 4 in 1 Full-color fixed dome with 20 m Smart Light for outdoor use. 1 / 2.8 "CMOS of 2MP. 4 in 1 output (HDCVI / HDTV / AHD / 960H) switchable by UTC DAHUA-498 knob. 2.8 mm (107 °) fixed lens. 0.001 lux. Color 24h. OSD, AWB, AGC, BLC, HLC, WDR 130dB, 3D-NR, privacy masks.</li> </ul>	IRR 26,200,000	IRR 20,000,000
		<a href="#">DH-HAC-HDW1239TLQP-LED-0280B-S2</a>		<ul style="list-style-type: none"> <li>-24/7 color imaging, Max. 30 fps@1080p</li> <li>-20 m illumination distance</li> <li>-Super Adapt, 130 dB true WDR, 3D NR</li> <li>-Built-in mic (-A)</li> <li>-Quick-to-install eyeball saves installation time</li> <li>-3.6 mm fixed lens (2.8 mm optional)</li> <li>-CVI/CVBS/AHD/TVI switchable</li> <li>-IP67, 12V ± 30% DC</li> </ul>	IRR 18,850,000	
		<a href="#">DH-HAC-HDW1400MP</a>		<ul style="list-style-type: none"> <li>4MP HDCVI IR Eyeball Camera</li> <li>-Max 30fps@4MP - IP67, DC12V</li> <li>-HD and SD output switchable</li> <li>-3.6mm fixed lens (2.8mm, 6mm optional)</li> <li>-Max. IR length 30m, Smart IR</li> </ul>		
		<a href="#">DH-HAC-HDW1400EMP-A</a>		<ul style="list-style-type: none"> <li>-Max. 30fps@4MP(2560x1440)</li> <li>-Built-in mic - IP67, DC12V</li> <li>-HD and SD output switchable</li> <li>-3.6mm fixed lens (2.8mm, 6mm optional)</li> <li>-Max. IR length 50m, Smart IR</li> </ul>		
		<a href="#">DH-HAC-HDW1409TP-A-LED</a>		<ul style="list-style-type: none"> <li>4MP Full-color Starlight HDCVI Eyeball Camera</li> <li>- Full-color starlight</li> <li>-40 m LED distance, - Max. 30fps@4MP</li> <li>-CVI/CVBS/AHD/TVI switchable, - Built-in mic (-A)</li> <li>-3.6 mm fixed lens (2.8 mm optional)</li> <li>-IP67, 12V±30% DC</li> </ul>		
		<a href="#">DH-HAC-HDW1400TP-Z-A</a>		<ul style="list-style-type: none"> <li>-Max 30fps@4MP(2560x1440)</li> <li>-HD and SD output switchable</li> <li>-Built-in mic - IP67, DC12V</li> <li>-2.7-12mm motorized lens</li> <li>-Max. IR length 60m, Smart IR</li> </ul>		
		<a href="#">DH-HAC-HDW1500EMP-A</a>		<ul style="list-style-type: none"> <li>-Max. 20fps@5MP(2592x1944)</li> <li>-Built-in mic - IP67, DC12V</li> <li>-HD and SD output switchable</li> <li>-3.6mm fixed lens (2.8mm, 6mm optional)</li> <li>-Max. IR length 50m, Smart IR</li> </ul>		
		<a href="#">DH-HAC-HDW1509TP-A-LED-0280B-S2</a>		<ul style="list-style-type: none"> <li>SMP Full-color Starlight HDCVI Eyeball Camera</li> <li>- Full-color starlight</li> <li>-20 m LED distance, - Max. 20fps@5MP</li> <li>-CVI/CVBS/AHD/TVI switchable, - Built-in mic (-A)</li> <li>-3.6 mm fixed lens (2.8 mm optional)</li> <li>-IP67, 12V±30% DC</li> </ul>	IRR 39,450,000	
250552	210552	<a href="#">DH-HAC-HFW1509TLMP-A-LED</a>		<ul style="list-style-type: none"> <li>SMP Full-color HDCVI Bullet Camera -&gt; Max 25 fps@5MP (16:9 video output)</li> <li>-&gt; 120 dB true WDR, 3D NR 24/7 color imaging</li> <li>-&gt; 40 m illumination distance&gt; CVI/CVBS/AHD/TVI switchable</li> <li>-&gt; Built-in mic (-A)&gt; 3.6 mm fixed lens (2.8 mm optional)- IP67, 12</li> </ul>	IRR 36,170,000	
		<a href="#">DH-HAC-HFW1509TLP-A-LED-0360B-S2</a>		<ul style="list-style-type: none"> <li>SMP Full-color HDCVI Bullet Camera</li> <li>-&gt; Max 25 fps@5MP (16:9 video output)</li> <li>-&gt; 120 dB true WDR, 3DNR</li> <li>-&gt; 24/7 color imaging</li> <li>-&gt; 40 m illumination distance</li> <li>-&gt; CVI/CVBS/AHD/TVI switchable</li> <li>-&gt; Built-in mic</li> <li>-&gt; 3.6 mm fixed lens</li> <li>-IP67, 12V ± 30% DC</li> </ul>	IRR 37,660,000	
		<a href="#">DH-HAC-HFW1509TP-LED-0280B-S2</a>		<ul style="list-style-type: none"> <li>Dahua Full-Color 4-in-1 Camera. CMOS SMP. 5MP @ 25fps (CVI). Switchable 4-in-1 output. Color 24/7, 0.001 lux, Smart Light 20m. 2.8 mm lens. BLC, HLC, HLC-Pro, WDR 120dB, 3D-DNR. It incorporates a microphone. IP67, 3AXIS</li> </ul>	IRR 29,600,000	IRR 30,600,000















250551	210551	<a href="#">DH-HAC-HFW1509TLMP-LED</a>		<ul style="list-style-type: none"> <li>- Full-color starlight</li> <li>- 40 m LED distance</li> <li>- Max. 20fps@5MP</li> <li>- CVI/CVBS/AHD/TVI switchable</li> <li>- Built-in mic (-A)</li> <li>- 3.6 mm fixed lens</li> </ul>	IRR 19,820,000	IRR 29,500,000
		<a href="#">DH-HAC-HDW1509TLQP-LED-0360B-S2</a>		<ul style="list-style-type: none"> <li>SMP Full-color HDCVI Quick-to-install Eyeball Camera</li> <li>&gt; Max 25 fps@SMP (16.9 video output)- 120dB true WDR, 3D NR</li> <li>&gt; 24/7 color imaging- 20 m illumination distance</li> <li>&gt; CVI/CVBS/AHD/TVI switchable</li> <li>&gt; Built-in mic (-A)- 3.6 mm fixed lens (2.8 mm optional)</li> <li>&gt; IP67, 12 V DC</li> </ul>	IRR 30,560,000	IRR 28,400,000
		<a href="#">DH-HAC-HFW1509CP-LED-0280B-S2</a>		<ul style="list-style-type: none"> <li>120dB true WDR, 3D NR</li> <li>24/7 color imaging</li> <li>20 m illumination distance</li> <li>CVI/CVBS/AHD/TVI switchable</li> <li>2.8 mm fixed lens (2.8 mm optional)</li> <li>IP67</li> </ul>	IRR 28,260,000	
		<a href="#">DH-HAC-HDW1509TP-LED-0280B-S2</a>		<ul style="list-style-type: none"> <li>SMP Full-color Starlight HDCVI Eyeball Camera</li> <li>&gt; Full-color starlight</li> <li>&gt; 40 m LED distance</li> <li>&gt; Max. 20fps@5MP</li> <li>&gt; CVI/CVBS/AHD/TVI switchable</li> <li>&gt; 2.8 mm fixed lens (2.8 mm optional)</li> <li>&gt; IP67, 12V±30% DC</li> </ul>	IRR 33,630,000	
		<a href="#">DH-HAC-HDW1500TLMP-LED-0280B-S2</a>		<ul style="list-style-type: none"> <li>SMP Starlight HDCVI Quick-to-install IR Eyeball Camera</li> <li>&gt; Max 25 fps@SMP (16.9 video output)</li> <li>&gt; Quick-to-install eyeball saves installation time</li> <li>CVI/CVBS/AHD/TVI switchable- 2.8 mm fixed lens (2.8 mm optional)</li> <li>Max. IR length 30 m, Smart IR, IP67, DC12V</li> </ul>	IRR 23,450,000	IRR 23,800,000
		<a href="#">HAC-HDW1500TLMP</a>		<ul style="list-style-type: none"> <li>* The parameters and details below can only be applied to 1500-S2 series.</li> <li>* In order to use the SMP 16.9 HDCVI camera, the firmware of XVR must be upgraded to V4.001.0000001.0.R.200908 or later version.</li> <li>&gt; Max 25 fps@SMP (16.9 video output)</li> <li>&gt; CVI/CVBS/AHD/TVI switchable</li> </ul>		IRR 22,000,000
		<a href="#">DH-HAC-HDW1509TLQP-A-LED</a>		<ul style="list-style-type: none"> <li>SMP Full-color HDCVI Quick-to-install Eyeball Camera</li> <li>Max 25 fps@SMP (16.9 video output)</li> <li>120dB true WDR, 3D NR&gt; 24/7 color imaging</li> <li>20 m illumination distance, Built-in mic</li> <li>CVI/CVBS/AHD/TVI switchable, 3.6 mm fixed lens (2.8 mm optional)</li> <li>&gt; IP67, 12 V DC&gt; Quick-to-install eyeball saves installation time</li> </ul>	IRR 31,460,000	IRR 30,300,000
		<a href="#">HAC-HDW1509TLQP-LED</a>		<ul style="list-style-type: none"> <li>Max 25 fps@SMP (16.9 video output)</li> <li>- 120dB true WDR, 3D NR</li> <li>- 24/7 color imaging</li> <li>- 20 m illumination distance</li> <li>- CVI/CVBS/AHD/TVI switchable</li> <li>- Built-in mic (-A)</li> </ul>	IRR 34,930,000	IRR 28,400,000
		<a href="#">DH-HAC-HDW1500TP-Z-A</a>		<ul style="list-style-type: none"> <li>- Max. 20fps@SMP (25±20%±194k), 1/2.77" Progressive CMOS</li> <li>- 20fps@SMP, 25/30fps@4MP, 25/30fps@1080P</li> <li>- HD and SD output switchable- Built-in mic</li> <li>- 2.7-12mm motorized lens - IP67, DC12V</li> <li>- Max. IR length 60m, Smart IR</li> </ul>		
		<a href="#">DH-HAC-HFW1200RP</a>		<ul style="list-style-type: none"> <li>- 2MP HDCVI IR Bullet Camera</li> <li>- Max 30fps@1080P (1920×1080)</li> <li>- HD and SD output switchable</li> <li>- 3.6mm fixed lens (2.8mm, 6mm optional)</li> <li>- Max. IR length 20m, Smart IR - IP67, DC12V</li> </ul>		
		<a href="#">DH-HAC-HFW1200SP-0360B-S5</a>		<ul style="list-style-type: none"> <li>Max 30fps@1080P (1920×1080)</li> <li>- 2MP HDCVI IR Bullet Camera</li> <li>- HD and SD output switchable</li> <li>- 3.6mm fixed lens (2.8mm, 6mm optional)</li> <li>- Max. IR length 30m, Smart IR - IP67, DC12V</li> </ul>	IRR 15,790,000	IRR 14,550,000
		<a href="#">DH-HAC-HFW1230TLP</a>		<ul style="list-style-type: none"> <li>2MP Starlight HDCVI IR Bullet Camera</li> <li>- Max. 30fps@1080P</li> <li>- HD and SD output switchable</li> <li>- 3.6mm fixed lens (2.8mm, 6mm optional)</li> <li>- Max. IR length 40m, Smart IR - IP67, DC12V</li> </ul>		
		<a href="#">DH-HAC-HFW1230TP</a>		<ul style="list-style-type: none"> <li>2MP Starlight HDCVI IR Bullet Camera</li> <li>- Max. 30fps@1080P, Starlight</li> <li>- HD and SD output switchable</li> <li>- 3.6mm fixed lens (2.8mm, 6mm optional)</li> <li>- Max. IR length 30m, Smart IR - IP67, DC12V</li> </ul>		
		<a href="#">DH-HAC-HFW1230THP-18</a>		<ul style="list-style-type: none"> <li>2MP Starlight HDCVI IR Bullet Camera</li> <li>- Max. 30fps@1080P</li> <li>- HD and SD output switchable</li> <li>- 3.6mm fixed lens (6mm, 8mm optional)</li> <li>- Max. IR length 80m, Smart IR</li> <li>- IP67, DC12V</li> </ul>		
		<a href="#">HAC-HFW1231TMP-18-A(s)</a>		<ul style="list-style-type: none"> <li>2MP HDCVI IR Bullet Camera-&gt; Max 30 fps@1080P</li> <li>2MP Starlight HDCVI IR Bullet Camera</li> <li>&gt; 3.6 mm fixed lens (2.8 mm, 6 mm optional)Day/Night Auto switch by ICR</li> <li>6LC BLC WDR/HLC-WDR 130 dB@IP67, DC 12 V</li> </ul>		
		<a href="#">HAC-HFW1200THP-14-0280B-S5</a>		<ul style="list-style-type: none"> <li>2MP HDCVI IR Bullet Camera</li> <li>- Max 30fps@1080P</li> <li>- HD and SD output switchable</li> <li>- 3.6mm fixed lens (2.8mm, 6mm optional)</li> <li>- Max. IR length 40m, Smart IR - IP67, DC12V</li> </ul>	IRR 12,310,000	IRR 20,000,000
		<a href="#">DH-HAC-HFW1200THP-18-0360B-S5</a>		<ul style="list-style-type: none"> <li>2MP HDCVI IR Bullet Camera</li> <li>- Max 30fps@1080P</li> <li>- HD and SD output switchable</li> <li>- 3.6mm fixed lens (2.8mm, 6mm optional)</li> <li>- Max. IR length 80m, Smart IR - IP67, DC12V</li> </ul>	IRR 19,020,000	IRR 22,000,000
250433		<a href="#">DH-HAC-HFW1200TP-S5</a>		<ul style="list-style-type: none"> <li>2MP HDCVI IR Bullet Camera</li> <li>- Max 30fps@1080P</li> <li>- HD and SD output switchable</li> <li>- 3.6mm fixed lens (2.8mm, 6mm optional)</li> <li>- Max. IR length 30m, Smart IR - IP67, DC12V</li> </ul>		
250484	210484	<a href="#">DH-HAC-HFW1200TP-A</a>		<ul style="list-style-type: none"> <li>2MP HDCVI IR Bullet Camera</li> <li>- Max 30fps@1080P</li> <li>- HD and SD output switchable</li> <li>- 3.6mm fixed lens (6mm, 8mm optional)</li> <li>- Max. IR length 30m, Smart IR - IP67, DC12V</li> </ul>	IRR 16,740,000	
250441	210441	<a href="#">DH-HAC-HFW1200DP-0360B-S5</a>		<ul style="list-style-type: none"> <li>Max 30fps@1080P (1920×1080)</li> <li>- HD and SD output switchable</li> <li>- 3.6mm fixed lens (6mm, 8mm optional)</li> <li>- Max. IR length 80m, Smart IR - IP67, DC12V</li> </ul>	IRR 20,230,000	IRR 18,500,000
		<a href="#">DH-HAC-HFW1230DP(s)</a>		<ul style="list-style-type: none"> <li>Starlight</li> <li>- Max. 30fps@1080P</li> <li>- HD and SD output switchable</li> <li>- 3.6mm fixed lens (6mm, 8mm optional)</li> <li>- Max. IR length 80m, Smart IR</li> <li>- IP67, DC12V</li> </ul>		
		<a href="#">DH-HAC-HFW1200RP-Z-IRE6</a>		<ul style="list-style-type: none"> <li>Max 30fps@1080P (1920×1080)</li> <li>- HD and SD output switchable</li> <li>- 2.7-12mm Motorized lens</li> <li>- Max. IR length 60m, Smart IR - IP67, DC12V</li> </ul>	IRR 33,450,000	IRR 31,000,000
250609	210609	<a href="#">DH-HAC-HFW1209CP-LED</a>		<ul style="list-style-type: none"> <li>Full-color starlight</li> <li>- 20 m illumination distance</li> <li>- Max. 30fps@1080P - CVI/CVBS/AHD/TVI switchable</li> <li>- Fixed lens (2.8 mm; 3.6 mm optional)</li> <li>- IP67, 12V±30% DC</li> </ul>	IRR 13,790,000	IRR 16,400,000
		<a href="#">DH-HAC-HFW1209CP-A-LED-0280B-S2</a>		<ul style="list-style-type: none"> <li>24/7 color imaging</li> <li>- 20 m illumination distance</li> <li>- Max. 30 fps@1080P</li> <li>- CVI/CVBS/AHD/TVI switchable</li> <li>- Fixed lens (2.8 mm; 3.6 mm optional)</li> <li>- IP67, 12V±30% DC</li> </ul>	IRR 16,550,000	

		HAC-HFW1239CP-LED		<ul style="list-style-type: none"> <li>24/7 color imaging, Max. 30fps@1080p</li> <li>-20 m illumination distance</li> <li>-Super Adapt, 130 dB true WDR, 3D NR</li> <li>- Built-in mic (-A)</li> <li>-3.6 mm fixed lens (2.8 mm optional)</li> <li>-CVI/CVBS/AHD/TVI switchable</li> </ul>		IRR 22,500,000
		DH-HAC-HDW1209TQP-LED-0280B-S2		<ul style="list-style-type: none"> <li>2MP Full-color HDCVI Quick-to-install Eyeball Camera</li> <li>&gt; Full-color starlight</li> <li>&gt; 20 m illumination distance</li> <li>&gt; Max. 30fps@1080P</li> <li>&gt; Quick-to-install eyeball saves installation time</li> <li>&gt; CVI/CVBS/AHD/TVI switchable</li> <li>&gt; Fixed lens (2.8 mm, 3.6 mm optional)</li> <li>&gt; IP67, 12V±30% DC</li> </ul>	IRR 15,430,000	
		HAC-HDW1209TLQP-A-LED		<ul style="list-style-type: none"> <li>2MP Full-color HDCVI Quick-to-install Eyeball Camera</li> <li>&gt; Full-color starlight</li> <li>&gt; 20 m illumination distance</li> <li>&gt; Max. 30fps@1080P</li> <li>&gt; Built-in mic (-A)</li> <li>&gt; Quick-to-install eyeball saves installation time</li> <li>&gt; CVI/CVBS/AHD/TVI switchable</li> <li>&gt; Fixed lens (2.8 mm, 3.6 mm optional)</li> </ul>	IRR 18,180,000	
250444	210444	HAC-HDW1200MP-S5		<ul style="list-style-type: none"> <li>Dahua DH-HAC-HDW1200MP-0280B-S5 Dahua 4 in 1 fixed dome with...</li> <li>Dahua 4 in 1 fixed dome with Smart IR 30m for outdoor use. CMOS 1/2.7" 2MP. Output 4 in 1 by a BNC port. Fixed optics 2.8 mm (101), 0.02 lux. ICR filter. OSD, AWB, AGC, BLC, HLC, digital WDR, 2D-NR, Mirror, privacy masks. 3AXIS, 12V DC.</li> </ul>	IRR 14,710,000	IRR 15,100,000
		DH-HAC-HFW1200CMP-0280B-S5		<ul style="list-style-type: none"> <li>2 MP HDCVI Bullet Camera with IR illumination</li> <li>&gt; Up to 30fps @ 1080P</li> <li>&gt; Switchable CVI / CVBS / AHD / TVI outputs</li> <li>&gt; Fixed lens 3.6mm (2.8mm optional), &gt; Built-in microphone</li> <li>&gt; Max. IR illumination range 30m, intelligent IR illumination</li> <li>&gt; IP67, DC 12V</li> </ul>	IRR 14,810,000	
		DH-HAC-HFW1200CMP-A		<ul style="list-style-type: none"> <li>2 MP HDCVI Bullet Camera with IR illumination</li> <li>&gt; Up to 30fps @ 1080P</li> <li>&gt; Switchable CVI / CVBS / AHD / TVI outputs</li> <li>&gt; Fixed lens 3.6mm (2.8mm optional), &gt; Built-in microphone (-A)</li> <li>&gt; Max. IR illumination range 30m, intelligent IR illumination</li> <li>&gt; IP67, DC 12V</li> </ul>	IRR 21,210,000	
250633	210633	DH-HAC-HFW1209CMP-LED-0280B		<ul style="list-style-type: none"> <li>2MP Full-color HDCVI Bullet Camera</li> <li>&gt; 24/7 color imaging</li> <li>&gt; 20 m illumination distance</li> <li>&gt; Max. 30 fps @ 1080p, &gt; Built-in mic (-A)</li> <li>&gt; CVI / CVBS / AHD / TVI switchable</li> <li>&gt; Fixed lens (2.8 mm, 3.6 mm optional), &gt; IP67, 12V ± 30% DC</li> </ul>	IRR 15,860,000	
		DH-HAC-HFW1231RP-Z-A		<ul style="list-style-type: none"> <li>2MP Starlight HDCVI IR Bullet Camera</li> <li>&gt; Max. 30 fps@1080P</li> <li>&gt; Starlight, 130dB true WDR, 3D NR</li> <li>&gt; Auto focus, 2.7mm-12mm motorized lens</li> <li>&gt; CVI/CVBS/AHD/TVI switchable Super Adapt</li> <li>&gt; Built-in mic- Max. IR length 80 m, Smart IR</li> </ul>	IRR 42,830,000	
		DH-HAC-HFW1231CMP		<ul style="list-style-type: none"> <li>2MP Starlight HDCVI IR Bullet Camera</li> <li>&gt; Max 30 fps@1080P</li> <li>&gt; Starlight, 130 dB true WDR, 3D NR</li> <li>&gt; 3.6 mm fixed lens (2.8 mm optional)</li> <li>&gt; CVI/CVBS/AHD/TVI switchable</li> <li>&gt; Super Adapt</li> </ul>		
		DH-HAC-HFW1231TMP-IR-A		<ul style="list-style-type: none"> <li>2MP Starlight HDCVI IR Bullet Camera</li> <li>&gt; Max 30 fps@1080P</li> <li>&gt; Starlight, 130 dB true WDR, 3D NR</li> <li>&gt; 3.6 mm fixed lens (2.8 mm, 6 mm, 8 mm optional)</li> <li>&gt; CVI/CVBS/AHD/TVI switchable</li> <li>&gt; Super Adapt</li> </ul>		
250454	210454	DH-HAC-HFW1239TP-LED		<ul style="list-style-type: none"> <li>Full-color starlight</li> <li>-20m LED distance</li> <li>-Max. 30fps@1080P, CVI/CVBS/AHD/TVI Switchable</li> <li>-3.6mm fixed lens (2.8mm Optional)</li> <li>-IP67, DC12V±30% DC</li> </ul>	IRR 15,080,000	IRR 23,600,000
		DH-HAC-HFW1239TP-A-LED-0280B-S2		<ul style="list-style-type: none"> <li>Full-color starlight</li> <li>-20m LED distance - Max. 30fps@1080P</li> <li>-CVI/CVBS/AHD/TVI Switchable</li> <li>-Built-in mic, -3.6mm fixed lens (2.8mm Optional)</li> <li>-IP67, DC12V±30% DC</li> </ul>	IRR 22,300,000	
		DH-HAC-HFW1239TMP-A-LED-0360B-S2		<ul style="list-style-type: none"> <li>Full-color starlight</li> <li>-40m LED distance</li> <li>-Max. 30fps@1080P</li> <li>-CVI/CVBS/AHD/TVI Switchable</li> <li>-Built-in mic(-A)</li> <li>-3.6mm fixed lens (2.8mm Optional)</li> <li>-IP67, 12V±30% DC</li> </ul>	IRR 28,270,000	
		DH-HAC-HFW1400TLP		<ul style="list-style-type: none"> <li>Max. 30fps@4MP</li> <li>-HD and SD output switchable</li> <li>-3.6mm fixed lens (2.8mm, 6mm optional)</li> <li>-Max. IR length 40m, Smart IR - IP67, DC12V</li> </ul>		
		DH-HAC-HFW1400TP-IR		<ul style="list-style-type: none"> <li>4MP HDCVI IR Bullet Camera</li> <li>-Max. 30fps@4MP - IP67, DC12V</li> <li>-HD and SD output switchable</li> <li>-3.6mm fixed lens (6mm, 8mm optional)</li> <li>-Max. IR length 80m, Smart IR</li> </ul>		
250429		DH-HAC-HFW1400TP-0280B-S3		<ul style="list-style-type: none"> <li>Max. 30fps@4MP(2560x1440)</li> <li>-HD and SD output switchable</li> <li>-3.6mm fixed lens (2.8mm, 6mm optional)</li> <li>-Max. IR length 30m, Smart IR - IP67, DC12V</li> </ul>	IRR 23,540,000	
		DH-HAC-HFW1400TP-A		<ul style="list-style-type: none"> <li>4MP HDCVI IR Bullet Camera</li> <li>-Max. 30fps@4MP</li> <li>-Built-in mic -IP67, DC12V, -HD and SD output switchable</li> <li>-3.6mm fixed lens (2.8mm, 6mm optional), -Max. IR length 30m, Smart IR</li> </ul>		
		DH-HAC-HFW1400SP		<ul style="list-style-type: none"> <li>Max 30fps@4MP(2560x1440)</li> <li>-HD and SD output switchable</li> <li>-3.6mm fixed lens (2.8mm, 6mm optional)</li> <li>-Max. IR length 30m, Smart IR</li> <li>-IP67, DC12V</li> </ul>		
		DH-HAC-HFW1400RP(s)		<ul style="list-style-type: none"> <li>Max 30fps@4MP(2560x1440)</li> <li>-HD and SD output switchable</li> <li>-2.7-12mm Motorized lens</li> <li>-Max. IR length 60m, Smart IR</li> <li>-IP67, DC12V</li> </ul>		
		DH-HAC-HFW1500CMP-0360B-S2		<ul style="list-style-type: none"> <li>HAC-HFW1500CMP-A-POC</li> <li>5MP Starlight HDCVI POC IR Bullet Camera</li> <li>* In order to use the SMP 16-9 HDCVI camera, the firmware of XVR must be upgraded to V4.001.0000001.0.R.200908 or later version.</li> <li>&gt;The parameters and datasheets below can only be applied to 1500-S2 series.&gt; Max 25 fps@5MP (16:9 video output)&gt; CVI/CVBS/AHD/TVI switchable&gt; 3.6 mm fixed lens (2.8 mm optional)&gt; Max. IR length 30m, Smart IR&gt; Built-in mic- IP67, POC (only CVI/12V±30% D</li> </ul>	IRR 23,540,000	IRR 23,600,000
		HAC-HFW1500CP		<ul style="list-style-type: none"> <li>Max 25 fps@5MP (16:9 video output)</li> <li>-CVI/CVBS/AHD/TVI switchable</li> <li>-3.6 mm fixed lens (2.8 mm optional)</li> <li>-Max. IR length 30 m, Smart IR</li> <li>- Built-in mic(-A)</li> <li>-IP67, 12V DC</li> </ul>	IRR 21,000,000	






		<a href="#">HAC-HFW1500CMP-A</a>		<ul style="list-style-type: none"> <li>-Max 25 fps@5MP (16:9 video output)</li> <li>-CVI/CVBS/AHD/TVI switchable</li> <li>-3.6 mm fixed lens (2.8 mm optional)</li> <li>-Max. IR length 30m, Smart IR</li> <li>-Built-in mic(A)</li> <li>-IP67, DC12V</li> </ul>		IRR 25,400,000
		<a href="#">DH-HAC-HFW1500TLP</a>		<p>HAC-HFW1500TL SMP Starlight HDCVI IR Bullet Camera</p> <p>* The parameters and datasheets below can only be applied to 1500-S2 series * In order to use the SMP 16-9 HDCVI camera, the firmware of XVR must be upgraded to V4.001.0000001.0.R.200908 or later version-&gt; Max 25 fps@5MP (16:9 video output) &gt; CVI/CVBS/AHD/TVI switchable&gt; 3.6 mm fixed lens (2.8 mm optional)</p>	IRR 15,870,000	
		<a href="#">DH-HAC-HFW1500SLP</a>		<ul style="list-style-type: none"> <li>-1/2.7" Progressive CMOS</li> <li>-HD and SD output switchable</li> <li>-Day/Night (ICR), BLC / HLC / DWDR / AGC</li> <li>-3.6mm fixed lens (2.8mm, 6mm optional)</li> <li>-Max. IR length 30m, Smart IR: IP67, DC12</li> <li>20fps@5MP, 25/30fps@4MP, 25/30fps@1080P</li> </ul>		
		<a href="#">DH-HAC-HFW1500RP-Z-IRE6-A</a>		<ul style="list-style-type: none"> <li>-Max. 20fps@5MP(2592*1944), 1/2.7" Progressive CMOS</li> <li>-20fps@5MP, 25/30fps@4MP, 25/30fps@1080P</li> <li>-HD and SD output switchable - Built-in mic</li> <li>-2.7-12mm motorized lens - IP67, DC12V</li> <li>-Max. IR length 60m, Smart IR</li> </ul>	IRR 30,150,000	IRR 43,800,000
		<a href="#">DH-HAC-HUM3201BP-B</a>		<p>2MP Starlight HDCVI Pinhole Camera Starlight, 120dB true WDR, 30NR, Max 30fps@1080P, HD and SD output switchable, 3.6mm fixed lens (2.8mm optional), DC12V</p>		
<b>COOPER</b>						
		<a href="#">DH-HAC-B2A51P-0360B-S2</a>		<p>SMP HDCVI IR Eyeball Camera, 1/2.7" 5Megapixel CMOS 20fps@5MP, 25/30fps@4MP &amp; @1080P (16:9 video output) 3.6mm &amp; 2.8mm fixed lens DWR, Day/Night(ICR), AWB, AGC, BLC, HLC, 2DNR HD and SD output switchable, Support OSD Menu Max. IR length 20m, Smart IR, IP67, DC12V, Casing: Aluminium</p>	IRR 18,300,000	
250705		<a href="#">HAC-B2A51P-0280B-S2</a>		<p>SMP HDCVI Fixed IR Bullet Camera 20m -Max. 25 fps@5MP (16:9 video output) -CVI/CVBS/AHD/TVI switchable -2.8 mm fixed lens -Max. IR length 20 m, Smart IR -IP67, DC12V</p>	IRR 18,300,000	IRR 17,200,000
		<a href="#">DH-HAC-B2A21P-0360B</a>		<p>1/2.7" 2Megapixel CMOS 25/30fps@1080P, 25/30/50/60fps@720P, 3.6mm fixed lens HD and SD output switchable, Support OSD Menu DWR, Day/Night(ICR), AWB, AGC, BLC, HLC, 2DNR Max. IR length 20m, Smart IR, IP67, DC12V, Casing: Aluminium</p>	IRR 12,330,000	
250425	210425	<a href="#">DH-HAC-B2A21P-0280B</a>		<p>1/2.7" 2Megapixel CMOS, 25/30fps@1080P, 50/60fps@720P 2.8mm fixed lens HD and SD output switchable, Support OSD Menu DWR, Day/Night(ICR), AWB, AGC, BLC, HLC, 2DNR Max. IR length 20m, Smart IR, IP67, DC12V, Casing: Aluminium</p>	IRR 12,330,000	IRR 8,600,000
250360	210360	<a href="#">DH-HAC-T2A21P-0280B</a>		<p>1/2.7" 2Megapixel CMOS, 25/30fps@1080P, 50/60fps@720P 2.8mm fixed lens HD and SD output switchable, Support OSD Menu DWR, Day/Night(ICR), AWB, AGC, BLC, HLC, 2DNR Max. IR length 20m, Smart IR, IP67, DC12V, Casing: Aluminium</p>	IRR 12,800,000	IRR 11,460,000
		<a href="#">DH-HAC-B2A21P-0360B</a>		<p>1/2.7" 2Megapixel CMOS, 25/30fps@1080P, 50/60fps@720P 3.6mm fixed lens HD and SD output switchable, Support OSD Menu DWR, Day/Night(ICR), AWB, AGC, BLC, HLC, 2DNR Max. IR length 20m, Smart IR, IP67, DC12V, Casing: Aluminium</p>	IRR 12,800,000	IRR 11,460,000
250425	210425	<a href="#">DH-HAC-T1A21P-0280B</a>		<p>1/2.7" 2Megapixel CMOS, 25/30fps@1080P, 50/60fps@720P 2.8mm fixed lens HD and SD output switchable, Support OSD Menu DWR, Day/Night(ICR), AWB, AGC, BLC, HLC, 2DNR Max. IR length 20m, Smart IR, Casing: Plastic, DC12V</p>	IRR 9,900,000	IRR 9,800,000
250443	210443	<a href="#">DH-HAC-T1A21P-0360B</a>		<p>1/2.7" 2Megapixel CMOS, 25/30fps@1080P, 50/60fps@720P 2.8mm &amp; 3.6 fixed lens HD and SD output switchable, Support OSD Menu DWR, Day/Night(ICR), AWB, AGC, BLC, HLC, 2DNR Max. IR length 20m, Smart IR, Casing: Plastic, DC12V</p>		IRR 9,800,000
		<a href="#">DH-HAC-T1A41P-S2</a>		<p>4MP HDCVI IR Eyeball Camera -Max. 30fps@4MP (2560*1440) -HD and SD output switchable -3.6mm fixed lens (2.8mm, 6mm optional) -Max. IR length 20m, Smart IR, DC12V</p>	IRR 13,520,000	
		<a href="#">DH-HAC-T1A51P</a>		<p>SMP HDCVI Fixed IR Eyeball Camera &gt;Max. 25 fps@5MP (16:9 video output) &gt; CVI/CVBS/AHD/TVI switchable &gt; 3.6 mm fixed lens (2.8 mm optional) &gt;Max. IR length 20 m, Smart IR &gt; DC12V</p>		IRR 16,400,000
		<a href="#">DH-HAC-T2A41P-0280B-S2</a>		<ul style="list-style-type: none"> <li>-Max. 30fps@4MP(2560*1440)</li> <li>-HD and SD output switchable</li> <li>-3.6mm Fixed lens (2.8mm,6mm optional)</li> <li>-Max. IR length 20m, Smart IR - IP67, DC12V</li> </ul>	IRR 16,490,000	
	210584	<a href="#">DH-HAC-T2A51P-S2</a>		<p>SMP HDCVI IR Eyeball Camera -Max. 20fps@5MP (2592*1944) -HD and SD output switchable -3.6mm fixed lens (2.8mm,6mm optional) -Max. IR length 20m, Smart IR. IP67, DC12V</p>	IRR 19,130,000	
250434		<a href="#">DH-HAC-B1A21P-0360B</a>		<ul style="list-style-type: none"> <li>-2MP HDCVI IR Bullet Camera</li> <li>-Max. 30fps@1080P (1920*1080)</li> <li>-HD and SD output switchable</li> <li>-3.6mm fixed lens (2.8mm, 6mm optional)</li> <li>-Max. IR length 20m, Smart IR. IP67, DC12V</li> </ul>	IRR 10,060,000	IRR 9,500,000
		<a href="#">DH-HAC-B1A21P-0280B</a>		<ul style="list-style-type: none"> <li>-2MP HDCVI IR Bullet Camera</li> <li>-Max. 30fps@1080P (1920*1080)</li> <li>-HD and SD output switchable</li> <li>-2.8mm fixed lens (2.8mm, 6mm optional)</li> <li>-Max. IR length 20m, Smart IR. IP67, DC12V</li> </ul>	IRR 10,060,000	
		<a href="#">DH-HAC-T1A41P-0280B-S2</a>		<p>4MP HDCVI IR Bullet Camera -Max. 30fps@4MP (2560*1440) -HD and SD output switchable -3.6mm fixed lens (6mm optional) -Max. IR length 20m, Smart IR. IP67, DC12V</p>	IRR 13,520,000	
		<a href="#">DH-HAC-B2A41P-0280B-S2</a>		<ul style="list-style-type: none"> <li>-Max. 30fps@4MP</li> <li>-HD and SD output switchable</li> <li>-3.6mm Fixed lens (2.8mm,6mm optional)</li> <li>-Max. IR length 20m, Smart IR</li> <li>-IP67, DC12V</li> </ul>	IRR 17,730,000	
		<a href="#">HAC-B1A51P-0280B-S2</a>		<p>SMP HDCVI Fixed IR Bullet Camera * The parameters and datasheets below can only be applied to AS1-S2 series * In order to use the SMP 16-9 HDCVI camera, the firmware of XVR must be upgraded to V4.001.0000001.0.R.200908 or later version-&gt; Max. 25 fps@5MP (16:9 video output) &gt; CVI/CVBS/AHD/TVI switchable&gt; 3.6 mm fixed lens (2.8 mm optional) &gt; Max. IR length 20 m, Smart IR- IP67, DC12V</p>	IRR 12,700,000	IRR 16,300,000

		HAC-D1A51P		<ul style="list-style-type: none"> <li>- Max. 20fps@5MP - HD and SD output switchable - 3.6mm fixed lens (2.8mm optional) - Max. IR length 20m, Smart IR - DC12V</li> </ul>		
		DH-HAC-B2A41P		<ul style="list-style-type: none"> <li>- Max. 30fps@4MP(2560x1440)</li> <li>- HD and SD output switchable</li> <li>- 3.6mm fixed lens (2.8mm, 6mm optional)</li> <li>- Max. IR length 20m, Smart IR - IP67, DC12V</li> </ul>	IRR 17,730,000	
		DH-SD4221S-HC-LA		<ul style="list-style-type: none"> <li>- 2MP 32x Starlight HDCVI PTZ Camera</li> <li>- &gt; 1/2.8" 2Megapixel STARVIS™ CMOS</li> <li>- &gt; Powerful 15x optical zoom</li> <li>- &gt; Starlight technology</li> <li>- &gt; 120dB true WDR, 3D DNR</li> <li>- &gt; Max. 25/30fps@1080P, 25/30/50/60fps@720P</li> </ul>	IRR 114,760,000	
		DH-SD59230I-HC		<ul style="list-style-type: none"> <li>- 1/2.8" 2Megapixel STARVIS™ CMOS</li> <li>- Powerful 30x optical zoom</li> <li>- Starlight technology</li> <li>- 120dB true WDR, 3D DNR</li> <li>- Max. 25/30fps@1080P, 25/30/50/60fps@720P</li> <li>- IR distance up to 150m - IP66</li> </ul>		
		DH-SD59232-HC-LA		<ul style="list-style-type: none"> <li>- 2MP 32x Starlight IR PTZ HDCVI Camera</li> <li>- &gt; 1/2.8" 2Megapixel STARVIS™ CMOS</li> <li>- &gt; Powerful 32X optical zoom</li> <li>- &gt; Starlight technology</li> <li>- &gt; 120dB true WDR, 3D DNR</li> <li>- &gt; Max. 25/30fps@1080P, 25/30/50/60fps@720P</li> </ul>	IRR 238,950,000	
		DH-SD59430I-HC		<ul style="list-style-type: none"> <li>- 1/3" 4Megapixel CMOS</li> <li>- Powerful 30x optical zoom</li> <li>- 120dB true WDR, 3D DNR</li> <li>- Max. 25/30fps@4M/1080P, 25/30/50/60fps@720P</li> <li>- IR distance up to 100m - IP66</li> </ul>		
<b>XVR</b>						
		<a href="#">DH-XVR1A08</a>		<ul style="list-style-type: none"> <li>- 8 Channel Penta-brid 1080N/720P Cooper 1U</li> <li>- H.264 video compression</li> <li>- Supports HDCV/AHD/TVI/CVBS/IP video inputs</li> <li>- Max 10 channels IP camera inputs, each channel up to 5MP; Max 40Mbps Incoming Bandwidth</li> <li>- Long transmission distance over coax cable</li> <li>- Supports 1 SATA HDD, up to 6TB</li> </ul>	IRR 23,100,000	
		<a href="#">DH-XVR1A04</a>		<ul style="list-style-type: none"> <li>- 4Channel Penta-brid 1080N/720P Cooper 1U</li> <li>- H.264 video compression</li> <li>- Supports HDCV/AHD/TVI/CVBS/IP video inputs</li> <li>- Max 5 channels IP camera inputs, each channel up to 2MP; Max 20Mbps Incoming Bandwidth</li> <li>- Long transmission distance over coax cable</li> <li>- Supports 1 SATA HDD, up to 6TB</li> </ul>		
250457	210457	<a href="#">DH-XVR1B04-I</a>		<ul style="list-style-type: none"> <li>- 4 Channel Penta-brid 1080N/720P Real-time WisSense AI XVR</li> <li>- H.265+/H.265/H.264+/H.264 dual-stream video compression</li> <li>- Pentabrid (IP+CVI+AHD+TVI+CVBS) N+M (4+1 IP up to 2MP(20 Mbps), 4CH 1/6 Playback, HDMI, VGA, simultaneous video output</li> <li>- 1 SATA port, up to 6 TB capacity, 2*USB 2.0, 10/100 Mbps LAN Interface, P2P Support</li> <li>- SMD Plus, Full channel AI-Coding, Human/Vehicle Classification</li> <li>- 15,900,000, 70 DH-XVR1A08, 8CH Penta-brid 1080N/720P noneReal-Time Cooper Recorder</li> </ul>	IRR 26,660,000	
250402	210402	<a href="#">DH-XVR1B08-I</a>		<ul style="list-style-type: none"> <li>- 8 Channel Penta-brid 1080N/720P Real-time WisSense AI XVR</li> <li>- H.265+/H.265/H.264+/H.264 dual-stream video compression</li> <li>- Pentabrid (IP+CVI+AHD+TVI+CVBS) N+M (8+2 IP up to 6MP(40 Mbps), 4CH: 1/4/9 Playback</li> <li>- HDMI, VGA, simultaneous video output, 1 SATA port, up to 6 TB capacity</li> <li>- 2*USB 2.0, 10/100 Mbps LAN Interface, P2P Support, 4ch SMD Plus, Full channel AI-Coding, Human/Vehicle Classification</li> </ul>	IRR 33,200,000	IRR 31,000,000
250450	210450	<a href="#">DH-XVR1B16-I</a>		<ul style="list-style-type: none"> <li>- 16CH Penta-brid 1080N/720P None Real-Time Cooper Recorder</li> <li>- H.265+/H.265 dual-stream video compression</li> <li>- 1st channel 1080N/720P@25fps, others 1080N/720P@15fps</li> <li>- 16CH: 1/4/9/16 Playback, Pentabrid (IP+CVI+AHD+TVI+CVBS) N+M (16+2 IP up to 6 MP(72 Mbps))</li> <li>- 1 Audio Input / 1 Audio Output, 1 SATA Port, Up to 6TB, HDMI, VGA, simultaneous video output</li> <li>- 2 USB 2.0, 10/100 Mbps LAN Interface, P2P Support</li> </ul>	IRR 62,970,000	IRR 61,000,000
		<a href="#">DH-XVR1B16H</a>		<ul style="list-style-type: none"> <li>- 16 Channel Penta-brid 4M-A/1080P Cooper 1U 1HDD Digital Video Recorder</li> <li>- H.265+/H.265 dual-stream video compression</li> <li>- Supports HDCV/AHD/TVI/CVBS/IP video inputs</li> <li>- Max 24 channels IP camera inputs, each channel up to 6MP; Max 96Mbps incoming bandwidth, Long transmission distance over coax cable</li> <li>- Supports 1 SATA HDD, up to 6TB, Smart Search and Intelligent Video System</li> </ul>		
		<a href="#">DH-XVR4104HS-I</a>		<ul style="list-style-type: none"> <li>- 4 Channel Penta-brid 1080N/720p Compact 1U 1HDD WisSense Digital Video Recorder</li> <li>- H.265+/H.265 dual-stream video compression</li> <li>- Supports Full-channel AI-Coding</li> <li>- Supports HDCV/AHD/TVI/CVBS/IP video inputs</li> <li>- Max 5 channels IP camera inputs, each channel up to 2MP; Max 32 Mbps incoming bandwidth</li> <li>- Up to 4 channels video stream ( analog channel ) SMD Plus</li> </ul>	IRR 23,900,000	
		<a href="#">DH-XVR4108HS-I</a>		<ul style="list-style-type: none"> <li>- 8 Channel Penta-brid 1080N/720p Compact 1U 1HDD WisSense Digital Video Recorder</li> <li>- H.265+/H.265 dual-stream video compression</li> <li>- Supports Full-channel AI-Coding</li> <li>- Supports HDCV/AHD/TVI/CVBS/IP video inputs</li> <li>- Max 10 channels IP camera inputs, each channel up to 6MP; Max 32 Mbps incoming bandwidth</li> <li>- Up to 8 channels video stream ( analog channel ) SMD Plus</li> </ul>	IRR 49,100,000	
	210435	<a href="#">DH-XVR4116HS-I</a>		<ul style="list-style-type: none"> <li>- 16 Channel Penta-brid 720p Compact 1U 1HDD WisSense Digital Video Recorder</li> <li>- H.265+/H.265 video compression</li> <li>- Supports Full-channel AI-Coding</li> <li>- Supports HDCV/AHD/TVI/CVBS/IP video inputs</li> <li>- Max 18 channels IP camera inputs, each channel up to 6MP; Max 64 Mbps Incoming Bandwidth</li> <li>- Long transmission distance over coax cable</li> <li>- Up to 8 channels video stream ( analog channel ) SMD Plus</li> </ul>	IRR 51,270,000	IRR 75,200,000
250447	210447	<a href="#">DH-XVR5104HS-I3</a>		<ul style="list-style-type: none"> <li>- 4 Channel Penta-brid 5M-A/1080p None Real-Time WisSense AI XVR</li> <li>- H.265+/H.265/H.264+/H.264 dual-stream video compression</li> <li>- Pentabrid (IP+CVI+AHD+TVI+CVBS) N+M (4+2 IP up to 6MP(32 Mbps)</li> <li>- HDMI/VGA Simultaneous Video Output, 1ch Audio I/O</li> <li>- Playback 1/4ch, 1 SATA Port up to 6 TB capacity, 2*USB 2.0, RS485, 10/100 Mbps LAN Interface, P2P Support, 1ch Perimeter(Tripwire/Intrusion) 10 IVS each channel, 1ch FaceRecognition up to 10,000 Face Library, 4ch SMD Plus, Full channel AI-Coding, Human/Vehicle Classification, IoT Support</li> </ul>	IRR 43,500,000	IRR 49,000,000
250446	210446	<a href="#">DH-XVR5108HS-I3</a>		<ul style="list-style-type: none"> <li>- 8 Channel Penta-brid 5M-A/1080p None Real-Time WisSense AI XVR</li> <li>- H.265+/H.265/H.264+/H.264 dual-stream video compression</li> <li>- Pentabrid (IP+CVI+AHD+TVI+CVBS) N+M 8+4 IP up to 6MP(64 Mbps)</li> <li>- HDMI/VGA Simultaneous Video Output, 1ch Audio I/O, Playback 1/4/9ch</li> <li>- 1 SATA Port up to 10 TB capacity, 2*USB 2.0, RS485, 10/100 Mbps LAN Interface, P2P Support</li> <li>- 1ch Perimeter(Tripwire/Intrusion) 10 IVS each channel, 1ch FaceRecognition up to 10,000 Face Library, 8ch SMD Plus, Full channel AI-Coding, Human/Vehicle Classification, IoT Support</li> </ul>	IRR 66,950,000	IRR 69,000,000



				<p>4 Channel Penta-brid 4K-N/5MP Compact 1U 1HDD WiSense Digital Video Recorder</p> <ul style="list-style-type: none"> <li>-H.265+/H.265 dual-stream video compression</li> <li>-Supports HDCVI/AHD/TVI/CVBS/IP video inputs</li> <li>-Max 8 channels IP camera inputs, each channel up to 8MP; Max 64 Mbps incoming bandwidth</li> <li>-Up to 2 channels video stream (analog channel) Perimeter Protection</li> <li>-Up to 4 channels video stream (analog channel) SMD Plus</li> <li>-Up to 2 channels video stream (analog channel) human face recognition</li> <li>-IoT &amp; POS functionalities</li> </ul>		
250582	210582	<a href="#">DH-XVR5104HS-4KL-I3</a>		<p>4 Channel Penta-brid 4K WiSense Ai XVR</p> <p>4K@7fps, 6MP@10fps, 5MP@12fps, 4MP@15fps, 4MN/1080p/720p@25/30fps</p> <p>H.265+/H.265/H.264+/H.264 dual-stream video compression</p> <p>Pentabrid (IP+CVI+AHDI+TVI+CVBS)N+M 4+4 IP up to 8MP(64 Mbps)</p> <p>HDMI/VGA Simultaneous Video Output, 1ch Audio I/O</p> <p>Playback 1/4ch, 1 SATA Port up to 10 TB capacity, 2*USB 2.0, RS485, 10/100 Mbps LAN Interface, P2P Support, 1ch Perimeter(Tripwire/Intrusion) 10 IVS each channel, 1ch FaceRecognition up to , 10,000 Face Library, 4ch SMD Plus, Full channel AI-Coding, Human/Vehicle ,Classification, IoT Support</p>	IRR 63,230,000	IRR 60,900,000
250553	210553	DH-XVR5108HS-4KL-I2		<p>8 Channel Penta-brid 4K-N/5MP WiSense Ai XVR</p> <p>4K@7fps, 6MP@10fps, 5MP@12fps, 4K-N/4MP@15fps, 4MN/1080p/720p@25/30fps</p> <p>H.265+/H.265/H.264+/H.264 dual-stream video compression</p> <p>Pentabrid (IP+CVI+AHDI+TVI+CVBS)N+M 8+8 IP up to 8MP(128 Mbps)</p> <p>HDMI/VGA Simultaneous Video Output, 1ch Audio I/O, Playback 1/4/9ch</p> <p>1 SATA Port up to 10 TB capacity</p> <p>1*USB 2.0, 1*USB 3.0, RS485, 1*1000 Mbps LAN Interface, RS485, P2P Support</p> <p>2ch Perimeter(Tripwire/Intrusion) 10 IVS each channel, 2ch FaceRecognition up to 20,000 Face Library, 8ch SMD Plus, Human/Vehicle Classification, IoT Support</p>		
	210563	DH-XVR5108HS-4KL		<p>8 Channel Penta-brid 4K-N/5MP WiSense Ai XVR</p> <p>4K@7fps, 6MP@10fps, 5MP@12fps, 4K-N/4MP@15fps, 4MN/1080p/720p@25/30fps</p> <p>H.265+/H.265/H.264+/H.264 dual-stream video compression</p> <p>Pentabrid (IP+CVI+AHDI+TVI+CVBS)N+M 8+8 IP up to 8MP(128 Mbps)</p> <p>HDMI/VGA Simultaneous Video Output, 1ch Audio I/O</p> <p>Playback 1/4/9ch</p> <p>1 SATA Port up to 10 TB capacity 1*USB 2.0, 1*USB 3.0, RS485, 1*1000 Mbps LAN Interface, RS485, P2P Support 2ch Perimeter(Tripwire/Intrusion) 10 IVS each</p>	IRR 103,790,000	
	210593	DH-XVR5108HS-4KL-I3		<p>8 Channel Penta-brid 4K-N/5MP Compact 1U 1HDD WiSense Digital Video Recorder</p> <p>&gt; H.265+/H.265 dual-stream video compression &gt; Supports Full-channel AI Coding</p> <p>&gt; Supports HDCVI/AHD/TVI/CVBS/IP video inputs</p> <p>&gt; Max 16 channels IP camera inputs, each channel up to 8MP; Max 128 Mbps incoming bandwidth</p> <p>&gt; Up to 2 channels video stream (analog channel) Perimeter Protection</p> <p>&gt; Up to 8 channels video stream (analog channel) SMD Plus</p> <p>&gt; Up to 2 channels video stream (analog channel) human face recognition</p> <p>&gt; IoT &amp; POS functionalities</p>	IRR 101,690,000	IRR 98,300,000
		DH-XVR5108HS-4KL-S2		<p>8 Channel Penta-brid 4K-N/5MP Compact 1U 1HDD WiSense Digital Video Recorder</p> <p>-H.264+/H.264 dual-stream video compression</p> <p>-Supports HDCVI/AHD/TVI/CVBS/IP video inputs</p> <p>-Max 16 channels IP camera inputs, each channel up to 8MP; Max 128 Mbps incoming bandwidth</p> <p>-Up to 2 channels video stream (analog channel) Perimeter Protection</p> <p>-Up to 8 channels video stream (analog channel) SMD Plus</p> <p>-Up to 2 channels video stream (analog channel) human face recognition</p> <p>-IoT &amp; POS functionalities</p>		
	210572	DH-XVR5116H-I2		<p>16 Channel Penta-brid 5M-N/1080P WiSense Ai XVR</p> <p>5MN@10fps, 4MN/5MP@15fps, 3MN/4MP@25/30fps</p> <p>H.265+/H.265/H.264+/H.264 dual-stream video compression</p> <p>Pentabrid (IP+CVI+AHDI+TVI+CVBS)N+M 16+4 IP up to 6MP(128 Mbps)</p> <p>HDMI/VGA Simultaneous Video Output, 1ch Audio I/O</p> <p>Playback 1/4/9/16ch, 1 SATA Port up to 10 TB capacity</p> <p>1*USB 2.0, 1*USB 3.0, RS485, 1*1000 Mbps LAN Interface, RS485, P2P Support</p> <p>2ch Perimeter(Tripwire/Intrusion) 10 IVS each channel, 2ch FaceRecognition up to 10,000 Face Library, 16ch SMD Plus, Human/Vehicle Classification, IoT Support</p>	IRR 72,130,000	
250761		DH-XVR5116HS-I3		<p>-H.265+/H.265 dual-stream video compression</p> <p>-Supports HDCVI/AHD/TVI/CVBS/IP video inputs</p> <p>-Max 24 channels IP camera inputs, each channel up to 6MP; Max 128 Mbps incoming bandwidth</p> <p>-Up to 2 channels video stream (analog channel) Perimeter Protection</p> <p>-Up to 16 channels video stream (analog channel) SMD Plus</p> <p>-Up to 2 channels video stream (analog channel) human face recognition</p> <p>-IoT &amp; POS functionalities</p>	IRR 108,260,000	IRR 106,000,000
250480	210480	DH-XVR5116HS-S2		<p>-H.264+/H.264 dual-stream video compression</p> <p>-Supports HDCVI/AHD/TVI/CVBS/IP video inputs</p> <p>-Max 24 channels IP camera inputs, each channel up to 6MP; Max 128 Mbps incoming bandwidth</p> <p>-Up to 2 channels video stream (analog channel) Perimeter Protection</p> <p>-Up to 16 channels video stream (analog channel) SMD Plus</p> <p>-Up to 2 channels video stream (analog channel) human face recognition</p> <p>-IoT &amp; POS functionalities</p>	IRR 72,480,000	
		DH-XVR5216AN-I2		<p>16 Channel Penta-brid 5M-N/1080P 1U 2HDDs WiSense Digital Video Recorder</p> <p>-H.265+/H.265 dual-stream video compression</p> <p>-Supports HDCVI/AHD/TVI/CVBS/IP video inputs</p> <p>-Max 24 channels IP camera inputs, each channel up to 6MP; Max 128 Mbps incoming bandwidth</p> <p>-Up to 2 channels video stream (analog channel) Perimeter Protection</p> <p>-Up to 16 channels video stream (analog channel) SMD Plus</p> <p>-Up to 2 channels video stream (analog channel) human face recognition IoT &amp; POS functionalities</p>	IRR 74,810,000	
		DHI-XVR5216AN-S2		<p>16 Channel Penta-brid 1080P Digital Video Recorder</p> <p>- Embedded processor - H.264+/H.264 dual-stream video compression - Support HDCVI/AHD/TVI/CVBS/IP video inputs - Max 6/12/24 channels IP camera inputs, each channel up to 5MP; Max 24/48/96Mbps Incoming Bandwidth - Smart Search and Intelligent Video System</p>	IRR 94,500,000	
250478	210478	DH-XVR5216AN-4KL		<p>16 Channel Penta-brid 4K 1U Digital Video Recorder</p> <p>-H.265+/H.265 dual-stream video compression</p> <p>-Supports HDCVI/AHD/TVI/CVBS/IP video inputs</p> <p>-Max 12/24 channels IP camera inputs, each channel up to 8MP; Max 48/96Mbps Incoming Bandwidth</p> <p>- Smart Search and Intelligent Video System</p>	IRR 166,410,000	
	210734	DH-XVR5216AN-4KL-I2		<p>16 Channel Penta-brid 4KN/5MP WiSense Ai XVR</p> <p>4K@7fps, 6MP@10fps, 5MN@12fps, 4KN/4MP@15fps, 4MN/2MP/1MP@25/30fps</p> <p>H.265+/H.265/H.264+/H.264 dual-stream video compression</p> <p>Pentabrid (IP+CVI+AHDI+TVI+CVBS)N+M 16+4 IP up to 8MP(128 Mbps)</p> <p>HDMI/VGA Simultaneous Video Output, 1ch Audio I/O</p> <p>Playback 1/4/9/16ch</p> <p>2 SATA Port up to 10 TB capacity each port(20TB Total)</p> <p>1*USB 2.0, 1*USB 3.0, RS485, 1*1000 Mbps LAN Interface, RS485, P2P Support</p> <p>2ch Perimeter(Tripwire/Intrusion) 10 IVS each channel, 2ch FaceRecognition up to 20,000 Face Library, 16ch SMD Plus, Human/Vehicle Classification, IoT Support</p>	IRR 140,850,000	
		DH-XVR5216AN-4KL-I3		<p>16 Channel Penta-brid 4K-N/5MP 1U 2HDDs WiSense Digital Video Recorder</p> <p>-H.265+/H.265 dual-stream video compression</p> <p>-Supports HDCVI/AHD/TVI/CVBS/IP video inputs</p> <p>-Max 32 channels IP camera inputs, each channel up to 8MP; Max 128 Mbps incoming bandwidth</p> <p>-Up to 2 channels video stream (analog channel) Perimeter Protection</p> <p>-Up to 16 channels video stream (analog channel) SMD Plus</p> <p>-Up to 2 channels video stream (analog channel) human face recognition</p> <p>-IoT &amp; POS functionalities</p>	IRR 204,490,000	IRR 200,000,000



250682		DH-XVRS216AN-I3		<ul style="list-style-type: none"> <li>.16 Channel Penta-brid SM-N/1080P 1U 2HDDs WiSense Digital Video Recorder</li> <li>- H.265+/H.265 dual-stream video compression</li> <li>- Supports HDCV/AHD/TVI/CVBS/IP video inputs</li> <li>- Max 24 channels IP camera inputs, each channel up to 6MP; Max 128 Mbps incoming bandwidth</li> <li>- Up to 2 channels video stream (analog channel) Perimeter Protection</li> <li>- Up to 16 channels video stream (analog channel) SMD Plus</li> <li>- Up to 2 channels video stream (analog channel) human face recognition</li> <li>- IoT &amp; POS functionalities</li> </ul>	IRR 144,610,000	
250556		DH-XVRS216AN-S2		<ul style="list-style-type: none"> <li>.16 Channel Penta-brid SM-N/1080P 1U 2HDDs WiSense Digital Video Recorder</li> <li>- Embedded processor</li> <li>- H.264+/H.264 dual-stream video compression</li> <li>- Support HDCV/AHD/TVI/CVBS/IP video inputs</li> <li>- Max 6/12/24 channels IP camera inputs, each channel up to 5MP; Max 24/48/96Mbps Incoming Bandwidth</li> <li>- Smart Search and Intelligent Video System</li> </ul>		
		DHI-XVRS232AN-S2		<ul style="list-style-type: none"> <li>.32 Channel Penta-brid 1080P Digital Video Recorder</li> <li>- Embedded processor -H.264+/H.264 dual-stream video compression -Support HDCV/AHD/TVI/CVBS/IP video inputs -Max 32 channels IP camera inputs; Max 128Mbps Incoming Bandwidth -Long transmission distance over coax cable -Support 2 SATA HDD, up to 16TB</li> </ul>	IRR 142,300,000	
		DH-XVRS232AN-X		<ul style="list-style-type: none"> <li>.32 Channel Penta-brid 1080P</li> <li>- H.265+/H.265 dual-stream video compression</li> <li>- Supports HDCV/AHD/TVI/CVBS/IP video inputs</li> <li>- Max 32 channels IP camera inputs, each channel up to 6MP; Max 128Mbps incoming bandwidth</li> <li>- Smart Search and Intelligent Video System</li> <li>- Interface : 1 HDMI, 1 VGA, 1 TV</li> <li>- 2 SATA Ports, up to 10TB capacity</li> </ul>		
		DH-XVRS232AN-I2		<ul style="list-style-type: none"> <li>.32 Channel Penta-brid SM-N/1080P WiSense Ai XVR</li> <li>5MN@10fps, 4MN/2MP@15fps, 2MN/1MP@25/30fps</li> <li>H.265+/H.265/H.264+/H.264 dual-stream video compression</li> <li>Pentabrid (IP+CVI+AHDI+TVI+CVBS)N+M 32ch IP up to 6MP(128 Mbps)</li> <li>HDMI/VGA Simultaneous Video Output, 1ch Audio I/O</li> <li>Playback 1/4/9/16ch</li> <li>2 SATA Port up to 10 TB capacity each port(20TB Total)</li> <li>1*USB 2.0, 1*USB 3.0, RS485, 1*1000 Mbps LAN interface, RS485, P2P Support</li> <li>2ch Perimeter(Tripwire/Intrusion) 10 IVS each channel, 2ch FaceRecognition up to 10,000 Face Library, 16ch SMD Plus, Human/Vehicle Classification, IoT Support</li> </ul>	IRR 120,270,000	
		DH-XVRS232AN-I3		<ul style="list-style-type: none"> <li>.32 Channel Penta-brid SM-N/1080P 1U 2HDDs WiSense Digital Video Recorder</li> <li>- H.265+/H.265 dual-stream video compression</li> <li>- Supports HDCV/AHD/TVI/CVBS/IP video inputs</li> <li>- Max 32 channels IP camera inputs, each channel up to 6MP; Max 128 Mbps incoming bandwidth</li> <li>- Up to 2 channels video stream (analog channel) Perimeter Protection</li> <li>- Up to 16 channels video stream (analog channel) SMD Plus</li> <li>- Up to 2 channels video stream (analog channel) human face recognition</li> <li>- IoT &amp; POS functionalities</li> </ul>	IRR 227,640,000	IRR 253,000,000
		<a href="#">DH-XVRS432L-I3</a>		<ul style="list-style-type: none"> <li>.32 Channel Penta-brid SM-N/1080P WiSense Ai XVR</li> <li>5MN@10fps, 4MN/2MP@15fps, 2MN/1MP@25/30fps</li> <li>H.265+/H.265/H.264+/H.264 dual-stream video compression</li> <li>Pentabrid (IP+CVI+AHDI+TVI+CVBS)N+M 32ch IP up to 6MP(128 Mbps)</li> <li>HDMI/VGA Simultaneous Video Output, 4/1ch Audio I/O, 1/6/6 Alarm I/O</li> <li>Playback 1/4/9/16ch</li> <li>4 SATA Port up to 10 TB capacity each port(40TB Total)</li> <li>1*USB 2.0, 2*USB 3.0, RS485, 1*1000 Mbps LAN interface, RS485, RS232, P2P Support</li> <li>2ch Perimeter(Tripwire/Intrusion) 10 IVS each channel, 2ch FaceRecognition up to 10,000 Face Library, 16ch SMD Plus, Human/Vehicle Classification, IoT Support</li> </ul>	IRR 418,000,000	