

PRICE LIST



☎ ۰۲۱۸۷۷۰۰۸۸۷
 WWW.RADIS-CO.COM
 RADIS_NET











Network Camera -IP














SKU (#)	SKU (P)	Items	Description	User Price (با گارانتی پارس ارتباط)	User Price (با الماس ایران)
250405	210405	DH-IPC-HFW2439SP-SA-LED-S2	 4MP Lite Full-color Fixed-focal Bullet Network Camera 4MP, 1/3" Progressive CMOS low illumination 0.004 Lux@F1.0 high image definition 4MP@25/30fps, 3.6mm Fixed lens SMART H.264+/H.265+, iVS Intrusion/Tripwire WDR (120db), 3D DNR, HLC, BLC, AWB, AGC, ROI, Smart Illumination, Day/Night ICR Auto Switch Micro SD 256GB, Built-in Mic 12V, PoE, IP67, 1 Warmlight LED 30m Distance, Onvif Profile S/G/T	IRR 49,310,000	IRR 53,600,000
		DH-IPC-HFW2439MP-AS-LED-B-S2	 4MP, 1/3" CMOS image sensor, low illumination, high image definition > Outputs 4MP (2560 × 1440) @ 25/30 fps, Max. supports 4MP (2688 × 1520) @ 20 fps > H.265 codec, high compression rate, ultra-low bit rate> Built-in warm lights, max. illumination distance: 40 m> ROI, SMART H.264+/H.265+, flexible coding, applicable to various bandwidth and storage environments> Rotation mode, WDR, 3D NR, HLC, BLC, digital watermarking, applicable to various monitoring scenes> Intelligent detection: Intrusion, tripwire > Abnormality detection: Motion detection, video tampering, scene changing, no SD card, SD card full, SD card error, network disconnection, IP conflict, illegal access, voltage detection> Alarm: 2 in, 2 out; audio: 1 in, 1 out; supports max. 256 GB Micro SD card> 12V DC/PoE power supply; 12V DC power output, max. current 165mA> IP67 protection	IRR 37,290,000	
250404	210404	DH-IPC-HFW2431SP-S-S2-0360B	 4MP WDR IR Bullet Network Camera 1/3" 4MP image sensor SMART H.264/H.265 dual stream encoding 4MP (2688 × 1520)@20 fps, 2560 × 1440 @25fps Min. Illumination:0.008 Lux@F1.6, 3.6mm Fixed lens WDR(120dB), Day/Night(ICR), 3DNR, AWB, AGC, BLC, HLC, ROI Smart Detection (Tripwire Intrusion) Micro SD memory 256 GB, max IR distance: 30 m, Smart IR, IP67, PoE	IRR 32,850,000	IRR 48,200,000
		DH-IPC-HFW2431TP-ZAS	 > 4MP, 1/3" CMOS image sensor, low illumination, high image definition > Outputs max. 4MP (2688 × 1520)@30 fps > H.265 codec, high compression rate, low bit rate > Built-in IR LED, max. IR distance: 60 m > ROI, SMART H.264+/H.265+, flexible coding, applicable to various bandwidth and storage environments> Rotation mode, WDR, 3D DNR, HLC, BLC, digital watermarking, applicable to various monitoring scenes> Intelligent detection: Intrusion, tripwire (support the classification and	IRR 93,190,000	IRR 61,000,000
		DH-IPC-HFW3441TP-ZAS	 4MP IR Vari-focal Bullet Wide-angle Network Camera > 4MP, 1/3" CMOS image sensor, low illumination, high image definition > Outputs max. 4MP (2688 × 1520)@30 fps > H.265 codec, high compression rate, low bit rate > Built-in IR LED, max. IR distance: 60 m > ROI, SMART H.264+/H.265+, flexible coding, applicable to various bandwidth and storage environments> Rotation mode, WDR, 3D NR, HLC, BLC, digital watermarking, applicable to various monitoring scenes> Intelligent detection: Intrusion, tripwire (support the classification and	IRR 110,230,000	
250439	210439	DH-IPC-HDW2439TP-AS-LED-S2	 4MP Lite Full-color Fixed-focal Bullet Network Camera 4MP, 1/3" Progressive CMOS low illumination 0.004 Lux@F1.0, high image definition 4MP@25/30fps, 2.8mm Fixed lens SMART H.264+/H.265+, iVS Intrusion/Tripwire WDR (120db), 3D DNR, HLC, BLC, AWB, AGC, ROI, Smart Illumination, Day/Night ICR Auto Switch Micro SD 256GB, Built-in Mic, 12V, PoE, IP67, 2 Warmlight LED 30m Distance, Onvif Profile S/G/T	IRR 50,140,000	IRR 51,800,000
		DH-IPC-HDBW2431RP-ZS-S2	 4MP Lite IR Vari-focal Dome Network Camera > 4MP, 1/3" CMOS image sensor, low illumination, high image definition > Outputs 4MP (2560 × 1440)@25/30 fps, Max. supports 4MP (2688 × 1520)@20 fps > H.265 codec, high compression rate, ultra-low bit rate > Built-in IR LED, max IR distance: 40 m > ROI, SMART H.264+/H.265+, flexible coding, applicable to various bandwidth and storage environments > Rotation mode, WDR, 3D NR, HLC, BLC, digital watermarking, applicable to various monitoring scenes> Intelligent detection: Intrusion, tripwire	IRR 57,740,000	IRR 84,200,000
	210566	DH-IPC-HDW2431TP-AS-S2	 4MP Lite IR Fixed-focal Eyeball Network Camera > 4MP, 1/3" CMOS image sensor, low illumination, high image definition > Built-in IR LED, max IR distance: 30 m > ROI, SMART H.264+/H.265+, flexible coding, applicable to various bandwidth and storage environments> Rotation mode, WDR, 3D NR, HLC, BLC, digital watermarking, applicable to various monitoring scenes> Intelligent detection: Intrusion, tripwire> Abnormality detection: Motion detection, video tampering, no SD card, SD card full, SD	IRR 35,700,000	IRR 48,200,000
		IPC-HFW2431TP-ZS-27135-S2	 4MP, 1/3" CMOS image sensor, low illumination, high image definition Outputs 4MP (2560 × 1440)@25/30 fps, max. supports 4MP (2688 × 1520)@20 fps H.265 codec, high compression rate, ultra-low bit rate Built-in IR LED, max IR distance: 60 m ROI, SMART H.264+/H.265+, flexible coding, applicable to various bandwidth and storage environments Rotation mode, WDR, 3D NR, HLC, BLC, digital watermarking, applicable to various	IRR 86,650,000	IRR 80,000,000
250595	210595	DH-IPC-HDW2431TMP-AS-S2	 4MP WDR IR Eyeball Network Camera, Starlight 1/3" 4Megapixel progressive CMOS, SMART H.264/H.265 dual stream encoding 4MP (2688 × 1520)@20 fps, 2560 × 1440 @25fps, Min. Illumination:0.008 Lux@F1.6, 2.8 mm Fixed lens, WDR(120dB), Day/Night(ICR), 3DNR, AWB, AGC, BLC, HLC, ROI, Smart Detection (Tripwire Intrusion), Micro SD memory 256 GB, Built in Mic max IR distance:30 m, Smart IR, IP67, PoE	IRR 58,610,000	
250461	210461	DH-IPC-HDBW2431EP-S-S2	 4MP IR Mini Dome Network Camera 1/3" 4Megapixel progressive CMOS, SMART H.264/H.265 dual stream encoding 4MP (2688 × 1520)@20 fps, 2560 × 1440 @25fps, Min. Illumination:0.008 Lux @ F1.6 2.8mm Fixed lens, WDR(120dB), Day/Night(ICR), 3DNR, AWB, AGC, BLC, HLC, ROI Smart Detection (Tripwire Intrusion), Micro SD memory 256 GB max IR distance:30 m, Smart IR, IP67, IK10, PoE	IRR 46,660,000	IRR 33,800,000














		DH-IPC-HFW1431SP-0360B-S4		<p>4MP, 1/3" CMOS image sensor, low illumination, high image definition Outputs 4MP (2560 x 1440) @25/30 fps, and supports max. 4MP(2688 x 1520) @20 fps H.265 codec, high compression rate, ultra-low bit rate: Built-in IR LED, max. IR distance: 30 m ROI, SMART H.264/H.265, flexible coding, Image flip, WDR, 3D DNR, HLC, BLC, digital watermarking, applicable to various monitoring scenes Abnormality detection: Motion detection, video tampering, network disconnection, IP conflict, illegal access, voltage detection, 12V DC/PoE power support</p>	IRR 41,700,000	IRR 44,900,000
		DH-IPC-HDPW1431R1P-0280B-S4		<p>IPC-HDPW1431R1P-S4, 4MP Entry IR Fixed-focal Dome Network Camera > 4MP, 1/3" CMOS image sensor, low illumination, high image definition > Outputs 4MP (2560 x 1440) @25/30 fps, and supports max. 4MP (2688 x 1520) @20 fps > H.265 codec, high compression rate, ultra-low bit rate > Built-in IR LED, max. IR distance: 30 m > ROI, SMART H.264/H.265, flexible coding, applicable to various bandwidth and storage environments > Image Rotation, WDR, 3D DNR, HLC, BLC, digital watermarking, applicable to various monitoring scenes > Abnormality detection: Motion detection, video tampering, network disconnection, IP conflict, illegal access, voltage detection</p>		IRR 38,000,000
		DH-IPC-HDPW1431R1P-0280B-S4		<p>4MP Entry IR Fixed-focal Dome Network Camera > 4MP, 1/3" CMOS image sensor, low illumination, high image definition > Outputs 4MP (2560 x 1440) @25/30 fps, and supports max. 4MP (2688 x 1520) @20 fps > H.265 codec, high compression rate, ultra-low bit rate > Built-in IR LED, max. IR distance: 30 m > ROI, SMART H.264/H.265, flexible coding, applicable to various bandwidth and storage environments > Image Rotation, WDR, 3D DNR, HLC, BLC, digital watermarking, applicable to various monitoring scenes > Abnormality detection: Motion detection, video tampering, network disconnection, IP conflict, illegal access, voltage detection > 12V DC/PoE power support > IP67, protection</p>		IRR 38,000,000
		DH-IPC-HDW1431TP-0280B-S4		<p>4MP Entry IR Fixed-focal Eyeball Network Camera 1/3" 4Megapixel progressive CMOS, 20fps@4.1M(2688x1520) & 25fps@4M(2560x1440) H.265+/H.265/H.264+/H.264 dual-stream encoding WDR(120dB), Day/Night(ICR), 3DNR, AWB, AGC, BLC, HLC, Support ROI Max. IR LEDs Length 30m, IP67, PoE</p>	IRR 37,990,000	IRR 38,000,000
		DH-IPC-HFW2231SP-S-S2		<p>2MP WDR IR Bullet Network Camera, starlight 1/2.8" 2Megapixel progressive CMOS, Min. Illumination:0.002 Lux@F1.6 Outputs max. 2MP (1920 x 1080) @25/30 fps, 3.6mm Fixed lens SMART H.264/H.265 dual-stream encoding, IVS(Tripwire, intrusion) WDR(120dB), Day/Night(ICR), 3DNR, AWB, AGC, BLC, HLC, ROI Micro SD memory 256GB Max. IR LEDs Length 30m, Smart IR, IP67, PoE</p>	IRR 44,380,000	IRR 34,500,000
		DH-IPC-HFW2239SP-SA-LED-0360B-S2		<p>2MP Lite IR Fixed-focal Eyeball Network Camera > 2MP, 1/2.8" CMOS image sensor, low illumination, high image definition, > Outputs max. 2MP (1920 x 1080) @25/30 fps > H.265 codec, high compression rate, ultra-low bit rate > Built-in warm lights, max. illumination distance: 30 m > ROI, SMART H.264+/H.265+, flexible coding, applicable to various bandwidth and storage environments > Rotation mode, WDR, 3D NR, HLC, BLC, digital watermarking, applicable to various monitoring</p>	IRR 45,810,000	
210568		DH-IPC-HDW2231TP-AS-0280B-S2-QH		<p>2MP Lite IR Fixed-focal Eyeball Network Starlight Camera 2MP, 1/2.8" Progressive CMOS low illumination 0.002 Lux @F1.6, high image definition 2MP@25/30fps 2.8mm fixed lens, SMART H.264+/H.265+, IVS Intrusion/Tripwire WDR (120db), 3D DNR, HLC, BLC, AWB, AGC, ROI, Smart Illumination, Day/Night ICR Auto Switch Micro SD 256GB, Built-in Mic 12V, PoE, IP67, 2 IR LEDs 30m Distance, Onvif Profile S/G/T</p>	IRR 42,830,000	IRR 41,800,000
250426	210426	DH-IPC-HFW1239S1-LED-SS		<p>2MP Lite Full-color Fixed-focal Bullet Network Camera 2MP, 1/2.8" Progressive CMOS low illumination 0.005 Lux @F1.6 high image definition 2MP@25/30fps 3.6mm fixed lens, SMART H.264+/H.265+ DWDR/BLC/HLC/AWB/AGC/3D DNR/ROI, Smart Illumination 12V, PoE, IP67, 1 Warmlight LED 15m Distance, Onvif Profile S/T</p>	IRR 35,020,000	IRR 21,300,000
		DH-IPC-HDBW1239T1P-LED-S5		<p>2MP, 1/2.7" CMOS image sensor, low illumination, high image definition > Outputs max. 2MP (1920 x 1080) @25/30 fps H.265 codec, high compression rate, ultra-low bit rate, Built-in LEDs, max LED distance: 15 m > ROI, SMART H.264/H.265, flexible coding, applicable to various bandwidth and storage environments > Rotation mode, DWDR, 3D DNR, HLC, BLC, digital watermarking, applicable to various monitoring scenes</p>	IRR 30,940,000	
250452	210452	DH-IPC-HDW1239T1-LED		<p>2MP, 1/2.7" CMOS image sensor, low illumination, high image definition Outputs max. 2MP (1920 x 1080) @25/30 fps H.265 codec, high compression rate, ultra-low bit rate Built-in LEDs, max LED distance: 15 m ROI, SMART H.264/H.265, flexible coding, applicable to various bandwidth and storage environments</p>	IRR 21,480,000	IRR 30,600,000
250662		DH-IPC-HFW1230S-S5		<p>2MP Entry IR Fixed-focal Bullet Network Camera 1/2.7" 2Megapixel progressive CMOS SMART H.264/H.265 dual stream encoding max. 2MP (1920 x 1080p) @25/30 fps Min. Illumination:0.01 Lux@F2.0 3.6 Fixed lens DWDR, Day/Night(ICR), 3DNR, AWB, AGC, BLC, HLC, ROI</p>	IRR 29,960,000	
250423	210423	DH-IPC-HFW1230SP-0280B-S5-QH2		<p>2MP Entry IR Fixed-focal Bullet Network Camera 1/2.7" 2Megapixel progressive CMOS SMART H.264/H.265 dual stream encoding, max. 2MP (1920 x 1080p) @25/30 fps Min. Illumination:0.01 Lux@F2.0 2.8 Fixed lens, DWDR, Day/Night(ICR), 3DNR, AWB, AGC, BLC, HLC, ROI max IR distance:30 m, Smart IR, IP67, PoE</p>	IRR 33,300,000	IRR 29,640,000
		DH-IPC-HFW1230SP-0360B-S5-QH2		<p>2MP Entry IR Fixed-focal Bullet Network Camera 1/2.7" 2Megapixel progressive CMOS SMART H.264/H.265 dual stream encoding, max. 2MP (1920 x 1080p) @25/30 fps Min. Illumination:0.01 Lux@F2.0 3.6 Fixed lens, DWDR, Day/Night(ICR), 3DNR, AWB, AGC, BLC, HLC, ROI max IR distance:30 m, Smart IR, IP67, PoE</p>	IRR 33,300,000	
		IPC-A22EP-A		<p>Human Detection 1080P 360° Coverage Built-in Siren Smart Tracking Privacy Mode Abnormal Sound Alarm Night Vision</p>		
		DH-IPC-HFW1230S1P-0360B-S5		<p>2MP, 1/2.8" CMOS image sensor, low illumination, high image definition Outputs max. 2MP (1920 x 1080) @25/30 fps; H.265 codec, high compression rate, ultra-low bit rate, Built-in efficient IR illuminator, and the max. illumination distance is 30 m ROI, SMART H.264+/H.265+, flexible coding, applicable to various bandwidth and storage environments, Rotation mode, DWDR, 3D NR, HLC, BLC, digital watermarking, applicable to various monitoring scenes, Abnormality detection: Motion detection> 12V DC/PoE power supply, IP67 protection</p>	IRR 29,540,000	IRR 26,370,000





		DH-IPC-HFW1230S1P-0280B-S5-QH2		2MP, 1/2.8" CMOS image sensor, low illumination, high image definition Outputs max. 2MP (1920 x 1080) @25/30 fps. H.265 codec, high compression rate, ultra-low bit rate. Built-in efficient IR illuminator, and the max. illumination distance is 30 m ROI, SMART H.264+/H.265+, flexible coding, applicable to various bandwidth and storage environments. Rotation mode, DWDNR, 3D NR, HLC, BLC, digital watermarking, applicable to various monitoring scenes, Abnormality detection: Motion detection > 12V DC/PoE power supply, IP67 protection	IRR 29,540,000	
		DH-IPC-HDW1230T1P-LED		2MP Entry IR Fixed-Focal Eyeball Network Camera 1/2.7" 2Megapixel progressive CMOS SMART H.264/H.265 dual stream encoding, max. 2MP (1920 x 1080p) @25/30 fps Min. Illumination: 0.01 Lux @ F2.0 2.8 Fixed lens, DWDNR, Day/Night(ICR), 3DNR, AWB, AGC, BLC, HLC, ROI, EIS max IR distance: 30 m, Smart IR, IP67, PoE	IRR 31,230,000	
250579	210579	DH-IPC-HDW2230T-AS-S2		> Outputs 2MP (1920 x 1080) @25/30 fps > H.265 coding, high compression rate, low bit rate > Built-in IR LED, max IR distance: 30 m > ROI, SMART H.264+/H.265+, flexible coding, applicable to various bandwidth and storage environments > Rotation mode, DWDNR, 3D NR, HLC, BLC, digital watermarking, applicable to various monitoring scenes > Intelligent detection: Intrusion, tripwire > Abnormality detection: Motion detection, video tampering, no SD card, SD card full, > Supports max. 256 GB Micro SD card & built-in Micro 12V DC/PoE power supply > IP67 protection	IRR 29,360,000	IRR 40,000,000
		IPC-HDW2230TP-AS		2MP, 1/2.7" CMOS image sensor, low illumination, high image definition - Outputs 2MP (1920 x 1080) @25/30 fps - H.265 coding, high compression rate, low bit rate - Built-in IR LED, max IR distance: 30 m - ROI, SMART H.264+/H.265+, flexible coding, applicable to various bandwidth and storage environments - Rotation mode, DWDNR, 3D NR, HLC, BLC, digital watermarking, applicable to various monitoring scenes - Intelligent detection: Intrusion, tripwire		
		IPC-HDBW2230EP-S		2MP, 1/2.7" CMOS image sensor, low illumination, high image definition - Outputs 2MP (1920 x 1080) @25/30 fps - H.265 codec, high compression rate, ultra-low bit rate - Built-in IR LED, max IR distance: 30 m - ROI, SMART H.264+/H.265, flexible coding, applicable to various bandwidth and storage environments - Rotation mode, DWDNR, 3D DNR, HLC, BLC, digital watermarking, applicable to various monitoring scenes - Intelligent detection: Intrusion, tripwire		IRR 42,800,000
		DH-IPC-HFW2230SP-S-0360B-S2-QH3		> 2MP, 1/2.7" CMOS image sensor, low illumination, high image definition > Outputs 2MP (1920 x 1080) @25/30 fps > H.265 codec, high compression rate, ultra-low bit rate > Built-in IR LED, max IR distance: 30 m > ROI, SMART H.264+/H.265+, flexible coding, applicable to various bandwidth and storage environments > Rotation mode, DWDNR, 3D NR, HLC, BLC, digital watermarking, applicable to various monitoring scenes > Intelligent detection: Intrusion, tripwire > Abnormality detection: Motion detection, video tampering, no SD card, SD card full, SD card error, network disconnected, IP conflict, illegal access, voltage detection > Supports max. 256 GB Micro SD card & 12V DC/PoE power supply > IP67 protection	IRR 38,640,000	
		DH-IPC-HFW2230SP-S-0280B-S2-QH3		> H.265 codec, high compression rate, ultra-low bit rate > Built-in IR LED, max IR distance: 30 m > ROI, SMART H.264+/H.265+, flexible coding, applicable to various bandwidth and storage environments > Rotation mode, DWDNR, 3D NR, HLC, BLC, digital watermarking, applicable to various monitoring scenes > Intelligent detection: Intrusion, tripwire > Abnormality detection: Motion detection, video tampering, no SD card, SD card full, SD card error, network disconnected,	IRR 38,640,000	IRR 30,900,000
		DH-IPC-HDBW2231S-S-S2				
		IPC-HDBW2231EP-S-0280B-S2-QH		> 2MP, 1/2.8" CMOS image sensor, low illumination, high image definition > Outputs 2MP (1920 x 1080) @ 25/30 fps > H.265 codec, high compression rate, ultra-low bit rate > Built-in IR LED, max IR distance: 30 m > ROI, SMART H.264+/H.265+, flexible coding, applicable to various bandwidth and storage environments > Rotation mode, WDR, 3D NR, HLC, BLC, digital watermarking, applicable to various monitoring scenes	IRR 46,550,000	IRR 43,680,000
		DH-IPC-HDW2231TM-AS-S2		2MP Lite IR Fixed-focal Eyeball Network Camera > 2MP 1/2.8" CMOS image sensor, low luminance, and high definition image. > Outputs max. 2MP (1920 x 1080) @25/30 fps. > H.265 codec, high compression rate, ultra-low bit rate. > Built-in IR LED, and the max. illumination distance is 30 m. > ROI, SMART H.264+/H.265+, flexible coding, applicable to various bandwidth and storage environments. > Rotation mode, WDR, 3D NR, HLC, BLC, digital watermarking, applicable to various monitoring		
		DH-IPC-HFW2231TP-ZS-27135-S2-QH		2MP, 1/2.8" CMOS image sensor, low illumination, high image definition Outputs 2MP (1920 x 1080) @25/30 fps H.265 codec, high compression rate, ultra-low bit rate Built-in IR LED, max IR distance: 60 m ROI, SMART H.264+/H.265+, flexible coding, applicable to various bandwidth and storage environments	IRR 73,910,000	IRR 66,380,000
		DH-IPC-HDW2231TMP-AS-0280B-S2-QH		2MP, 1/2.8" CMOS image sensor, low illumination, high image definition - Outputs max. 2MP (1920 x 1080) @25/30 fps - H.265 codec, high compression rate, ultra-low bit rate - Built-in IR LED, max IR distance: 30 m - ROI, SMART H.264+/H.265, flexible coding, applicable to various bandwidth and storage environments - Rotation mode, WDR, 3D DNR, HLC, BLC, digital watermarking, applicable to various monitoring scenes - Intelligent detection: Intrusion, tripwire	IRR 49,740,000	
		IPC-HDBW2231RP-ZS-27135-S2-QH		Dahua IP Dome. 2MP@25fps, H.265+/H.264+, ICR, 0.002 lux, Smart IR 40m. Motorized optics 2.7-13.5 mm. WDR 120dB, 3D-NR, 4 ROIs. IVS intelligence. MicroSD slot, R45, Onvif, IP67, IK10, 3AXIS, PoE.		IRR 44,600,000
		DH-IPC-HDW2239TP-AS-LED-S2		2MP Lite IR Fixed-focal Eyeball Network Camera - 2MP, 1/2.8" CMOS image sensor, low illumination, high image definition - Outputs max. 2MP (1920 x 1080) @25/30 fps - H.265 codec, high compression rate, ultra-low bit rate - Built-in warm lights, max illumination distance: 30 m - ROI, SMART H.264+/H.265+, flexible coding, applicable to various bandwidth and storage environments - Rotation mode, WDR, 3D DNR, HLC, BLC, digital watermarking, applicable to various monitoring scenes - Intelligent detection: Intrusion, tripwire - Abnormality detection: Motion detection, video tampering, scene changing, no	IRR 45,970,000	IRR 43,600,000
		DH-IPC-B1B20P-L		2MP IR Mini-Bullet Network Camera - 1/2.7" 2Megapixel progressive CMOS - H.265+ & H.265 dual-stream encoding - 25/30fps@1080P(1920x1080) - DWDNR, Day/Night(ICR), 3DNR, AWB, AGC, BLC - Multiple network monitoring: Web viewer, CMS(DSS/PSS) & DMSS - 2.8 mm fixed lens (3.6mm optional) - Max IR LEDs Length 30m - IP67, PoE		
		DH-IPC-B1B20P		1/2.7" 2Megapixel progressive CMOS - H.265+ & H.265 dual-stream encoding - 25/30fps@1080P(1920x1080) - DWDNR, Day/Night(ICR), 3DNR, AWB, AGC, BLC - Multiple network monitoring: Web viewer, CMS(DSS/PSS) & - 2.8 mm fixed lens (3.6mm optional) - Max IR LEDs Length 30m - IP67, PoE		













		DH-IPC-B1B40P		<ul style="list-style-type: none"> · 1/3" 4Megapixel progressive CMOS · H.265+ & H.265 dual-stream encoding · 20fps@4M(2560x1440) & 25/30fps@3M(2304x1296) · DWDR, Day/Night(ICR), 3DNR, AWB, AGC, BLC · Multiple network monitoring: Web viewer, CMS(DSS/PSS) & DMSS · 2.8 mm fixed lens (3.6mm optional) · Max IR LEDs Length 30m. IP67, PoE 		
		DH-IPC-B2B20P-ZS		<ul style="list-style-type: none"> · 1/2.7" 2Megapixel progressive CMOS · H.265+ & H.265 dual-stream encoding · 25/30fps@1080P(1920x1080) · 2.8~12mm motorized lens · DWDR, Day/Night(ICR), 3DNR, AWB, AGC, BLC · Multiple network monitoring: Web viewer, CMS(DSS/PSS) & DMSS · Max IR LEDs Length 40m · Micro SD card memory, IP67, PoE7 		
		DH-IPC-B2B40P-ZS		<ul style="list-style-type: none"> · 1/3" 4Megapixel progressive CMOS · H.265+ & H.265 dual-stream encoding · 2.8~12mm motorized lens · 20fps@4M(2560x1440) & 25/30fps@3M(2304x1296) · DWDR, Day/Night(ICR), 3DNR, AWB, AGC, BLC · Multiple network monitoring: Web viewer, CMS(DSS/PSS) & DM 		
250325		DH-IPC-HFW1238S1P-LED		<ul style="list-style-type: none"> · 2MP, 1/2.7" CMOS image sensor, low illumination, high image definition · Outputs max. 2MP (1920 x 1080) @ 25/30 fps · H.265 codec, high compression rate, ultra-low bit rate · Built-in LEDs, max LED distance: 15 m · ROI, SMART H.264/H.265, flexible coding, applicable to various bandwidth and storage environments · Rotation mode, DWDR, 3D DNR, HLC, BLC, digital watermarking, applicable to various monitoring scenes · Abnormality detection: Motion detection, video tampering, network disconnection, IP conflict, illegal access · 12V DC/PoE power support, · IP67 protection 		
		DH-IPC-HDW1230SP-0280B-S5-QH2		<ul style="list-style-type: none"> · 1/2.7" 2Megapixel progressive CMOS · H.265 & H.264 dual-stream encoding · 25/30fps@1080P(1920x1080) · DWDR, Day/Night(ICR), 3DNR, HLC, AGC, BLC · Multiple network monitoring: Web viewer, CMS(DSS/PSS) & DMSS · 2.8 mm fixed lens (3.6mm optional) · Max IR LEDs Length 30m · IP67, PoE 	IRR 31,260,000	IRR 31,000,000
		IPC-HDW1230SP-LED		<ul style="list-style-type: none"> · 2MP, 1/2.8" CMOS image sensor, low illumination, high image definition · Outputs max. 2MP (1920 x 1080) @ 25/30 fps · H.265 codec, high compression rate, ultra-low bit rate · Built-in efficient IR illuminator, and the max. illumination distance is 30 m · ROI, SMART H.264/H.265+, flexible coding, applicable to various bandwidth and storage environments · Rotation mode, DWDR, 3D NR, HLC, BLC, digital watermarking, applicable to various monitoring scenes · Abnormality detection: Motion detection, video tampering, network disconnection, IP conflict, illegal access 		
		DH-IPC-HDW1230T1P-0280B-S5-QH2		<ul style="list-style-type: none"> · Outputs max. 2MP (1920 x 1080) @ 25/30 fps · H.265 codec, high compression rate, ultra-low bit rate · Built-in LEDs, max LED distance: 15 m · ROI, SMART H.264/H.265, flexible coding, applicable to various bandwidth and storage environments · Rotation mode, DWDR, 3D DNR, HLC, BLC, digital watermarking, applicable to various monitoring scenes · Abnormality detection: Motion detection, video tampering, network disconnection, IP conflict, illegal access · 12V DC/PoE power support, · IP67 protection 	IRR 29,300,000	
		DH-IPC-HDW1230T1P-0360B-S5-QH2		<ul style="list-style-type: none"> · 2MP, 1/2.7" CMOS image sensor, low illumination, high image definition · Outputs max. 2MP (1920 x 1080) @ 25/30 fps · H.265 codec, high compression rate, ultra-low bit rate · Built-in LEDs, max LED distance: 15 m · ROI, SMART H.264/H.265, flexible coding, applicable to various bandwidth and storage environments · Rotation mode, DWDR, 3D DNR, HLC, BLC, digital watermarking, applicable to various monitoring scenes · Abnormality detection: Motion detection, video tampering, network disconnection, IP conflict, illegal access · 12V DC/PoE power support, · IP67 protection 	IRR 29,300,000	
		DH-IPC-HDBW1230EP		<ul style="list-style-type: none"> · 1/2.7" 2Megapixel progressive CMOS · H.265 & H.264 dual-stream encoding · 25/30fps@1080P(1920x1080) · DWDR, Day/Night(ICR), 3DNR, AWB, AGC, BLC · Multiple network monitoring: Web viewer, CMS(DSS/PSS) & DMSS · 2.8mm fixed lens (3.6mm optional) · Max IR LEDs length 30m. · IP67, IK10, PoE 		
		DH-IPC-HDBW1431EP-S4		<ul style="list-style-type: none"> · 1/3" 4Megapixel progressive CMOS · H.265& H.264 dual-stream encoding · 20fps@4M(2688x1520) & 25/30fps@3M(2304x1296) · WDR(120db), Day/Night(ICR), 3DNR, AWB, AGC, BLC · Multiple network monitoring: Web viewer, CMS(DSS/PSS) & DMSS · 2.8 mm fixed lens (3.6 mm optional) · Max IR LEDs Length 30m · IP67, IK10, PoE 	IRR 44,960,000	
250585	210585	DH-IPC-HDBW2531EP-S-52		<ul style="list-style-type: none"> · SMP Lite IR Fixed-focal Dome Network Camera, STARLIGHT · SMP, 1/2.7" CMOS image sensor, low illumination, high image definition · Outputs max. SMP (2592 x 1944) @ 20 fps, and supports 2688 x 1520 (2688 x 1520) @ 25/30 fps · H.265 codec, high compression rate, ultra-low bit rate · Built-in IR LED, max IR distance: 30 m · ROI, SMART H.264+/H.265+, flexible coding, applicable to various bandwidth and storage environments · Rotation mode, WDR, 3D NR, HLC, BLC, digital watermarking, applicable to various monitoring scenes, Intelligent detection: Intrusion, tripwire · Abnormality detection: Motion detection, video tampering, no SD card, SD card full, SD card error, network disconnected, IP conflict, illegal access, voltage detection · Supports max. 256 GB Micro SD card. 12V DC/PoE power supply, · IP67, IK10 protection 	IRR 36,850,000	
250437		DH-IPC-HDBW2431RP-ZS		<ul style="list-style-type: none"> · 1/3" 4MP WDR IR Dome Network Camera · H.265 & H.264 dual-stream encoding · 20fps@4M(2688x1520)&25/30fps@3M(2304x1296) · WDR(120db), Day/Night(ICR), 3DNR, AWB, AGC, BLC · Multiple network monitoring: Web viewer, CMS(DSS/PSS) & DMSS · Micro SD card slot, up to 128GB · 2.7~13.5mm motorized lens, · Max IR LEDs Length 30m · IP67, IK10, PoE 		













	DH-IPC-HDBW2531RP-ZS		<ul style="list-style-type: none"> ·5MP WDR IR Dome Network Camera IP6730m ·1/2.7" 5Megapixel progressive CMOS, H.265 & H.264 dual-stream encoding ·15fps@5M(2592x1944)&25/30fps@3M(2304x1296) ·WDR(120dB), Day/Night(ICR), 3DNR, AWB, AGC, BLC ·Multiple network monitoring: Web viewer, CMS(DSS/PSS) & DMSS ·Micro SD card slot, up to 128GB ·2.7~13.5mm motorized lens; Max IR LEDs Length 30m, IP67, IK10, PoE 		
	DH-IPC-HDBW2831RP-ZS		<ul style="list-style-type: none"> ·1/1.8" 8Megapixel progressive CMOS ·H.265 & H.264 dual-stream encoding ·25/30fps@8MP(3840x2160) ·WDR(120dB), Day/Night(ICR), 3DNR, AWB, AGC, BLC ·Multiple network monitoring: Web viewer, CMS(DSS/PSS) & DMSS ·Micro SD card slot, up to 128GB ·IP67, IK10, PoE ·3.7~11mm motorized lens·Max IR LEDs Length 30m 	IRR 117,020,000	
	IPC-HDBW3241FP-AS-M		<p>Dahua,WizSense series network camera, Full HD, 2MP, vandal-resistant compact IR Mini Dome, 2.8mm lens, IVS, SMD, IP67, IK10</p> <p>1/2.8 inch progressive scan CMOS 2Mp, Starlight, H.264 / H.265 & triple stream encoding, Max 25fps @ 2M (1920 x 1080), 120dB WDR, 3DNR, HLC, BLC, 2.8mm lens, D&N(ICR), IR LEDs: 50m, micro SD card slot, microphone built-in, IVS, smart motion detection, perimeter detection, IP67, IK10, PoE and 12 VDC</p>		
	IPC-HFW3241EP-SA-		<ul style="list-style-type: none"> ·2MP, 1/2.8" CMOS image sensor, low illumination, high image definition · Outputs max. 2MP (1920 x 1080)@30 fps ·H.265 codec, high compression rate, low bit rate ·Built-in IR LED, max. IR distance: 50 m ·ROI, SMART H.264+/H.265+, flexible coding, applicable to various bandwidth and storage environments ·Rotation mode, WDR, 3D DNR, HLC, BLC, digital watermarking, applicable to various monitoring scenes ·Intelligent detection: Intrusion, tripwire (support the classification and accurate detection of vehicle and human) ·Abnormality detection: Motion detection, video tampering, scene changing, audio detection, no SD card, SD card full, SD card error, network disconnection, IP conflict, illegal access, voltage detection ·Supports max. 256 G Micro SD card, built-in Mic ·12V DC/POE power support ·IP67 protection ·SMD 	IRR 58,500,000	
	DH-IPC-HDBW3441EP-S		<ul style="list-style-type: none"> ·4MP IR Fixed focal Dome WizSense Network Camera ·4MP, 1/3" CMOS image sensor, low illumination, high image definition ·Outputs max. 4MP (2688 x 1520)@30 fps ·H.265 codec, high compression rate, low bit rate, ·Built-in IR LED, max. IR distance: 50 m ·ROI, SMART H.264+/H.265+, flexible coding, applicable to various bandwidth and storage environments ·Rotation mode, WDR, 3D DNR, HLC, BLC, digital watermarking, applicable to various monitoring scenes ·Intelligent detection: Intrusion, tripwire (support the classification and accurate detection of vehicle and human) ·Abnormality detection: Motion detection, video tampering, scene changing, no SD card, SD card full, SD card error, network disconnection, IP conflict, illegal access, voltage detection ·Supports max. 256 G Micro SD card ·12V DC/POE power supply, IP67, IK10 protection, SMD Plus 		
	DH-IPC-HDBW3441EP-AS		<ul style="list-style-type: none"> ·4MP IR Fixed focal Dome WizSense Network Camera, STARLIGHT ·4MP, 1/3" CMOS image sensor, low illumination, high image definition ·Outputs max. 4MP (2688 x 1520)@30 fps ·H.265 codec, high compression rate, low bit rate, ·Built-in IR LED, max. IR distance: 50 m ·ROI, SMART H.264+/H.265+, flexible coding, applicable to various bandwidth and storage environments ·Rotation mode, WDR, 3D DNR, HLC, BLC, digital watermarking, applicable to various monitoring scenes ·Intelligent detection: Intrusion, tripwire (support the classification and accurate detection of vehicle and human) ·Abnormality detection: Motion detection, video tampering, scene changing, audio abnormality detection, no SD card, SD card full, SD card error, network disconnection, IP conflict, illegal access, voltage detection ·Alarm: In, out; Audio: In, out; Supports max. 256 G Micro SD card ·12V DC/POE power supply, ·IP67, IK10 protection, SMD Plus 		
	DH-IPC-HDW3441TMP-AS		<ul style="list-style-type: none"> ·4MP IR Fixed focal Eyeball WizSense Network Camera ·1/3"4Megapixel progressive CMOS ·Min. Illumination:0.005 Lux@F1.6 ·2.8mm Motorized lens ·25/30fps@4Mp(2688x1520) ·SMART H.264+/H.265+ triple-stream encoding ·IVS(Tripwire: intrusion (Recognition of human and vehicle)) ·WDR(120dB), Day/Night(ICR), 3DNR, AWB, AGC, BLC, HLC, ROI ·Built-in Mic, Micro SD memory 256GB ·Max. IR LEDs Length 50m, Smart IR, IP67, PoE 	IRR 66,760,000	
	DH-IPC-HDW3449TMP-AS-LED		<ul style="list-style-type: none"> ·4MP, 1/2.7" CMOS image sensor, low illumination, high image definition ·Outputs max. 4MP (2688 x 1520) @ 30 fps ·H.265 codec, high compression rate, low bit rate ·Built-in Warm LED, max. LEDs distance: 30 m ·ROI, SMART H.264+/H.265+, flexible coding, applicable to various bandwidth and storage environments ·Rotation mode, WDR, 3D DNR, HLC, BLC, digital watermarking, applicable to various monitoring scenes ·Intelligent detection: Intrusion, tripwire (support the classification and accurate detection of vehicle and human) ·Abnormality detection: Motion detection, video tampering, scene changing, audio detection, no SD card, SD card full, SD card error, network disconnection, IP conflict, illegal access, voltage detection ·Supports max. 256 G Micro SD card, built-in Mic ·12V DC/PoE power support, ·IP67 protection ·SMD Plus 	IRR 72,610,000	IRR 65,450,000
	DH-IPC-HDBW3441RP-ZAS		<ul style="list-style-type: none"> ·4MP IR Vari-focal Dome WizSense Network Camera ·4MP, 1/3" CMOS image sensor, low illumination, high image definition ·Outputs max. 4MP (2688 x 1520)@30 fps. H.265 codec, high compression rate, low bit rate ·Built-in IR LED, max. IR distance: 40 m ·ROI, SMART H.264+/H.265+, flexible coding, applicable to various bandwidth and storage environments ·Rotation mode, WDR, 3D DNR, HLC, BLC, digital watermarking, applicable to various monitoring scenes ·Intelligent detection: Intrusion, tripwire (support the classification and accurate detection of vehicle and human) ·Abnormality detection: Motion detection, video tampering, scene changing, no SD card, SD card full, SD card error, network disconnection, IP conflict, illegal access, voltage detection ·Supports max. 256 G Micro SD card ·12V DC/POE power supply, ·IP67, IK10 protection, SMD Plus 	IRR 105,000,000	
	DH-IPC-HDW4831EMP-ASE		<ul style="list-style-type: none"> ·1/2.5" 8Megapixel progressive scan STARVIS™ CMOS ·H.265&H.264 triple-stream encoding ·15fps@4K(3840x2160),25/30fps@3M(2304x1296) ·Smart detection supported ·WDR(120dB), Day/Night(ICR), 3DNR,AWB,AGC,BLC ·Multiple network monitoring: Web viewer, CMS(DSS/PSS) & DMSS ·2.8mm fixed lens (4mm optional)- Built-in Mic ·Max. IR LEDs Length 50m, Micro SD memory, IP67, PoE 		















		DH-IPC-HDW4431EMP-AS		<ul style="list-style-type: none"> -1/3" 4Megapixel progressive scan CMOS -H.265&H.264 triple-stream encoding -25/30fps@4M(2688x1520)- Smart Detection supported -WDR(120dB), Day/Night(ICR), 3DNR,AWB,AGC,BLC -2.8mm fixed lens (3.6mm, 6mm optional) -Max. IR LEDs Length 50m -Built-in Mic- Micro SD memory, IP67, PoE 		
		DH-IPC-HDBW4431EP-S		<ul style="list-style-type: none"> -1/3" 4Megapixel progressive scan CMOS -H.265&H.264 triple-stream encoding -25/30fps@4Mp(2688x1520) - Smart Detection supported -WDR(120dB), Day/Night(ICR), 3DNR,AWB,AGC,BLC -Multiple network monitoring: Web viewer, CMS(DSS/PSS) & DMSS -2.8mm fixed lens (3.6mm, 6mm optional) -Max. IR LEDs Length 30m- Micro SD memory 256GB, IP67, IK10, PoE 		
		DH-IPC-HDBW4831EP-ASE		<ul style="list-style-type: none"> -1/2.5" 8Megapixel progressive scan STARVIS™ CMOS -H.265&H.264 triple-stream encoding -15fps@4K(3840x2160),25/30fps@3M(2304x1296) - Smart Detection supported, -WDR(120dB), Day/Night(ICR), 3DNR,AWB,AGC,BLC -Multiple network monitoring: Web viewer, CMS(DSS/PSS) & DMSS -2.8mm fixed lens (4mm optional); 1/1 Alarm in/out, 1/1 audio in/out -Max. IR LEDs Length 30m- Micro SD memory, IP67, IK10, PoE 		
		IPC-HDBW5242E-ZE-MF		<ul style="list-style-type: none"> 2MP IR Vari-focal Dome WizMind Network Camera > 1/1.8" 2Megapixel progressive scan CMOS > ROI, SVC, SMART H.264+/H.265+, AI H.264/H.265, flexible coding, applicable to various bandwidth and storage environments > 50/60 fps@1080P (1920 x 1080) > WDR (140 db), Day/Night (ICR), 3D NR, AWB, AGC, BLC > Multiple network monitoring: Web viewer, CMS (DSS/PSS) & DMSS > 2.7 mm-12.0 mm motorized lens, > 1/1 Alarm in/out, 1/1 audio in/out > Max. IR LEDs Length 40 m, > Micro SD memory, IP67, IK10, > SMD 3.0 		IRR 133,000,000
		DH-IPC-HDW5431RP-ZE		<ul style="list-style-type: none"> -1/3" 4Megapixel progressive scan CMOS -H.265&H.264 triple-stream encoding -25/30fps@4Mp(2688x1520)- Built-in Mic -WDR(120dB), Day/Night(ICR), 3DNR, AWB, AGC, BLC -Multiple network monitoring: Web viewer, CMS(DSS/PSS) & DMSS -2.7mm ~13.5mm motorized lens- Max. IR LEDs Length 50m -Micro SD card memory, IP67, PoE 		
		DH-IPC-HDBW5831RP-ZE		<ul style="list-style-type: none"> 8MP WDR IR Dome Network Camera > 1/2.5" 8Megapixel progressive scan STARVIS™ CMOS > H.265&H.264 dual-stream encoding > 15fps@4K(3840x2160),25/30fps@3M(2304x1296),> Day/Night(ICR), 3DNR, AWB, AGC, BLC > Multiple network monitoring: Web viewer, CMS(DSS/PSS) & DMSS > 2.7mm ~12mm motorized lens- Max. IR LEDs Length 50m > Micro SD card memory, IP67,IK10, PoE 		
		DH-IPC-HDBW5431RP-ZE		<ul style="list-style-type: none"> -4MP WDR IR Dome Network Camera -1/3" 4Megapixel progressive scan CMOS -H.265&H.264 triple-stream encoding -25/30fps@4Mp(2688x1520) -WDR(120dB), Day/Night(ICR), 3DNR, AWB, AGC, BLC -Multiple network monitoring: Web viewer, CMS(DSS/PSS) & DMSS -2.7mm ~13.5mm motorized lens -Max. IR LEDs Length 50m- Micro SD card memory, IP67,IK10, PoE 		
		DH-IPC-HDBW5442EP-ZE		<ul style="list-style-type: none"> -4MP IR Vari-focal Dome WizMind Network Camera -1/1.8" 4Megapixel progressive scan CMOS -ROI, SMART H.264+/H.265+, flexible coding, applicable to various bandwidth and storage environments -25/30 fps@2688 x 1520, 50/60 fps@1080P (1920 x 1080) -WDR (140 db), Day/Night (ICR), 3D DNR, AWB, AGC, BLC -Multiple network monitoring: Web viewer, CMS (DSS/PSS) & DMSS -2.7 mm-12.0 mm motorized lens - 1/1 Alarm in/out, 1/1 audio in/out -Max. IR LEDs Length 40 m. Micro SD memory, IP67, IK10 	IRR 147,410,000	IRR 124,000,000
		DH-IPC-HDBW5631EP-ZE		<ul style="list-style-type: none"> 31EP-ZE -1/2.9" 6Megapixel progressive scan STARVIS™ CMOS -H.265&H.264 dual-stream encoding -20fps@6M(3072x2048),25/30fps@4M(2688x1520) -Day/Night(ICR), 3DNR, AWB, AGC, BLC -Multiple network monitoring: Web viewer, CMS(DSS/PSS) & DMSS -2.7mm ~13.5mm motorized lens -Max. IR LEDs Length 50m, - Micro SD card memory, IP67,IK10, PoE+ 		
		IPC-HF5241EP-E		<ul style="list-style-type: none"> 2 MP Box WizMind Network Camera > 2-MP 1/2.8" CMOS image sensor, low luminance, and high definition image. > Outputs max. 2 MP (1920 x 1080) @ 30 fps, > H.265 codec, high compression rate, ultra-low bit rate > ROI, SMART H.264+/H.265+, AI H.264/H.265, flexible coding, applicable to various bandwidth and storage environments. > Rotation mode, WDR, 3D NR, HLC, BLC, digital watermarking, applicable to various monitoring scenes. > Intelligent monitoring: Intrusion, tripwire, fast moving (the three functions support the classification and accurate detection of vehicle and human); abandoned object, missing object, loitering detection, people gathering, parking detection, heat map and face detection. -Abnormality detection: Motion detection, video tampering, network disconnection, IP conflict, illegal access, Supports max. 256 GB Micro SD card 		IRR 98,600,000
		DH-IPC-K22P		<ul style="list-style-type: none"> P -2MP, 1/2.7" CMOS image sensor, low illumination, high image definition -Outputs max. 2MP (1920 x 1080) @ 25/30 fps -H.265 codec, high compression rate, ultra-low bit rate -Max. IR distance: 10 m -Rotation mode, WDR, 3D DNR, HLC, BLC, digital watermarking, applicable to various monitoring scenes -H.264/H.265, flexible coding, applicable to various bandwidth and storage environments. -Alarm: 1 in, 1 out; 256 G SD card, built-in Mic and speaker -Supports 256 G Micro SD card, 12V DC power supply, easy for installation -Supports PIR. Supports Wi-Fi 		
		DH-IPC-K100W		<ul style="list-style-type: none"> -1/3" 1.3Megapixel Aptina CMOS -H.264 & MIPEG dual-stream encoding -Max 15fps@1.3M (1280x960)/25/30fps@720P(1280x720) -DWDR, Day/Night, 2DNR, Auto iris, AWB, AGC, BLC -Multiple network monitoring: Web viewer, CMS(DSS/PSS) & DMSS -3.6mm fixed lens • White LEDs length 10m -PIR sensor range 6m • Micro SD memory, Wi-Fi 		
		DH-IPC-HFW1230T1P-ZS		<ul style="list-style-type: none"> -2MP, 1/2.8" CMOS image sensor, low illumination, high image definition -Outputs max. 2MP (1920 x 1080p) @25/30 fps -H.265 codec, high compression rate, ultra-low bit rate -Built-in IR LED, max. IR distance: 50 m -ROI, SMART H.264+/H.265+, flexible coding, applicable to various bandwidth and storage environments -Rotation mode, DWDR, 3D DNR, HLC, BLC, digital watermarking, applicable to various monitoring scenes -Abnormality detection: Motion detection, video tampering, network disconnection, IP conflict, illegal access, Supports max. 256 GB Micro SD card -12V DC/PoE power supply, IP67 protection 		
















		DH-IPC-HFW1330SP		<ul style="list-style-type: none"> · 1/3" 3Megapixel progressive CMOS · H.264+ & H.264 dual-stream encoding · 20fps@3M(2048x1536)&25/30fps@1080P(1920x1080) · WDR, Day/Night(ICR), 3DNR, AWB, AGC, BLC · Multiple network monitoring: Web viewer, CMS(DSS/PSS) & DMSS · 2.8mm fixed lens (3.6mm 6mm optional) · Max IR LEDs Length 30m IP67, PoE 		
		DH-IPC-HDW1431SP-0280B-S4			IRR 41,700,000	
		DH-IPC-HFW1431S1P-0280B-S4		<ul style="list-style-type: none"> · 4MP, 1/3" CMOS image sensor, low illumination, high image definition · Outputs 4MP (2560 x 1440) @25/30 fps, and supports max. 4MP (2688 x 1520) @20 fps · H.265 codec, high compression rate, ultra-low bit rate · Built-in IR LED, max. IR distance: 30 m · ROI, SMART H.264/H.265, flexible coding, applicable to various bandwidth and storage environments · Image flip, WDR, 3D DNR, HLC, BLC, digital watermarking, applicable to various monitoring scenes · Abnormality detection: Motion detection, video tampering, network disconnection, IP conflict, illegal access, voltage detection · 12V DC/PoE power support, IP67, protection 	IRR 37,390,000	
		DH-IPC-HDW1530T-S6		<ul style="list-style-type: none"> · 5MP, 1/2.7" CMOS image sensor, low illumination, high image definition image. · Outputs max. 5MP (2880 x 1620) @20 fps and supports 2688 x 1520 (2688 x 1520) @25/30 fps. · H.265 codec, high compression rate, and ultra-low bit rate. · Built-in IR LED, and the max. illumination distance is 30 m. · ROI, SMART H.264+/H.265+, flexible coding, applicable to various bandwidth and storage environments. 		
		DH-IPC-HFW1831EP		<ul style="list-style-type: none"> · 1/1.8" 8Megapixel progressive scan CMOS · H.265&H.264 dual-stream encoding · 25/30fps@8MP(3840x2160) · WDR(120dB), Day/Night(ICR), 3DNR, AWB, AGC, BLC · Multiple network monitoring: Web viewer, CMS(DSS/PSS) & DMSS · 2.8mm fixed lens (4mm, 6mm optional), Max. IR LEDs Length 50m IP67, PoE 		
		DH-IPC-HFW2231T-ZS		<ul style="list-style-type: none"> · 1/2.8" 2Megapixel progressive STARVIS™ CMOS · H.265 & H.264 dual-stream encoding · 25/30fps@1080P(1920x1080) · WDR(120dB), Day/Night(ICR), 3DNR, AWB, AGC, BLC · Multiple network monitoring: Web viewer, CMS(DSS/PSS) & DMSS · Micro SD card slot, up to 128GB · 2.7~13.5mm motorized lens: Max IR LEDs Length 60m, IP67, IK10(optional), PoE 		
		DH-IPC-HFW2531SP-S-0208B-S2		<ul style="list-style-type: none"> · SMP Lite IR Fixed-focal Bullet Network Camera STARLIGHT · SMP, 1/2.7" CMOS image sensor, low illumination, high image definition · Outputs max. 5MP (2592 x 1944) @20 fps, and supports 2688 x 1520 (2688 x 1520) @25/30 fps · H.265 codec, high compression rate, ultra-low bit rate · Built-in IR LED, max IR distance: 30 m · ROI, SMART H.264+/H.265+, flexible coding, applicable to various bandwidth and storage environments · Rotation mode, WDR, 3D NR, HLC, BLC, digital watermarking, applicable to various monitoring scenes, intelligent detection: intrusion, tripwire · Abnormality detection: Motion detection, video tampering, no SD card, SD card full, SD card error, network disconnected, IP conflict, illegal access, voltage detection · Supports max. 256 GB Micro SD card, 12V DC/PoE power supply IP67 protection 	IRR 55,140,000	
		DH-IPC-HFW2531SP-S-0360B-S2		<ul style="list-style-type: none"> · SMP Lite IR Fixed-focal Bullet Network Camera STARLIGHT · SMP, 1/2.7" CMOS image sensor, low illumination, high image definition · Outputs max. 5MP (2592 x 1944) @20 fps, and supports 2688 x 1520 (2688 x 1520) @25/30 fps · H.265 codec, high compression rate, ultra-low bit rate · Built-in IR LED, max IR distance: 30 m · ROI, SMART H.264+/H.265+, flexible coding, applicable to various bandwidth and storage environments · Rotation mode, WDR, 3D NR, HLC, BLC, digital watermarking, applicable to various monitoring scenes, intelligent detection: intrusion, tripwire · Abnormality detection: Motion detection, video tampering, no SD card, SD card full, SD card error, network disconnected, IP conflict, illegal access, voltage detection · Supports max. 256 GB Micro SD card, 12V DC/PoE power supply IP67 protection 	IRR 36,850,000	
		DH-IPC-HDW2531TP-AS		<ul style="list-style-type: none"> · 1/2.7" 5Megapixel progressive CMOS · H.265 & H.264 dual-stream encoding · 15fps@5M(2592x1944)&25/30fps@3M(2304x1296) · WDR(120dB), Day/Night(ICR), 3DNR, AWB, AGC, BLC · Multiple network monitoring: Web viewer, CMS(DSS/PSS) & DMSS · Micro SD card slot, up to 128GB IP67, PoE+ · 2.7~13.5mm motorized lens: Max IR LEDs Length 60m 	IRR 55,140,000	IRR 64,800,000
		DH-IPC-HFW2531TP-AS		<ul style="list-style-type: none"> · 1/2.7" 5Megapixel progressive CMOS · H.265 & H.264 dual-stream encoding · 15fps@5M(2592x1944)&25/30fps@3M(2304x1296) · WDR(120dB), Day/Night(ICR), 3DNR, AWB, AGC, BLC · Multiple network monitoring: Web viewer, CMS(DSS/PSS) & DMSS · Micro SD card slot, up to 128GB IP67, PoE+ · 2.7~13.5mm motorized lens: Max IR LEDs Length 60m 	IRR 79,700,000	
250692	210692	DH-IPC-HFW2831SP-S		<ul style="list-style-type: none"> · SMP Lite IR Fixed-focal Bullet Network Camera · > 8MP, 1/2.7" CMOS image sensor, low illumination, high image definition · > Outputs max. 8MP (3840 x 2160) @15 fps, and supports 2688x1520 (2688 x 1520) @25/30 fps · > H.265 codec, high compression rate, ultra-low bit rate · > Built-in IR LED, max IR distance: 30 m · > ROI, SMART H.264+/H.265+, flexible coding, applicable to various bandwidth and storage environments · > Rotation mode, WDR, 3D NR, HLC, BLC, digital watermarking, applicable to various monitoring scenes · > Intelligent detection: Intrusion, tripwire · > Abnormality detection: Motion detection, video tampering, no SD card, SD card full, SD card error, network disconnected, IP conflict, illegal access, voltage detection 	IRR 55,480,000	IRR 78,600,000
		DH-IPC-HFW2831TP-AS				
250555		DH-IPC-HFW2831TP-ZS		<ul style="list-style-type: none"> · 1/1.8" 8Megapixel progressive CMOS · H.265 & H.264 dual-stream encoding · 25/30fps@8MP(3840x2160) · WDR(120dB), Day/Night(ICR), 3DNR, AWB, AGC, BLC · Multiple network monitoring: Web viewer, CMS(DSS/PSS) & DMSS · Micro SD card slot, up to 128GB 3.7~11mm motorized lens · Max IR LEDs Length 60m IP67, IK10(optional), PoE 	IRR 112,870,000	IRR 123,000,000














		DH-IPC-HFW3441EP-SA		<ul style="list-style-type: none"> 4MP, 1/3" CMOS image sensor, low illumination, high image definition Outputs max. 4MP (2688 x 1520)@30fps; H.265 codec, high compression rate, low bit rate Built-in IR LED, max. IR distance: 50 m ROI, SMART H.264+/H.265+, flexible coding, applicable to various bandwidth and storage environments Rotation mode, WDR, 3D DNR, HLC, BLC, digital watermarking, applicable to various monitoring scenes Intelligent detection: Intrusion, tripwire (support the classification and accurate detection of vehicle and human) Abnormality detection: Motion detection, video tampering, scene changing, audio detection, no SD card, SD card full, SD card error, network disconnection, IP conflict, illegal access, voltage detection, Supports max. 256 G Micro SD card, built-in Mic 12V DC/PoE power supply, IP67 protection - SMD Plus 	IRR 65,190,000	IRR 71,800,000
		DH-IPC-HFW3449EP-AS-LED		<ul style="list-style-type: none"> 4MP, 1/2.7" CMOS image sensor, low illumination, high image definition Outputs max. 4MP (2688 x 1520) @ 30fps; H.265 codec, high compression rate, low bit rate. Built-in Warm LED, max. LED distance: 30 m ROI, SMART H.264+/H.265+, flexible coding, applicable to various bandwidth and storage environments Rotation mode, WDR, 3D DNR, HLC, BLC, digital watermarking, applicable to various monitoring scenes Intelligent detection: Intrusion, tripwire (support the classification and accurate detection of vehicle and human) Abnormality detection: Motion detection, video tampering, scene changing, audio detection, no SD card, SD card full, SD card error, network disconnection, IP conflict, illegal access, voltage detection Alarm: 1 in, 1 out; audio: 1 in, 1 out; supports max. 256 G Micro SD card, built-in Mic 12V DC/PoE power support, IP67 protection - SMD Plus 	IRR 79,250,000	IRR 70,910,000
		DH-IPC-HFW4431EP-S-54		<ul style="list-style-type: none"> 1/3" 4 Megapixel progressive scan CMOS H.265 & H.264 triple-stream encoding 25/30fps@4MP(2688 x 1520) True Day/Night (ICR); WDR; BLC; 3DNR; AWB; AGC, Corridor Mode; Privacy Zones; Motion Detection Smart Functions: Tripwire; Intrusion; Scene Change; Face Detect Integrated IR LEDs; maximum 40m illumination, Micro SD Card Support Multiple network monitoring: Web viewer, CMS & Mobile 3.6mm Fixed Lens (81° Angle of View) IP67 Weatherproof and metal construction with cable managed bracket PoE and 12Vdc power input 	IRR 57,880,000	
		DH-IPC-HFW4431TP-S-54		<ul style="list-style-type: none"> 1/3" 4Megapixel progressive scan CMOS H.265&H.264 triple-stream encoding 25/30fps@4MP(2688x1520) - Smart Detection supported WDR(120dB), Day/Night(ICR), 3DNR, AWB, AGC, BLC Multiple network monitoring: Web viewer, CMS(DSS/PSS) & DMSS 3.6mm fixed lens (6mm, 8mm, 12mm optional) Max. IR LEDs Length 80m, - Micro SD memory 256GB, IP67, IK10, PoE Smart Functions: Tripwire, Intrusion, Scene Change, Face Detect Integrated IR LEDs; maximum 40m illumination, Micro SD Card Support 		
		DH-IPC-HFW4441EP-AS		<ul style="list-style-type: none"> 4MP, 1/3" CMOS image sensor, low illumination, high image definition Outputs max. 4MP (2688 x 1520)@30fps H.265 codec, high compression rate, low bit rate Built-in IR LED, max. IR distance: 50 m ROI, SMART H.264+/H.265+, flexible coding, applicable to various bandwidth and storage environments Rotation mode, WDR, 3D DNR, HLC, BLC, digital watermarking, applicable to various monitoring scenes 	IRR 89,810,000	
		DH-IPC-HFW4831EP-SE		<ul style="list-style-type: none"> 1/2.5" 8Megapixel progressive scan STARVIS™ CMOS H.265&H.264 triple-stream encoding 15fps@4K(3840x2160),25/30fps@3M(2304x1296) Smart Detection supported, -WDR(120dB), Day/Night(ICR), 3DNR, AWB, AGC, BLC Multiple network monitoring: Web viewer, CMS(DSS/PSS) & DMSS 2.8mm fixed lens (4mm optional); - Max. IR LEDs Length 40m Micro SD Memory, IP67, PoE 2 MP Box WizMind Network Camera 		
		DH-IPC-HFW5241EP-E		<ul style="list-style-type: none"> 2MP 1/2.8" CMOS image sensor, low luminance, and high definition image. Outputs max. 2 MP (1920 x 1080) @30fps. H.265 codec, high compression rate, ultra-low bit rate. ROI, SMART H.264+/H.265+/AI H.264/H.265, flexible coding, applicable to various bandwidth and storage environments. Rotation mode, WDR, 3D NR, HLC, BLC, digital watermarking, applicable to various monitoring scenes 		IRR 93,500,000
		IPC-HFW5241EP-ZE		<ul style="list-style-type: none"> 2MP IR Vari-focal Bullet WizMind Network Camera 2-MP 1/2.8" CMOS image sensor, low luminance, and high definition image. Outputs max. 2 MP (1920 x 1080)@30fps. Built-in IR LED, and the max. illumination distance is 60 m. ROI, SVC, SMART H.264+/H.265+, AI H.264/H.265, encoding after filter, flexible coding, applicable to various bandwidth and storage environments. Rotation mode, WDR, 3D NR, HLC, BLC, digital watermarking, applicable to various monitoring scenes. Three switchable intelligent resources: IVS, face detection, and people counting. Alarm: 2 in, 1 out; audio: 1 in, 1 out; supports max. 256 G Micro SD card. 12VDC/PoE power supply, easy for installation 		IRR 132,000,000
		DH-IPC-HFW5442EP-Z4E-0832		<ul style="list-style-type: none"> 1/1.8" 4Megapixel progressive scan CMOS (AI-SATRULIGHT) H.265 & H.264 triple-stream encoding 25/30fps@2688 x 1520, 50/60fps@1080P(1920 x 1080) WDR (120 dB), Day/Night (ICR), 3D DNR, AWB, AGC, BLC Multiple network monitoring: Web viewer, CMS (DSS/PSS) & DMSS 2.7 mm-12.0 mm motorized lens, - 2/1 Alarm in/out, 1/1 audio in/out Max. IR LEDs Length 50 m, - Micro SD memory, IP67, IK10 	IRR 156,830,000	
		DH-IPC-HFW5541TP-ASE		<ul style="list-style-type: none"> 1/2.7" 5Megapixel progressive scan CMOS ROI, SMART H.264+/H.265+, flexible coding, applicable to various bandwidth and storage environments 20 fps@2592 x 1944, 50/60 fps@1080P (1920 x 1080); WDR (120 dB), Day/Night (ICR), 3D DNR, AWB, AGC, BLC; Multiple network monitoring: Web viewer, CMS (DSS/PSS) & DMSS 2.8 mm fixed lens (3.6 mm, 6.0 mm, 8.0 mm, 12.0 mm optional) 1/1 Alarm in/out, 1/1 audio in/out, - Max. IR LEDs Length 80 m, - Micro SD memory, IP67, IK10 		
		DH-IPC-HFW5541EP-ZE		<ul style="list-style-type: none"> 5MP IR Vari-focal Bullet WizMind Network Camera 5-MP 1/2.7" CMOS image sensor, low luminance, and high definition image. Outputs max. 5 MP (2592 x 1944)@20fps. Built-in IR LED, and the max. illumination distance is 60 m. ROI, SVC, SMART H.264+/H.265+, AI H.264/H.265, encoding after filter, flexible coding, applicable to various bandwidth and storage environments. Rotation mode, WDR, 3D NR, HLC, BLC, digital watermarking, applicable to various monitoring scenes. Three switchable intelligent resources: IVS, face detection, and people counting. 		
		DH-IPC-HFW5631EP-ZE		<ul style="list-style-type: none"> 6MP WDR IR Bullet Network Camera 1/2.9" 6Megapixel progressive scan STARVIS™ CMOS H.265&H.264 dual-stream encoding 20fps@6M(3072x2048),25/30fps@4M(2688x1520); Day/Night(ICR), 3DNR, AWB, AGC, BLC Multiple network monitoring: Web viewer, CMS(DSS/PSS) & DMSS 2.7mm~13.5mm motorized lens - Max. IR LEDs Length 50m - Micro SD memory, IP67, IK10, PoE 		
		DH-IPC-HFW5831EP-ZE		<ul style="list-style-type: none"> 1/2.5" 8Megapixel progressive scan STARVIS™ CMOS H.265&H.264 dual-stream encoding 15fps@4K(3840x2160),25/30fps@3M(2304x1296) Day/Night(ICR), 3DNR, AWB, AGC, BLC Multiple network monitoring: Web viewer, CMS(DSS/PSS) & DMSS 2.7mm~12mm motorized lens - Max. IR LEDs Length 50m Micro SD memory, IP67, IK10, PoE 2 MP Box WizMind Network Camera 		
		DH-IPC-HDBW5842EP-ZE-2712-S2		<ul style="list-style-type: none"> 8MP 1/1.8" CMOS image sensor, low illumination, high image definition. Outputs max. 8MP (3840x 2160) @ 30 fps, -> Max. IR distance: 40 m. ROI, SMART H.264+/H.265+, flexible coding, applicable to various bandwidth and storage environments Rotation mode, WDR, 3D NR, HLC, BLC, digital watermarking, applicable to various monitoring scenes. 	IRR 153,510,000	













		DH-IPC-HFW5842EP-ZE-2712-SZ		<p>8MP 1/1.8" CMOS image sensor, low illuminance, high image definition (high definition image).Outputs max. 8MP (3840x2160) @30 fps.</p> <p>> Max. IR distance: 60 m. > ROI, SMART H.264+/H.265+, flexible coding, applicable to various bandwidth and storage environments > Rotation mode, WDR, 3D NR, HLC, BLC, digital watermarking, applicable to various monitoring scenes > Alarm: 2 in, 1 out; audio: 1 in, 1 out; supports max. 256 G Micro SD card. 12V DC/PoE power supply. > ePoE, IP67, IK10 protection.> SMD 3.0</p>	IRR 153,510,000	
PTZ IP Camera						
210438		DH-SD5A432XA-HNR		<p>4MP 32x Starlight IR WizSense Network PTZ Camera</p> <p>1/2.8" 4Megapixel STARVIS™ Progressive CMOS, H.265+, H.264+, H.265, H.264, MJPEG(Sub Stream) 3 Stream, Max. 25/30fps@4M, Min. Illumination Color: 0.005 Lux@F1.35, 8/W: 0.0005 Lux@F1.35, 0 Lux (IR on), 4.9 mm-156 mm Powerful 32x optical zoom, Max. Aperture F1.35-F4.4, Max Presets Speed: Pan: 400°/s Tilt: 300°/s, Pan: 0°-360° endless rotation</p> <p>WDR(120), EIS, Defog, ROI, 2D DNR, 3D DNR, HLC, BLC, AWB, AGC, Day/Night Auto ICR</p> <p>Deep Learning, Auto Track, Tripwire, intrusion, Object Abandoned/Missing, SMD Plus, Face Detection, human/motor, vehicle/non-motor vehicle Classification, Animals/Leaves/Light False Alarm Filtering, Up to 300 presets, 8 tour, 5 pattern, Auto scan, Auto Pan</p> <p>Micro SD card (256G), 1/1 Audio I/O, 2/1 Alarm I/O, ONVIF Profile S&G&T</p> <p>IR distance up to 150m, DC 24 V/2.5 A, PoE+, IP67, IK10, 6000V lightning proof, surge protection; voltage transient protection</p>	IRR 564,600,000	
		SD5A232XB-HNR		<p>2MP 32x Starlight IR WizSense Network PTZ Camera</p> <p>> 1/2.8" 2Megapixel STARVIS™ CMOS</p> <p>> Powerful 32x optical zoom</p> <p>> Max. 50/60 fps@2M</p> <p>> IR distance up to 150 m</p> <p>> Deep-learning-based auto tracking and perimeter protection</p> <ul style="list-style-type: none"> > SMD PLUS > PoE+ > IP67, IK10 > Face detection 	IRR 381,000,000	
		DH-SD49225XA-HNR		<p>2MP 25x Starlight IR PTZ AI Network Camera, 1/2.8" STARVIS™ CMOS</p> <p>H.265+/H.265/H.264+/H.264/MJPEG (sub stream), Max. 1*60fps@1080P.960P, 720P</p> <p>4.8mm~120mm 25x optical zoom, Max 240°/s pan speed, 360° endless pan rotation</p> <p>WDR(120dB), Day/Night(ICR)(Color/B/W), Ultra, DNR(2D/3D), BLC, HLC, AWB, AGC, Auto Iris, Auto focus, NVR/Tripwire, intrusion, Abandoned/Missing, Face Detection, Human, Vehicle, SMD Plus, Region of Interest)</p> <p>False Alarm Avoidance for Animals, Leaves, Bright Light, Support Defog and EIS</p> <p>Up to 300 presets, 8 tour, 5 pattern, Auto scan, Auto Pan, Built-in 2/1 Alarm in/out, Audio 1/1 in/out, Support PoE+</p>	IRR 259,340,000	IRR 245,000,000
		SD59232XA-HNR		<p>2MP 32x Starlight IR WizSense Network PTZ Camera> 1/2.8" STARVIS™ CMOS</p> <ul style="list-style-type: none"> > Powerful 32x optical zoom > Starlight technology > Max. 50/60fps@1080P <p>> Deep-learning-based auto tracking and perimeter protection</p> <ul style="list-style-type: none"> > Support PoE+ > IR distance up to 150 m > SMD PLUS > IP66 	IRR 383,000,000	
		DH-SD59230U-HNI		<p>2MP 32x Starlight IR WizSense Network PTZ Camera</p> <p>> 1/2.8" 2Megapixel STARVIS™ CMOS</p> <p>> Powerful 32x optical zoom</p> <p>> Max. 50/60 fps@1080P</p> <p>> IR distance up to 150 m</p> <p>> Deep-learning-based auto tracking and perimeter protection</p> <ul style="list-style-type: none"> > SMD PLUS > PoE+ > IP67, IK10 > Face Detection 		
		DH-SD29204UE-GN		<ul style="list-style-type: none"> · 1/2.8" STARVIS™ CMOS, STARLIGHT · Powerful 4x optical zoom · Support Triple-streams encoding · WDR, Day/Night(ICR), Ultra DNR · Max. 25/30fps@1080P - HVS · Support PoE - IR distance up to 30m 		
250723		DH-SD6A1445XA-HNR		<p>1/2.8" 4Megapixel CMOS - Powerful 45x optical zoom</p> <p>Starlight technology - Max. 25/30 fps@4MP</p> <p>Deep-learning-based auto tracking and perimeter protection</p> <ul style="list-style-type: none"> Support face detection Laser distance up to 550m Support Hi-PoE SMD PLUS 	IRR 787,000,000	
		SD49225XA-HNR-s3		<p>2MP 25x Starlight IR WizSense Network PTZ Camera</p> <p>> 1/2.8" 2Megapixel STARVIS™ CMOS</p> <ul style="list-style-type: none"> > Powerful 25x optical zoom > Starlight technology > Max. 25/30 fps@1080p > IR distance up to 100 m > Perimeter protection > Face detection > SMD Plus > IP66 		
		DH-SD49225DB-HNY		<p>2MP 25x Starlight IR Network PTZ Camera</p> <p>> 1/2.8" 2Megapixel STARVIS™ CMOS.</p> <ul style="list-style-type: none"> > 25x optical zoom. > Starlight technology. > Max. 25/30 fps@1080p. > IR distance up to 100 m. > H.265 encoding. > Perimeter protection. <p>> Face Detection. Up to 8 faces captured at the same time.</p>	IRR 221,810,000	
		DH-SD49225-HC-LA1		<p>2MP 25x Starlight IR PTZ HDCVI Camera</p> <p>> 1/2.8" 4Megapixel STARVIS™ CMOS</p> <p>> Powerful 25x optical zoom> Starlight technology> 120 dB true WDR, 3D DNR</p> <p>> Max. 25/30 fps@1080P, 25/30/50/60 fps@720P</p> <p>> IR distance up to 100 m</p> <p>> IP66</p>	IRR 226,580,000	IRR 205,455,000
		SD49425XB-HNR		<p>4MP 25x Starlight IR WizSense Network PTZ Camera</p> <ul style="list-style-type: none"> > 1/2.8" 4Megapixel CMOS > Powerful 25x optical zoom > Starlight technology > Max.25/30fps@4M > Perimeter protection > Support PoE+ > IR distance up to 100m > SMD PLUS > IP66 	IRR 290,000,000	

		DH-SD5A232XB-HNR		<p>2MP 32x Starlight IR WizSense Network PTZ Camera > 1/2.8" 2Megapixel STARVIS™ CMOS > Powerful 32x optical zoom > Max. 50/60 fps@1080P, > IR distance up to 150 m > Deep-learning-based auto tracking and perimeter protection > SMD PLUS, > PoE+ > IP67, IK10, Face Detection</p>		
		DH-SD5A432XB-HNR		<p>1/2.8" 4Megapixel STARVIS™ CMOS · Powerful 32x optical zoom · Max. 25/30 fps@4M · IR distance up to 150 m · Deep-learning-based auto tracking and perimeter protection · SMD PLUS · PoE+ · IP67, IK10 · Face Detection</p>	IRR 536,320,000	
		DH-SD5A232XA-HNR		<p>2MP 32x Starlight IR WizSense Network PTZ Camera > 1/2.8" 2Megapixel STARVIS™ CMOS > Powerful 32x optical zoom > Max. 50/60 fps@1080P, > IR distance up to 150 m > Deep-learning-based auto tracking and perimeter protection > SMD PLUS, > PoE+ > IP67, IK10, Face Detection</p>	IRR 489,240,000	
NVR						
		DHI-NVR1104HS-S3/H		<p>4 Channel IPC Input, 4K Lite H.265 NVR 1/4 Live & Playback Smart H.265+/Smart H.264+/H.265/H.264 Network Bandwidth 80 Mbps for access, 80 Mbps for storage and 60Mbps for forwarding. Up to 8MP Resolution for Preview & Playback, Decoding Capacity: 1-ch@8MP(30FPS) or 1-ch@5MP(30FPS) or 2-ch@4MP(30FPS) or 2-ch@3MP(30FPS) or 4-ch@1080P(30FPS) Video Output 1 VGA/1 HDMI simultaneous video output, maximum resolution 1080P 1 SATA 2.0 port, up to 8TB, 1 front USB 2.0 port, 1 rear USB 2.0 port, 1ch Audio I/O for Two Way Talk Only, 1 RJ-45 port (10/100 Mbps), P2P Support, ONVIF(profile T/profile S/profile G)</p>	IRR 32,340,000	
		DHI-NVR1108HS-S3/H		<p>8 Channel IPC Input, 4K Lite H.265 NVR 1/4/8/9 Live & Playback Smart H.265+/Smart H.264+/H.265/H.264 Network Bandwidth 80 Mbps for access, 80 Mbps for storage and 60 Mbps for forwarding. Up to 8MP Resolution for Preview & Playback Decoding Capacity: 1-ch@8MP(30FPS) or 1-ch@5MP(30FPS) or 2-ch@4MP(30FPS) or 2-ch@3MP(30FPS) or 4-ch@1080P(30FPS) Video Output 1 VGA/1 HDMI simultaneous video output, maximum resolution 1080P 1 SATA 2.0 port, up to 8TB, 1 front USB 2.0 port, 1 rear USB 2.0 port, 1ch Audio I/O for Two Way Talk Only, 1 RJ-45 port (10/100 Mbps), P2P Support, ONVIF(profile T/profile S/profile G)</p>	IRR 35,970,000	
		DHI-NVR2216-4KS2		<p>16 Channel 4K Lite H.265 NVR 1/4 Live & Playback Dual-core embedded processor, H.265/H.264 codec decoding Max 80Mbps incoming bandwidth, Up to 1ch@8MP/4ch@1080P decoding HDMI/VGA simultaneous video output, 2 SATA III Ports, up to 6TB capacity for each, Total 12TB 1 front USB 2.0 port, 1 rear USB 2.0 port, 1ch Audio I/O for Two Way Talk Only 1 RJ-45 port (100Mbps), P2P Support, 40,000,000 77 NVR2116HS-16 Channel 12MP WizSense NVR 1/4/9/16 Live & Playback, Smart H.265+/H.264+/MJPEG</p>	IRR 67,360,000	
		NVR2216-16P-I		<p>16 Channel 1U 16PoE WizSense Network Video Recorder > New 4.0 user interface > Remote surveillance, live view and video play on mobile phone App > Max. decoding capability: 4x1080P@30fps. Supports adaptive decoding > Supports mainstream cameras of ONVIF and RTSP protocols > H.264/H265/Smart H.264+/Smart H.265+/MJPEG, H.265 auto switch > 1 VGA/1 HDMI simultaneous video output by default, the maximum resolution of HDMI is 4K; and non-simultaneous video output is also supported, the maximum resolution is 1080P > 1-channel face detection and recognition (AI by NVR); or 2-channel perimeter detection (AI by NVR); or 4-channel SMD (AI by NVR); up to 10 face databases and 5,000 face images > Security baseline 2.1</p>	IRR 103,000,000	
		DHI-NVR2216-I2		<p>16 Channel 1U WizSense Network Video Recorder > New 4.0 user interface-Remote surveillance, live view and video play on mobile phone App- Max. decoding capability: 4x1080P@30fps. Supports adaptive decoding > Supports mainstream cameras of ONVIF and RTSP protocols > H.264/H265/Smart H.264+/Smart H.265+/MJPEG, H.265 auto switch > 1 VGA/1 HDMI simultaneous video output by default, the maximum resolution of HDMI is 4K; and non-simultaneous video output is also supported, the maximum resolution is 1080P > 1-channel face detection and recognition (AI by NVR); or 2-channel perimeter detection (AI by NVR); or 4-channel SMD (AI by NVR); up to 10 face databases and 5,000 face images</p>	IRR 106,980,000	IRR 96,400,000
		DHI-NVR4104HS-4KS2/L		<p>4 Channel Compact 1U 1HDD Network Video Recorder · New 4.0 user interface, Security baseline 2.1 · H.264, H.265, Smart H.264+, and Smart H.265+ · H.265 auto switch · Max. decoding capability: 8 x 1080p@30 fps. Supports adaptive decoding · Supports mainstream cameras of ONVIF and RTSP protocols · P2P remote surveillance, video play on mobile device · VGA/HDMI simultaneous video output, maximum resolution of HDMI is 4K · AI by Camera: Face detection, perimeter protection, IVS, people counting, heat map, and SMD · Supports remote configuration and management of IPC, such as setting parameters, getting information, and upgrading IPC of the same model in batches</p>	IRR 59,520,000	IRR 39,600,000
		DHI-NVR4104HS-P-4KS2/L		<p>New 4.0 user interface, Security baseline 2.1 > H.264, H.265, Smart H.264+, and Smart H.265+ · H.265 auto switch > Max. decoding capability: 8 x 1080p@30 fps. Supports adaptive decoding > Supports mainstream cameras of ONVIF and RTSP protocols > P2P remote surveillance, video play on mobile device > VGA/HDMI simultaneous video output, maximum resolution of HDMI is 4K > AI by Camera: Face detection, perimeter protection, IVS, people counting, heat map, and SMD > Supports remote configuration and management of IPC, such as setting parameters, getting information, and upgrading IPC of the same model in batches</p>	IRR 82,750,000	
		DHI-NVR2108-8P-4KS2		<p>8 Channel Smart 1U 8PoE Lite 4K H.265 Network Video Recorder > Smart H.265+/Smart H.264+/H.265/H.264 > Max 80Mbps incoming bandwidth > Up to 8Mp resolution preview&playback > Up to 1ch@8MP/4ch@1080P decoding > HDMI/VGA simultaneous video output > Support IPC UPnP, 8PoE ports</p>	IRR 84,810,000	
		DHI-NVR4108HS-4KS2/L		<p>8 Channel Compact 1U 1HDD Network Video Recorder · New 4.0 user interface, Security baseline 2.1 · H.264, H.265, Smart H.264+, and Smart H.265+ · H.265 auto switch · Max. decoding capability: 8 x 1080p@30 fps. Supports adaptive decoding · Supports mainstream cameras of ONVIF and RTSP protocols · P2P remote surveillance, video play on mobile device · VGA/HDMI simultaneous video output, maximum resolution of HDMI is 4K · AI by Camera: Face detection, perimeter protection, IVS, people counting, heat map, and SMD · Supports remote configuration and management of IPC, such as setting parameters, getting information, and upgrading IPC of the same model in batches</p>	IRR 61,780,000	IRR 61,400,000

		DHI-NVR4116HS-4KS2/L		16 channel IP camera input, 16 channel Live Preview, Smart H.265/H.264 codec decoding Max 80Mbps incoming bandwidth, Up to 8MP Resolution for Preview and Playback 16-ch@720P decoding capacity, Support SMD Plus by Camera HDMI(4K)/VGA simultaneous video output, Support 1 SATA HDD up to 8TB, 2 USB2.0 100 Mbps Network Card, P2P support	IRR 81,530,000	
		NVR4208-8P-4KS2/L		8 Channel 1U 8PoE 4K 2HDDs & H.265 Lite Network Video Recorder 16/32-channel IP video access > Smart H.265+/Smart H.264+/H.265/H.264; H.265 auto switch > Max 200 Mbps incoming bandwidth > Up to 8MP resolution for preview and playback > 8-channel decoding@1080p (30 fps) > AI by Camera: Perimeter protection; SMD Plus; people counting; heat map > Support IPC UPnP, 8 PoE ports	IRR 100,000,000	
		DHI-NVR4216-16P-4KS2/L		16/32 Channel 1U 16PoE 4K & H.265 Lite Network Video Recorder > 16/32-channel IP video access > Smart H.265+/Smart H.264+/H.265/H.264; H.265 auto switch > Max 200 Mbps incoming bandwidth, > Up to 8MP resolution for preview and playback > 8-channel decoding@1080p (30 fps) > AI by Camera: Perimeter protection; SMD Plus; people counting; heat map > Support IPC UPnP, 16 PoE ports	IRR 187,070,000	
		DHI-NVR4216-4KS2/L		New UI interface with more easier operation experience - Smart H.265+/ Smart H.264+ - P2P remote surveillance, video play on mobile device - 16-ch@720P(30FPS), self-adaptive decoding capability - Supports mainstream cameras of ONVIF and RTSP protocol - VGA/HDMI simultaneous video output, maximum resolution of HDMI is 4K - Remote configuration and management of IPCs, such as setting parameters, acquiring information and upgrading IPCs of the same model in batches - DHCP(Dynamic Host Configuration Protocol), HTTP(Hypertext Transfer Protocol), NTP(Network Time Protocol) and DDNS(Dynamic Domain Name System)	IRR 104,350,000	IRR 100,000,000
		DHI-NVR5216-4KS2		16-channel IP video access > Smart H.265+/Smart H.264+/H.265/H.264/MJPEG; H.265 auto switch > Max 320 Mbps incoming bandwidth > Up to 24MP Resolution for live view and playback > 1-channel fisheye dewarping (AI by NVR) > AI by Camera: Perimeter protection; face detection and recognition; SMD Plus; video metadata; ANPR; people counting; stereo analysis; crowd distribution; heat map	IRR 183,010,000	IRR 158,200,000
		DHI-NVR4232-4KS2/L		32 channel IP camera input, 16 channel Live Preview, H.265/H.264 codec decoding Max 200Mbps incoming bandwidth, Up to 8MP Resolution for Preview and Playback HDMI/VGA simultaneous video output, Support 2 SATA HDD up to 6TB 2 USB Ports (1 USB2.0, 1 USB3.0) 4 Alarm Input, 2 Relay Output, 1*1000Mbps Network Card, P2P support	IRR 125,670,000	
		DHI-NVR4432-4KS2/L		32 Channel 1.5U 4HDDs WizSense Network Video Recorder - Smart H.265+/H.265/Smart H.264+/H.264/MJPEG decoding format - Access, storage or forwarding at 256 Mbps (160 Mbps when AI function enabled) - Max. decoding capability: 10 x 1080p@30 fps. Supports adaptive decoding - AI by NVR: 1-channel face detection and recognition; 2-channel	IRR 154,680,000	
		DHI-NVR5232-4KS2/V2		32Channel 1U 4K & H.265 Pro Network Video Recorder (V2.00) Smart H.265+/H.265/H.264+/H.264/MJPEG decoding Max 320Mbps incoming bandwidth Up to 12Mp resolution preview & playback Max 4-ch@8MP(30fps), 16-ch@1080P(30fps) decoding 1*HDMI(4K)/1*VGA simultaneous video output 2*SATA HDDs(10 TB for each HDD), 2 USB(1 USB3.0,1 USB2.0) 1*1000 Mbps Network Card RS232, RS485,4/2 Alarm In/out , P2P Support	IRR 192,120,000	IRR 200,000,000
		DHI-NVR5432-4KS2/L		32Channel 1.5U 4K & H.265 Pro Network Video Recorder(V2.00) Smart H.265+/H.265/H.264+/H.264/MJPEG decoding, Max 320Mbps incoming bandwidth, Up to 12Mp resolution preview & playback Max 4-ch@8MP(30fps), 16-ch@1080P(30fps) decoding, 2*HDMI/2*VGA simultaneous video output, 4*SATA HDDs(10 TB for each HDD), 3 USB(2 USB3.0,1 USB2.0), Support 1 e-SATA, 2*1000 Mbps Network Card RS232, RS485,16/6 Alarm In/out, P2P Support		
		DH-NVR1104HS-P-S3/H		- New 4.0 user interface - P2P remote surveillance, video play on mobile device - 4-ch@1080P(30FPS), self-adaptive decoding capability - Support for mainstream cameras of ONVIF and RTSP protocol - Smart H.265+/Smart H.264+/H.265/H.264 - VGA/HDMI simultaneous video output, maximum resolution of HDMI is 1080P - Remote configuration and management of IPCs, such as setting parameters, acquiring information and upgrading IPCs of the same model in batches - DHCP(Dynamic Host Configuration Protocol), HTTP(Hypertext Transfer Protocol), NTP(Network Time Protocol) and DDNS(Dynamic Domain Name System)		
		NVR2104HS-I		> New 4.0 user interface > Remote surveillance, live view and video play on mobile phone App > Max. decoding capability: 4x1080P@30fps. Supports adaptive decoding > Supports mainstream cameras of ONVIF and RTSP protocols > H.264/H.265/Smart H.264+/Smart H.265+/MJPEG, H.265 auto switch > 1 VGA/1 HDMI simultaneous video output by default, the maximum resolution of HDMI is 4K; and non-simultaneous video output is also supported, the maximum resolution is 1080P > 1-channel face detection and recognition (AI by NVR); or 2-channel perimeter detection (AI by NVR); or 4-channel SMD (AI by NVR); up to 10 face databases and 5,000 face images	IRR 60,200,000	
		DH-NVR4108HS-8P-4KS2		16 Channel Compact 1U 8PoE 4K&H.265 Lite Network Video Recorder - Smart H.265+/H.265/Smart H.264+/H.264 - Max 80Mbps Incoming Bandwidth - Up to 8MP Resolution for Preview and Playback - Up to 2ch@4K/8ch@1080P decoding - HDMI/VGA simultaneous video output - Support IPC UPnP, 8PoE ports		
250756		DH-NVR4108HS-8P-4KS2/L		- New 4.0 user interface, Security baseline 2.1 - H.264, H.265, Smart H.264+, and Smart H.265+. H.265 auto switch - Max. decoding capability: 8 x 1080p@30 fps. Supports adaptive decoding - Supports mainstream cameras of ONVIF and RTSP protocols - P2P remote surveillance, video play on mobile device - VGA/HDMI simultaneous video output, maximum resolution of HDMI is 4K - AI by Camera: Face detection, perimeter protection, iVCS, people counting, heat map, and SMD - Supports remote configuration and management of IPC, such as setting parameters, getting information, and upgrading IPC of the same model in batches		
		DH-NVR1108HS-8P-S3/H		- New 4.0 user interface - P2P remote surveillance, video play on mobile device - 8-ch@1080P(30FPS), self-adaptive decoding capability - Support for mainstream cameras of ONVIF and RTSP protocol - Smart H.265+/Smart H.264+/H.265/H.264 - VGA/HDMI simultaneous video output, maximum resolution of HDMI is 1080P - Remote configuration and management of IPCs, such as setting parameters, acquiring information and upgrading IPCs of the same model in batches - DHCP(Dynamic Host Configuration Protocol), HTTP(Hypertext Transfer Protocol), NTP(Network Time Protocol) and DDNS(Dynamic Domain Name System)		

		DH-NVR2104HS-4KS2		<ul style="list-style-type: none"> . 4 channel IP camera input 1U Lite 4K . H.265/H.264 codec decoding . 100 Mbps Network Card. P2P support . Max 80Mbps incoming bandwidth . HDMI/VGA simultaneous video output . Up to 8Mp resolution preview&playback . Up to 1ch@8MP/4ch@1080P decoding . Support 1 SATA HDD up to 6TB, 2 USB2.0 		
		DH-NVR2104HS-P-I2		<ul style="list-style-type: none"> 4 Channel Compact 1U 4PoE Lite 4K. H.265/H.264 codec decoding . Max 80Mbps incoming bandwidth-Up to 8Mp resolution . preview&playback-Up to 1ch@8MP/4ch@1080P decoding . HDMI/VGA simultaneous video output . Support 1 SATA HDD up to 6TB, 2 USB2.0 . 100 Mbps Network Card-4PoE Port. P2P support 		IRR 46,575,000
		NVR2104HS-I2		<ul style="list-style-type: none"> 4 Channel Compact 1U 4PoE 1HDD WizSense Network Video Recorder > Smart H.265+/H.265/Smart H.264+/H.264/MJPEG decoding format > Max. decoding capability: 6 x 1080p@30 fps. Supports adaptive decoding > 1-channel face detection and recognition (AI by NVR); 1-channel perimeter protection (AI by NVR); up to 10 face databases and 5,000 face images; 4-channel SMD Plus (AI by NVR); > AI by camera: Face detection and recognition, perimeter protection, and SMD Plus > Connected to the third-party network cameras > Security baseline 2.1 		IRR 60,200,000
250736		NVR2108HS-I2		<ul style="list-style-type: none"> NVR2108-8P-4KS2 8 Channel Smart 1U 8PoE Lite 4K H.265 Network Video Recorder > Smart H.265+/Smart H.264+/H.264/MJPEG > Max 80Mbps incoming bandwidth > Up to 8Mp resolution preview&playback > Up to 1ch@8MP/4ch@1080P decoding > HDMI/VGA simultaneous video output > Support IPC UPnP, 8PoE ports 		IRR 49,160,000
		DHI-NVR2108HS-4KS2(S)		<ul style="list-style-type: none"> . H.265/H.264 codec decoding . Max 80Mbps incoming bandwidth . Up to 8Mp resolution preview&playback . Up to 1ch@8MP/4ch@1080P decoding . HDMI/VGA simultaneous video output 		IRR 37,900,000
		DHI-NVR2108HS-I		<ul style="list-style-type: none"> . New 4.0 user interface > Remote surveillance, live view and video play on mobile phone App> Max. decoding capability: 4x1080P@30fps. Supports adaptive decoding> Supports mainstream cameras of ONVIF and RTSP protocols> H.264/H.265/Smart H.264+/Smart H.265+/MJPEG, H.265 auto switch> 1 VGA/1 HDMI simultaneous video output by default, the maximum resolution of HDMI is 4K; and non-simultaneous video output is also supported, the maximum resolution is 1080P> 1-channel face detection and recognition (AI by NVR); or 2-channel perimeter detection (AI by NVR); or 4-channel 		
250720		NVR2116HS-I2		<ul style="list-style-type: none"> 16 Channel Compact 1U 1HDD WizSense Network Video Recorder > Smart H.265+/H.265/Smart H.264+/H.264/MJPEG decoding format > Max. decoding capability: 6 x 1080p@30 fps. Supports adaptive decoding > 1-channel face detection and recognition (AI by NVR); 1-channel perimeter protection (AI by NVR); up to 10 face databases and 5,000 face images; 4-channel SMD Plus (AI by NVR); > AI by camera: Face detection and recognition, perimeter protection, and SMD Plus > Connected to the third-party network cameras > Security baseline 2. 		IRR 55,110,000
		DHI-NVR2116HS-4KS2		<ul style="list-style-type: none"> Smart H.265+/H.265/Smart H.264+/H.264 > Up to 8MP Resolution for Preview and Playback > Up to 2ch@4K/8ch@1080P decoding > HDMI/VGA . 		IRR 47,600,000
		DH-NVR2108-8P-4KS2		<ul style="list-style-type: none"> . 8 channel IP camera input 1U Lite 4K . H.265/H.264 codec decoding . 100 Mbps Network Card. P2P support . Max 80Mbps incoming bandwidth . HDMI/VGA simultaneous video output . Up to 8Mp resolution preview&playback . Up to 1ch@8MP/4ch@1080P decoding . Support 1 SATA HDD up to 6TB, 2 USB2.0 		IRR 84,810,000
		DH-NVR2104HS-P-4KS2		<ul style="list-style-type: none"> 4 Channel Compact 1U 4PoE Lite 4K. H.265/H.264 codec decoding . Max 80Mbps incoming bandwidth-Up to 8Mp resolution . preview&playback-Up to 1ch@8MP/4ch@1080P decoding . HDMI/VGA simultaneous video output . Support 1 SATA HDD up to 6TB, 2 USB2.0 . 100 Mbps Network Card-4PoE Port. P2P support 		
250324	210324	DH-NVR2108HS-8P-4KS2		<ul style="list-style-type: none"> 8 Channel Compact 1U 8PoE Lite 4K . H.265/H.264 codec decoding . HDMI/VGA simultaneous video output . Max 80Mbps incoming bandwidth . Up to 8Mp resolution preview&playback . Up to 1ch@8MP/4ch@1080P decoding . Support 1 SATA HDD up to 6TB, 2 USB2.0 . 100 Mbps Network Card-8Port PoE. P2P support 		IRR 58,540,000
250719		NVR2108-4KS2		<ul style="list-style-type: none"> 8 Channel Smart 1U 8PoE Lite 4K H.265 Network Video Recorder > Smart H.265+/Smart H.264+/H.265/H.264 > Max 80Mbps incoming bandwidth > Up to 8Mp resolution preview&playback > Up to 1ch@8MP/4ch@1080P decoding > HDMI/VGA simultaneous video output > Support IPC UPnP, 8PoE ports 		IRR 37,900,000
250755		NVR2108HS-8P-I		<ul style="list-style-type: none"> 4 Channel Compact 1U 4PoE Lite Network Video Recorder > New 4.0 user interface > Remote surveillance, live view and video play on mobile phone App > Max. decoding capability: 4x1080P@30fps. Supports adaptive decoding > Supports mainstream cameras of ONVIF and RTSP protocols > H.264/H.265/Smart H.264+/Smart H.265+/MJPEG, H.265 auto switch > 1 VGA/1 HDMI simultaneous video output by default, the maximum resolution of HDMI is 4K; and non-simultaneous video output is also supported, the maximum resolution is 1080P > 1-channel face detection and recognition (AI by NVR); or 2-channel perimeter detection (AI by 		IRR 85,300,000
250703		DH-NVR4104HS-4KS2/L		<ul style="list-style-type: none"> 4 Channel Compact 1U 4K&H.265 Lite Network Video Recorder . Smart H.265+/H.265/Smart H.264+/H.264 . Max 80Mbps incoming Bandwidth . Up to 8MP Resolution for Preview and Playback . Up to 2ch@4K/8ch@1080P decoding . HDMI/VGA simultaneous video output . 1 SATA III Port, Up to 6 TB capacity for each HDD 		IRR 59,520,000
	210666	DH-NVR4104HS-P-4KS2/L		<ul style="list-style-type: none"> 4 Channel Compact 1U 1HDD 4PoE Network Video Recorder . New 4.0 user interface, Security baseline 2.1 . H.264, H.265, Smart H.264+, and Smart H.265+. H.265 auto switch . Max. decoding capability: 8 x 1080p@30 fps. Supports adaptive decoding . Supports mainstream cameras of ONVIF and RTSP protocols . P2P remote surveillance, video play on mobile device . VGA/HDMI simultaneous video output, maximum resolution of HDMI is 4K . AI by Camera: Face detection, perimeter protection, IVS, people counting, heat map, and SMD . Supports remote configuration and management of IPC, such as setting parameters, getting information, and upgrading IPC of the same model in batches 		IRR 82,750,000

		DH-NVR4108HS-4KS2		<ul style="list-style-type: none"> 8 Channel Compact 1U 4K&H.265 Lite Network Video Recorder Smart H.265+/H.265/Smart H.264+/H.264 Max 80Mbps incoming Bandwidth Up to 8MP Resolution for Preview and Playback Up to 2ch@4K/Sch@1080P decoding HDMI/VGA simultaneous video output 	IRR 61,780,000	
250603	210603	DH-NVR4108HS-4KS2/L		<ul style="list-style-type: none"> New 4.0 user interface, Security baseline 2.1 H.264, H.265, Smart H.264+, and Smart H.265+. H.265 auto switch Max. decoding capability: 8 × 1080p@30 fps. Supports adaptive decoding Supports mainstream cameras of ONVIF and RTSP protocols P2P remote surveillance, video play on mobile device VGA/HDMI simultaneous video output, maximum resolution of HDMI is 4K AI by Camera: Face detection, perimeter protection, IVS, people counting, heat map, and SMD Supports remote configuration and management of IPC, such as setting parameters, getting information, and upgrading IPC of the same model in batches 	IRR 61,780,000	IRR 61,400,000
250420	210420	DH-NVR4116HS-4KS2/L		<ul style="list-style-type: none"> New 4.0 user interface, Security baseline 2.1 H.264, H.265, Smart H.264+, and Smart H.265+. H.265 auto switch Max. decoding capability: 8 × 1080p@30 fps. Supports adaptive decoding Supports mainstream cameras of ONVIF and RTSP protocols P2P remote surveillance, video play on mobile device VGA/HDMI simultaneous video output, maximum resolution of HDMI is 4K AI by Camera: Face detection, perimeter protection, IVS, people counting, heat map, and SMD Supports remote configuration and management of IPC, such as setting parameters, getting information, and upgrading IPC of the same model in batches 	IRR 81,530,000	
		DH-NVR4216-4KS2/L		<ul style="list-style-type: none"> 16 Channel 1U 2HDDs Network Video Recorder New 4.0 user interface, Security baseline 2.1 H.264, H.265, Smart H.264+, and Smart H.265+. H.265 auto switch Max. decoding capability: 8 × 1080p@30 fps. Supports adaptive decoding Supports mainstream cameras of ONVIF and RTSP protocols P2P remote surveillance, video play on mobile device VGA/HDMI simultaneous video output, maximum resolution of HDMI is 4K AI by Camera: Face detection, perimeter protection, IVS, people counting, heat map, and SMD Supports remote configuration and management of IPC, such as setting parameters, getting information, and upgrading IPC of the same model in batches 	IRR 104,350,000	IRR 100,000,000
	210608	DH-NVR4216-16P-4KS2/L		<ul style="list-style-type: none"> 16 Channel 1U 2HDDs 16PoE Network Video Recorder- New 4.0 user interface, Security baseline 2.1 H.264, H.265, Smart H.264+, and Smart H.265+. H.265 auto switch Max. decoding capability: 8 × 1080p@30 fps. Supports adaptive decoding Supports mainstream cameras of ONVIF and RTSP protocols P2P remote surveillance, video play on mobile device VGA/HDMI simultaneous video output, maximum resolution of HDMI is 4K AI by Camera: Face detection, perimeter protection, IVS, people counting, heat map, and SMD Supports remote configuration and management of IPC, such as setting parameters, getting information, and upgrading IPC of the same model in batches 	IRR 187,070,000	
250621		DH-NVR4232-4KS2		<ul style="list-style-type: none"> 32-channel IP video access Smart H.265+/Smart H.264+/H.265/H.264; H.265 auto switch Max 200 Mbps incoming bandwidth Up to 8MP resolution for preview and playback 8-channel decoding@1080p (30 fps) AI by Camera: Perimeter protection; SMD Plus; people counting; heat map 		
250422	210422	DH-NVR4232-4KS2/L		<ul style="list-style-type: none"> New 4.0 user interface, Security baseline 2.1 H.264, H.265, Smart H.264+, and Smart H.265+. H.265 auto switch Max. decoding capability: 8 × 1080p@30 fps. Supports adaptive decoding Supports mainstream cameras of ONVIF and RTSP protocols P2P remote surveillance, video play on mobile device VGA/HDMI simultaneous video output, maximum resolution of HDMI is 4K AI by Camera: Face detection, perimeter protection, IVS, people counting, heat map, and SMD Supports remote configuration and management of IPC, such as setting parameters, getting information, and upgrading IPC of the same model in batches 	IRR 125,670,000	
		DH-NVR4432-4KS2/L		<ul style="list-style-type: none"> 32 channel IP camera input: 1.5U 16 channel Live Preview-H.265/H.264 codec decoding Max 200Mbps incoming bandwidth Up to 8MP Resolution for Preview and Playback HDMI/VGA simultaneous video output, Support 4 SATA HDD up to 6TB 2 USB Ports (1 USB2.0, 1 USB3.0) 16 Alarm Input, 4 Relay Output-RS232, RS485 2*10/100/1000Mbps Mbps Network Card-P2P support 	IRR 154,680,000	
		DHI-NVR5208-4KS2		<ul style="list-style-type: none"> Smart H.265+/H.265/Smart H.264+/H.264/MJPEG Max 320Mbps incoming Bandwidth Up to 12MP Resolution for Preview and Playback HDMI/VGA simultaneous video output 	IRR 109,250,000	
		DHI-NVR5208-8P-4KS2		<ul style="list-style-type: none"> > 8/16-channel IP video access > Smart H.265+/Smart H.264+/H.265/H.264/MJPEG; H.265 auto switch > Max 320 Mbps incoming bandwidth > Up to 24MP resolution for live view and playback > 1-channel fisheye dewarping (AI by NVR) > AI by Camera: Perimeter protection; face detection and recognition; SMD Plus; video metadata; ANPR; people counting; stereo analysis; crowd distribution; heat map > Support IPC UPnP, 8 PoE ports 	IRR 151,260,000	
250460	210460	DH-NVR5216-4KS2		<ul style="list-style-type: none"> 16Channel 1U 4K&H.265 Pro Network Video Recorder (V2.00) Smart H.265+/H.265/Smart H.264+/H.264/MJPEG Max 320Mbps incoming Bandwidth Up to 12MP Resolution for Preview and Playback HDMI/VGA simultaneous video output 2 SATA III Ports, Up to 10 TB capacity for each HDD 	IRR 183,010,000	IRR 158,200,000
		DH-NVR5216-16P-4KS2E		<ul style="list-style-type: none"> 32 Channel 1U 2HDDs 16PoE 4K & H.265 Pro Network Video Recorder 32-channel IP video access Smart H.265+/Smart H.264+/H.265/H.264/MJPEG; H.265 auto switch Max 320 Mbps incoming bandwidth Up to 24MP resolution for live view and playback 1-channel fisheye dewarping (AI by NVR) AI by Camera: Perimeter protection; face detection and recognition; SMD Plus; video metadata; ANPR; people counting; stereo analysis; crowd distribution; heat map Support IPC UPnP, 16 PoE ports 		
250751		DH-NVR5216-16P-I		<ul style="list-style-type: none"> 16Channel 1U 16PoE AI Network Video Recorder 16 Channel IP video access Smart H.265+/H.265/Smart H.264+/H.264/MJPEG Up to 16 Channel perimeter protection Up to 4 Channel video stream face recognition Up to 22 face pictures/face processing Up to 20 face databases with 100,000 face images in total 1-8 PoE Ports support ePoE & EoC 		IRR 318,000,000

250151	210151	DH-NVR5232-4KSZ		<ul style="list-style-type: none"> .32 channel IP camera input.32 channel Live Preview . Up to 12Mp resolution preview&playback . Smart H.265+/H.265/Smart H.264+/H.264/MJPEG . Max 320Mbps incoming bandwidth-Record Rate 320 Mbps . Max 4-ch@8MP(30fps), 16-ch@1080P(30fps) decoding . HDMI/VGA simultaneous video output-16 channel playback . Support 2 SATA HDDs up to 20TB, 2 USB(1 USB3.0) . 1000 Mbps Network Card-RS232, RS485 . 4 Alarm Input, 2 Relay Output-Support P2 	IRR 192,120,000	IRR 200,000,000
250497	210497	DH-NVR5432-4KSZ		<ul style="list-style-type: none"> .32 Channel 1.5U 16PoE 4K&H.265 Pro Network Video Recorder . Smart H.265+/H.265/Smart H.264+/H.264/MJPEG . Max 320Mbps Incoming Bandwidth . Up to 12MP Resolution for Preview and Playback . 2HDMI/2VGA simultaneous video output . 1-8 PoE Ports Support 800m ePoE & EoC 	IRR 289,280,000	IRR 291,000,000
		DH-NVR5432-16P-4KS2E		<ul style="list-style-type: none"> .32Channel 1.5U 16PoE 4K&H.265 Pro Network Video Recorder . Smart H.265+/H.265/Smart H.264+/H.264/MJPEG . Max 320Mbps Incoming Bandwidth . Up to 12MP Resolution for Preview and Playback . 2HDMI/VGA simultaneous video output . 3D intelligent positioning with Dahua PTZ camera . 4 SATA III Ports, Up to 8 TB capacity for each HDD 		
250427		DH-NVR5832-4KS2		<ul style="list-style-type: none"> .32 channel IPC input-32 Channel Live Preview . H.265/H.264/MJPEG/MPEG4 codec decoding . Max 320Mbps incoming bandwidth. P2P Support-Raid 0/1/5/6/10 . Up to 12Mp resolution preview&playback . Max 16ch@1080P 4ch@4K.H.265 H.264 Playback . 2HDMI/VGA simultaneous video output . Support 8 SATA HDDs up to 64TB, 4 USB(2 USB3.0, 2 USB2.0) . 2*1000 Mbps Network Card-RS232-16 Alarm In, 6 Relay Output 		IRR 400,000,000
		NVR5864-4KS2		<ul style="list-style-type: none"> .64 channel IPC input-32 Channel Live Preview . H.265/H.264/MJPEG/MPEG4 codec decoding . Max 320Mbps incoming bandwidth. P2P Support-Raid 0/1/5/6/10 . Up to 12Mp resolution preview&playback . Max 16ch@1080P 4ch@4K.H.265 H.264 Playback . 2HDMI/VGA simultaneous video output . Support 8 SATA HDDs up to 64TB, 4 USB(2 USB3.0, 2 USB2.0) . 2*1000 Mbps Network Card-RS232-16 Alarm In, 6 Relay Output 		IRR 478,000,000
250591	210501	DH-NVR608-32-4KS2		<ul style="list-style-type: none"> . Intel Dual-core Processor-32 channel IPC input . 32 Channel Live Preview. 16 Alarm In, 8 Relay Output . (1st Screen:1/4/8/9/16/25/36,2nd Screen: 1/4/8/9/16) . H.265/H.264/MJPEG codec decoding. Max 384Mbps incoming bandwidth . Up to 12Mp resolution preview&playback. 2HDMI/VGA simultaneous video output . Support 8 SATA HDDs up to 64TB, 1 eSATA Port . Support Raid 0/1/5/6/10-4 USB(2 USB3.0, 2 USB2.0) . 2*1000 Mbps Network Card-RS232, RS485 	IRR 427,670,000	IRR 458,000,000
250481	210481	DH-NVR608-64-4KS2		<ul style="list-style-type: none"> . Intel Quad-core Processor . 64 channel IPC input-32 Channel Live Preview: . (1st Screen:1st Screen: 1/4/8/9/16/25/36 ,2nd Screen: 1/4/8/9/16) . H.265/H.264/MJPEG codec decoding . Max 384Mbps incoming bandwidth. 2HDMI/VGA simultaneous video output . Up to 12Mp resolution preview & playback. RS232, RS485-16 Alarm In . Support 8 SATA HDDs up to 64TB, 1 eSATA Port. Support Raid 0/1/5/6/10 . Support Smart Tracking and Intelligent Video . 4 USB(2 USB3.0, 2 USB2.0)-2*1000 Mbps Network Card 	IRR 821,890,000	IRR 870,000,000
		DH-NVR608-128-4KS2		<ul style="list-style-type: none"> . Intel Quad-core Processor . 128 channel IPC input-32 Channel Live Preview: . (1st Screen:1st Screen: 1/4/8/9/16/25/36 ,2nd Screen: 1/4/8/9/16) . H.265/H.264/MJPEG codec decoding . Max 384Mbps incoming bandwidth. 2HDMI/VGA simultaneous video output . Up to 12Mp resolution preview & playback. RS232, RS485-16 Alarm In . Support 8 SATA HDDs up to 64TB, 1 eSATA Port. Support Raid 0/1/5/6/10 . Support Smart Tracking and Intelligent Video . 4 USB(2 USB3.0, 2 USB2.0)-2*1000 Mbps Network Card 	IRR 924,810,000	
		NVR5216-EI		<ul style="list-style-type: none"> . 16 Channels 1U 2HDD WizSense Network Video Recorder . > Smart H.265+/H.265/Smart H.264+/H.264/MJPEG decoding format. . > 32-channel 1080p self-adaptive decoding capability. . > Max. 384 Mbps incoming/recording/outgoing bandwidth. . > AI by recorder: 2-channel face detection and recognition, 4-channel perimeter protection, and 8-channel SMD Plus. . > AI by camera: Face detection and recognition, perimeter protection, SMD Plus, metadata, ANPR, stereo analysis, heat map, and people counting. . > Security baseline 2.3 		IRR 215,000,000
		NVR5232-EI		<ul style="list-style-type: none"> . 32 Channels 1U 2HDD WizSense Network Video Recorder . > Smart H.265+/H.265/Smart H.264+/H.264/MJPEG decoding format. . > 32-channel 1080p self-adaptive decoding capability. . > Max. 384 Mbps incoming/recording/outgoing bandwidth. . > AI by recorder: 2-channel face detection and recognition, 4-channel perimeter protection, and 8-channel SMD Plus. . > AI by camera: Face detection and recognition, perimeter protection, SMD Plus, metadata, ANPR, stereo analysis, heat map, and people counting. . > Security baseline 2.3. 		IRR 245,000,000
		NVR5432-EI		<ul style="list-style-type: none"> . 32 Channels 1.5U 4HDD WizSense Network Video Recorder . > Smart H.265+/H.265/Smart H.264+/H.264/MJPEG decoding format. . > 32-channel 1080p self-adaptive decoding capability. . > Max. 384 Mbps incoming/recording/outgoing bandwidth. . > AI by recorder: 2-channel face detection and recognition, 4-channel perimeter protection, and 8-channel SMD Plus. . > AI by camera: Face detection and recognition, perimeter protection, SMD Plus, metadata, ANPR, stereo analysis, heat map, and people counting. . > Security baseline 2.3. 		IRR 318,500,000
		NVR5864-EI		<ul style="list-style-type: none"> . 64 Channels 2U 8HDD WizSense Network Video Recorder . > Smart H.265+/H.265/Smart H.264+/H.264/MJPEG decoding format. . > 32-channel 1080p self-adaptive decoding capability. . > Support Raid0/1/5/6/10. . > Max. 384 Mbps incoming/recording/outgoing bandwidth. . > AI by recorder: 2-channel face detection and recognition, 4-channel perimeter protection, and 8-channel SMD Plus. . > AI by camera: Face detection and recognition, perimeter protection, SMD Plus, metadata, ANPR, stereo analysis, heat map, and people counting. . > Security baseline 2.3. 		IRR 577,000,000
		NVR608H-64-XI		<ul style="list-style-type: none"> . 64 Channels 2U 8HDDs WizMind Network Video Recorder . > 32-channel 1080p self-adaptive decoding capability. . > Max. 1024/1024/800Mbps incoming/recording/outgoing bandwidth. . > Supports N+M cluster. . > Support Raid0/1/5/6/10. . > Drawer-like chassis design allows for HDD hot swapping. . > AI by recorder: 4-channel face detection and recognition; 8-channel metadata; 24-channel perimeter protection; 32-channel SMD Plus. . > AI by camera: Face detection and recognition, perimeter protection, SMD Plus, metadata, ANPR, and people counting. 		IRR 955,000,000

		DH-NVR104-P		<ul style="list-style-type: none"> · 4CH Smart Box 4PoE Network Video Recorder · Up to 4 channel IP camera input · H.264/MJPEG dual codec decoding · Max 56Mbps incoming bandwidth · HDMI/VGA simultaneous video output · All channel synchronous realtime playback, GRID interface · Support 1 SATA (2.5"removable HDD) up to 1TB, 2 USB2.0 · Support IPC UPnP, 4PoE ports · Support P2P (QR code Scan) 		
		DH-NVR108-P		<ul style="list-style-type: none"> · 8CH Smart Box 4PoE Network Video Recorder · Up to 8 channel IP camera input · H.264/MJPEG dual codec decoding · Max 56Mbps incoming bandwidth · HDMI/VGA simultaneous video output · All channel synchronous realtime playback, GRID interface · Support 1 SATA (2.5"removable HDD) up to 1TB, 2 USB2.0 · Support IPC UPnP, 4PoE ports · Support P2P (QR code Scan) 		
		DH-NVR1B08		<ul style="list-style-type: none"> · H.265+/H.264+ codec decoding · Max 8 channel IP camera inputs · Max 80Mbps incoming bandwidth · Up to 8MP resolution preview&playback · Up to 1ch@8MP/4ch@1080P decoding · HDMI/VGA simultaneous video output 		
		DH-NVR1B08HS-8P		<ul style="list-style-type: none"> · H.265+/H.264+ codec decoding · Max 80Mbps incoming bandwidth · Max 8 channel IP camera inputs · Up to 8MP resolution preview&playback · Up to 1ch@8MP/4ch@1080P decoding · HDMI/VGA simultaneous video output, Support IPC UPnP, 8PoE ports · 1SATA III Port, up to 6TB capacity for each HDD 		
		DH-NVR1B08HS		<ul style="list-style-type: none"> · H.265+/H.264+ codec decoding · Max 8 channel IP camera inputs · Max 80Mbps incoming bandwidth · Up to 8MP resolution preview&playback · Up to 1ch@8MP/4ch@1080P decoding · HDMI/VGA simultaneous video output · 1 SATA III Port, up to 6TB capacity for each HDD 		
		DH-NVR1B04-4P		<ul style="list-style-type: none"> · H.265+/H.264+ codec decoding · Max 4 channel IP camera inputs, Max 80Mbps incoming bandwidth · Up to 8MP resolution preview&playback · Up to 1ch@8MP/4ch@1080P decoding · HDMI/VGA simultaneous video output, Support IPC UPnP, 4PoE ports · 1 SATA III Port, up to 6TB capacity for each HDD 		
210417	DH-NVR1B04		<ul style="list-style-type: none"> · 4 Channel Smart 1U H.265 Network Video Recorder · H.265+/H.264+ codec decoding · Max 4 channel IP camera inputs · Max 80Mbps incoming bandwidth · Up to 8MP resolution preview&playback · Up to 1ch@8MP/4ch@1080P decoding · HDMI/VGA simultaneous video output 			
		DH-NVR2B16		<ul style="list-style-type: none"> · 16 Channel 1U H.265 Network Video Recorder · H.265+/H.264+ codec decoding · Max 16 channel IP camera inputs, Max 80Mbps incoming bandwidth · Up to 8MP resolution preview&playback, Up to 1ch@8MP/4ch@1080P decoding · HDMI/VGA simultaneous video output, 2 SATA III Ports, up to 6TB capacity for each HDD 		