

# PRICE LIST




















# HIKVISION



02144700447  
 WWW.RADIS-CO.COM  
 RADIS\_NET

## Accessories

Items	Description	User Price
<b>Switches</b>		
DS-3E0105P-E/M	 L2, Unmanaged, 4 100M PoE port, 1 100M uplink port, 802.3af PoE power budget 35W	Call
DS-3E0105P-E	 L2, Unmanaged, 4 100M PoE port, 1 100M uplink port, 802.3af/at, PoE power budget 58W	Call
DS-3E0109P-E/M	 L2, Unmanaged, 8 100M PoE port, 1 100M uplink port, 802.3af, PoE power budget 60W	Call
DS-3E0109P-E	 L2, Unmanaged, 8 100M PoE port, 1 100M uplink port, 802.3af/at, PoE power budget 123W	Call
DS-3E0318P-E	 L2, Unmanaged, 16 100M PoE port, 2 1000M combo port, 802.3af/at, PoE power budget 230W	Call
DS-3E0326P-E	 L2, Unmanaged, 24 100M PoE port, 2 1000M combo port, 802.3af/at, PoE power budget 370W	Call
DS-3E1310P-E	 L2, Web managed, 8 100M PoE port, 2 1000M combo port, 802.3af/at, PoE power budget 123W	Call
DS-3E1318P-E	 <p>802.3af/at PoE standard 8-core power supply technology, reducing the power circuit loss, Data monitor and control for the important ports, EXTEND mode available to extend the network cable transmission distance to 250 meters Buffer optimization to guarantee the video data transmission, VLAN configurable Port trunk, multicast and port mirroring, WEB management, Store-and-forward switching IEEE802.3, IEEE802.3u and IEEE802.3x network standards available MTBF (Mean Time Between Failure) ≥ 100,000 hours All-metal enclosed construction Table-mounted and rack-mounted design for convenient installation</p>	Call
<b>Cables</b>		
DS-1LN6-UE-W	 UTP / CAT.6 / Indoor PVC / 23AWG, Full 305m, OFC / 0.530mm, CM Rating, Default Color: BLUE. TEST FLUKE	Call
DS-1LN6-UU	 UTP / CAT.6 / Indoor PVC / 23AWG Full 305m OFC / 0.565mm CM Rating Default Color: Orange	Call
<b>Brackets</b>		
DS-1602ZJ	 Wall mount, Hik white, Aluminum alloy, 97x182x305mm Suitable for: DS-2DE/AE4xxx-DS-2DE/AE5xxx-DS-2DE/AE7xxx-DS-2DF8xxx-DS-2DF6xxx-DS-2DF7xxx-DS-2DF5xxx	Call
DS-1602ZJ-pole	 Vertical pole mount, Hik white, Aluminum alloy, 117x194x310mm, Suitable for: DS-2DE/AE5xxx-DS-2DE/AE7xxx-DS-2DF8xxx-DS-2DF6xxx-DS-2DF7xxx-DS-2DF5xxx	Call
DS-1605ZJ	 Wall Mount bracket Parameters: Wall mounting bracket-Colour: Hik White-Feature: Suitable for speed dome cameras Dimensions: Ø171.7 x 158 x 228.6mm	Call

DS-1661ZJ		Pendent Mounting Bracket In/Outdoor,-Color: -Hik white-Material: -Aluminum alloy- Dimensin: -116.5x200mm-Weight: -600g	Call
DS-1662ZJ		Pendant mount , Hik white , Aluminum alloy , Φ116.5×500mm Suitable for:-DS-2DE/AE4xxx-DS-2DE/AE5xxx-DS-2DE/AE7xxx-DS-2DF8xxx-DS-2DF6xxx- DS-2DF7xxx-DS-2DF5xxx	Call
DS-1663ZJ		Ceiling mount , Hik white , Aluminum alloy , Φ116.5×57mm-Suitable for:-DS-2DE/AE4xxx DS-2DE/AE5xxx-DS-2DE/AE7xxx-DS-2DF8xxx-DS-2DF6xxx-DS-2DF7xxx-DS-2DF5xxx	Call
DS-1693ZJ		Wall mount , Hik white , steel , 190x200x500mm , 5700g Suitable for PTZ positioner	49,960,000
DS-1681ZJ		Ceiling mount , Hik white , Aluminum alloy -Suitable for:-DS-2DE/AE4xxx-DS-2DE/AE5xxx DS-2DE/AE7xxx-DS-2DF8xxx-DS-2DF6xxx-DS-2DF7xxx-DS-2DF5xxx	2,310,000
DS-1273ZJ-135B	 	Wall mount , White , Aluminum alloy , with junction box , Φ135×182×120mm Suitable for: DS-2CD27xx	Call
<b>Keyboard</b>			
DS-1100KI		Network Keyboard, 7" TFT touch screen, up to 256 units of DVR/Network Cameras/Speed Dome management, 1-ch HD 1080p video steam decoding, USB 2.0 interface for video backup	Call
DS-1005KI		network Keyboard, USB interface, support Hikvision VMS, NVR, DVR	Call
<b>Tester</b>			
IPC-4300H		IPC-4300 IP camera tester 4.3 inch capacitive touch screen / ONVIF/ Hikvision, Dahua, etc more than 40 IP camera brands test /IP Camera view /12 V/2A power output / 5V 2A power bank / PoE power supply / HDMI output / WIFI	Call
DS-TT-X41T-tester		TurboHD (HD-TVI 2.0), HDMI 1.0, VGA, and CVBS Inputs - 7" TFT active matrix LCD monitor - TurboHD: Up to 720p @ 25/30/50/60 fps, 1080p @ 25/30 fps	Call
<b>Adapters</b>			
AD-121/P		12V-1A	Call
AD-122/P		12V -2A	Call
AD-122/PL		12V-2A	Call
AD-125/PL		12V -5A	Call
AD-12A/M		12V -10A-METAL	Call
AD-12F/M		12V -15A-METAL	Call
AD-12K/MF		12V -20A-METAL WITH FAN	Call
AD-12U/MF		12V -30A-METAL WITH FAN	Call