


















# PRICE LIST




















# HIKVISION











































0511111111  
 WWW.RADIS-CO.DS  
 RADIS.NET





















## Network Camera - NVR




















| SKU (#)                        | SKU (P) | Items                                       | Description   | User Price     |
|--------------------------------|---------|---|---|----------------|
| <b>Lite Mini Bullet Series</b> |         |   |   |                |
| 250281                         | 200281  | DS-2CV1021G0-IDW1                           |  2.0 MP IR Network Bullet Camera -1/2.8" progressive scan CMOS - Max. Frame Rate: 60Hz: 30fps (1920 × 1080, 1280 × 960, 1280 × 720 - 3D DNR (Digital Noise Reduction) - Up to 30 m IR range - 2.8 mm/4 mm/6 mm fixed lens - PoE (Power over Ethernet) - H.265+, H.265, H.264+, H.264 - IP66 - Dual stream - Digital WDR (Wide Dynamic Range)- Built-in WiFi  | call           |
| 250466                         | 200466  | DS-2CD1021G0E-I                             |  Hikvision 2MP Mini IR Network Bullet camera, 1/2.8" Progressive CMOS, ICR, 1920x1080:20fps (P)/(N), H.265 / H.264+ & H.264, 3D DNR, BLC, IR range: up to 30m, DC12V & PoE<br>Rs. 0.001Is our price higher or showing zero? Please chat now and ask for the best price. Prices if shown are inclusive of applicable taxes. Tax rate may be adjusted as per customer's taxation status. For supply of product only, excluding any cabling and/or installation. Shipping charges can sometimes vary. | call           |
| 250278                         | 200278  | <a href="#">DS-2CD1023G0E-I</a>             |  2.0 MP IR Network Bullet Camera -1/2.8" progressive scan CMOS - Max. Frame Rate: 60Hz: 30fps (1920 × 1080, 1280 × 960, 1280 × 720 - 3D DNR (Digital Noise Reduction) - Up to 30 m IR range - 2.8 mm/4 mm/6 mm fixed lens - PoE (Power over Ethernet) - H.265+, H.265, H.264+, H.264 - IP67 - Dual stream - Digital WDR (Wide Dynamic Range) - ECO CASE  | IRR 26,940,000 |
|                                | 200005  | <a href="#">DS-2CD1023G0-I</a>              |  2.0 MP IR Network Bullet Camera -1/2.8" progressive scan CMOS - Max. Frame Rate: 60Hz: 30fps (1920 × 1080, 1280 × 960, 1280 × 720 - 3D DNR (Digital Noise Reduction) - Up to 30 m IR range - 2.8 mm/4 mm/6 mm fixed lens - PoE (Power over Ethernet) - H.265+, H.265, H.264+, H.264 - IP67 - Dual stream - Digital WDR (Wide Dynamic Range)   | IRR 23,500,000 |
|                                | 200605  | <a href="#">DS-2CD1023G0-IUF</a>            |  2.0 MP IR Network Bullet Camera -1/2.7" progressive scan CMOS - Max. Frame Rate: 60Hz: 30fps (1920 × 1080, 1280 × 960, 1280 × 720 - 3D DNR (Digital Noise Reduction) - Up to 30 m IR range - 2.8-4 mm fixed lens - PoE (Power over Ethernet) - H.265+, H.265, H.264+, H.264 - IP67 - Dual stream - Digital WDR (Wide Dynamic Range)- Built-in microphone  | IRR 40,770,000 |
| 250288                         | 200288  | <a href="#">DS-2CD1043G0E-I</a>             |  4.0 MP IR Network Bullet Camera, 1/3" progressive scan CMOS, 3D DNR (Digital Noise Reduction), 2560 × 1440@20fps - Up to 30 m IR range, 2.8 mm/4 mm/6 mm fixed lens - PoE (Power over Ethernet), H.265+, H.265, H.264+, H.264 - IP67, Dual stream, Digital WDR (Wide Dynamic Range) - ECO CASE  | call           |
| 250401                         | 200401  | <a href="#">DS-2CD1047G0-L-ColorVu Lite</a> |  4 MP ColorVu Lite Fixed Bullet Network Camera, High quality imaging with 4 MP resolution<br>Excellent low-light performance, Efficient H.265+ compression technology, Water and dust resistant (IP67), 24/7 colorful imaging  | IRR 48,590,000 |
|                                | 200657  | <a href="#">DS-2CD1057G0-L</a>              |  5 MP ColorVu Lite Fixed Bullet Network Camera, High quality imaging with 5 MP resolution<br>Excellent low-light performance, Efficient H.265+ compression technology, Water and dust resistant (IP67), 24/7 colorful imaging  | IRR 58,820,000 |
| 250007                         | 200007  | <a href="#">DS-2CD1043G0-I</a>              |  4.0 MP IR Network Bullet Camera, 1/3" progressive scan CMOS, 3D DNR (Digital Noise Reduction), 2560 × 1440@20fps - Up to 30 m IR range, 2.8 mm/4 mm/6 mm fixed lens - PoE (Power over Ethernet), H.265+, H.265, H.264+, H.264 - IP67, Dual stream, Digital WDR (Wide Dynamic Range)   | IRR 35,160,000 |
| 250102                         | 200102  | <a href="#">DS-2CD1053G0-I</a>              |  5.0 MP IR Network Bullet Camera, 1/2.7" progressive scan CMOS, 3D DNR (Digital Noise Reduction), 2560 × 1920@20fps - Up to 30 m IR range, 2.8 mm/4 mm fixed lens - PoE (Power over Ethernet), H.265+, IP67, Dual stream, BLC, WDR 120 dB(Wide Dynamic Range)  | IRR 51,940,000 |
| <b>Lite Dome Series</b>        |         |   |   |                |
| 250103                         | 200103  | <a href="#">DS-2CD1323G0E-I</a>             |  1/2.8" progressive scan CMOS - 1920 × 1080@30fps - 2.8 mm/4 mm/6 mm fixed lens - H.264+, H.264 - Dual stream - Digital WDR (Wide Dynamic Range) - 3D DNR (Digital Noise Reduction) - Up to 30 m IR range - PoE (Power over Ethernet) - IP67   | IRR 29,590,000 |
| 250301                         | 200301  | <a href="#">DS-2CD1323G0-IU</a>             |  1/2.8" progressive scan CMOS - 1920 × 1080@30fps - 2.8 mm/4 mm/6 mm fixed lens - H.264+, H.264 - Dual stream - Digital WDR (Wide Dynamic Range) - 3D DNR (Digital Noise Reduction) - Up to 30 m IR range - PoE (Power over Ethernet) - IP67 - Built-in microphone   |                |
| 250403                         | 200403  | <a href="#">DS-2CD1323G0-IUF</a>            |  2 MP Fixed Turret Network Camera<br>1/2.7" progressive scan CMOS - 1920 × 1080@30fps - 2.8 mm/4 mm fixed lens - H.265+ - Digital WDR (Wide Dynamic Range) - 3D DNR (Digital Noise Reduction) - Up to 30 m IR range - PoE (Power over Ethernet) - IP67 - Built-in microphone, Metal & Plastic  | IRR 27,110,000 |
| 250389                         | 200389  | <a href="#">DS-2CD1327G0-L-ColorVu Lite</a> |  2 MP ColorVu Lite Fixed Turret Network Camera, High quality imaging with 2 MP resolution<br>Excellent low-light performance, Efficient H.265+ compression technology, Water and dust resistant (IP67), 24/7 colorful imaging  | IRR 35,000,000 |
| 250471                         | 200471  | <a href="#">DS-2CD1347G0-L-ColorVu Lite</a> |  4 MP ColorVu Lite Fixed Turret Network Camera, High quality imaging with 4 MP resolution<br>Excellent low-light performance, Efficient H.265+ compression technology, Water and dust resistant (IP67), 24/7 colorful imaging  | IRR 81,650,000 |
| 250631                         | 200631  | <a href="#">DS-2CD1357G0-L</a>              |  5 MP ColorVu Lite Fixed Turret Network Camera, High quality imaging with 5 MP resolution<br>Excellent low-light performance, Efficient H.265+ compression technology, Water and dust resistant (IP67), 24/7 colorful imaging  | IRR 58,790,000 |
|                                |         | DS-2CD2346G2-IU                             |  4 MP AcuSense Fixed Turret Network Camera<br>High quality imaging with 4 MP resolution<br>Excellent low-light performance with powered-by-DarkFighter technology<br>Clear imaging against strong backlight due to 120 dB WDR technology<br>Efficient H.265+ compression technology<br>Focus on human and vehicle targets classification based on deep learning<br>Built-in microphone for real-time audio security(-U)<br>Water and dust resistant (IP67)                                       | IRR 76,820,000 |



















|                           |        |   |   |   |                 |
|---------------------------|--------|---|---|---|-----------------|
| 250658                    | 200658 | <a href="#">DS-2CD2347G2-L (2.8mm)</a>      |    | High quality imaging with 4 MP resolution<br>Efficient H.265+ compression technology<br>Clear imaging against strong backlight due to 130 dB WDR technology<br>Built-in microphone for real-time audio security(-U)<br>Focus on human and vehicle targets classification based on deep learning<br>24/7 colorful imaging<br>Water and dust resistant (IP67)   | IRR 78,910,000  |
|                           |        | <a href="#">DS-2CD2327G2-L 2.8mm</a>        |    | High quality imaging with 2 MP resolution<br>Efficient H.265+ compression technology<br>Clear imaging against strong back light due to 120 dB WDR technology<br>Focusing on human and vehicle classification based on deep learning<br>Built-in microphone for real-time audio security(-U)<br>24/7 colorful imaging  | IRR 81,110,000  |
|                           |        | <a href="#">DS-2CD2347G2-LU</a>             |    | 4 MP ColorVu Fixed Turret Network Camera<br>High quality imaging with 4 MP resolution<br>Efficient H.265+ compression technology<br>Clear imaging against strong backlight due to 130 dB WDR technology<br>Built-in microphone for real-time audio security(-U)<br>Focus on human and vehicle targets classification based on deep learning<br>24/7 colorful imaging, Water and dust resistant (IP67)   | IRR 89,760,000  |
| 250725                    | 200725 | <a href="#">DS-2CD1353G0-I</a>              |    | 5 MP IR Fixed Network Turret Camera<br>* 1/2.7" Progressive Scan CMOS, * 2560 x 1920 @ 15fps<br>* Color: 0.01 Lux @ (F1.2, AGC ON), 0.028 Lux @ (F2.0, AGC ON), * 2.8/4/6 mm fixed lens<br>* H.265+, H.265, H.264+, H.264<br>* 3D Digital Noise Reduction<br>* IP67   | IRR 52,050,000  |
| 250647                    | 200647 | <a href="#">DS-2CD2743G2-ZS</a>             |    | 4 MP AcuSense Motorized Varifocal Dome Network Camera<br>High quality imaging with 4 MP resolution<br>Motorized varifocal lens for easy installation and monitoring<br>Clear imaging against strong backlight due to 120 dB WDR technology<br>Efficient H.265+ compression technology<br>Water and dust resistant (IP67) and vandal proof (IK10)<br>Focus on human and vehicle targets classification based on deep learning  | IRR 149,000,000 |
| 250104                    | 200104 | <a href="#">DS-2CD1123G0E-I</a>             |    | 2MP dome Exir, fixed lens 2.8mm, white color-1/2.8" progressive scan CMOS - 3D DNR (Digital Noise Reduction) - 1920 x 1080@30fps - Up to 30 m IR range - 2.8 mm/4 mm/6 mm fixed lens - PoE (Power over Ethernet) - H.265+, H.265, H.264+, H.264 - IP67, IK10 - Digital WDR (Wide Dynamic Range) - ECO CASE  | IRR 26,360,000  |
| 250006                    | 200006 | <a href="#">DS-2CD1123G0-I</a>              |    | 2MP dome Exir, fixed lens 2.8mm, white color-1/2.8" progressive scan CMOS - 3D DNR (Digital Noise Reduction) - 1920 x 1080@30fps - Up to 30 m IR range - 2.8 mm/4 mm/6 mm fixed lens - PoE (Power over Ethernet) - H.265+, H.265, H.264+, H.264 - IP67, IK10 - Digital WDR (Wide Dynamic Range)   | call            |
| 250769                    | 200769 | <a href="#">DS-2CD2126G2-4SU 2.8mm</a>      |    | 2 MP AcuSense Fixed Dome Network Camera<br>High quality imaging with 2 MP resolution<br>Excellent low-light performance with powered-by-DarkFighter technology<br>Efficient H.265+ compression technology<br>Clear imaging against strong back light due to 120 dB true WDR technology<br>Focus on human and vehicle classification based on deep learning<br>-SU: Built-in microphone for real-time audio security, Audio and alarm interface available<br>Water and dust resistant (IP67) and vandal resistant (IK10) | IRR 81,540,000  |
| 250002                    | 200002 | <a href="#">DS-2CD1143G0-I</a>              |    | 4.0 MP IR Network Dome Camera, 1/3" progressive scan CMOS - 3D DNR (Digital Noise Reduction), 2560 x 1440@20fps - Up to 30 m IR range, 2.8 mm/4 mm/6 mm fixed lens, PoE (Power over Ethernet), H.265+, H.265, H.264+, H.264 - IP67, IK10, Dual stream, Digital WDR (Wide Dynamic Range)   | IRR 41,780,000  |
| 250700                    | 200700 | <a href="#">DS-2CD1143G0-IUF</a>            |   | High quality imaging with 4 MP resolution<br>Efficient H.265+ compression technology<br>Clear imaging even with strong back lighting due to 120 dB WDR<br>Water and dust resistant (IP67)<br>EXIR 2.0: advanced infrared technology with long IR range<br>-UF: Built-in microphone for real-time audio security   | IRR 55,980,000  |
| 250328                    | 200328 | <a href="#">DS-2CD1153G0-I</a>              |  | 5 MP Fixed Dome Network Camera<br>High quality imaging with 5 MP resolution<br>Efficient H.265+ compression technology<br>Clear imaging even with strong back lighting due to 120 dB WDR<br>Water and dust resistant (IP67) and vandal resistant (IK10)<br>EXIR 2.0: advanced infrared technology with long IR range  | IRR 54,540,000  |
| <b>Mini Bullet Series</b> |        |   |   |   |                 |
| 250348                    | 200348 | <a href="#">DS-2CD2025FWD-I</a>             |  | 2 MP Powered-by-DarkFighter Fixed Mini Bullet Network Camera<br>High quality imaging with 2 MP resolution<br>Excellent low-light performance via powered-by-DarkFighter technology, Efficient H.265+ compression technology, Clear imaging against strong back light due to 120 dB true WDR technology, Water and dust resistant (IP67), Robust structure design with full metal material.  |                 |
|                           |        | <a href="#">DS-2CD2021G1-I</a>              |  | 2 MP IR Fixed Network Bullet Camera High quality imaging with 2 MP resolution<br>Efficient H.265+ compression technology<br>Clear imaging against strong back light due to 120 dB true WDR technology<br>Water and dust resistant (IP67)<br>Support up to 256 GB SD card storage  | IRR 49,980,000  |
| 250671                    | 200671 | <a href="#">DS-2CD2023G2-I</a>              |  | 2 MP IR Fixed Bullet Network Camera - 1/2.8" Progressive Scan CMOS - 1920 x 1080@30fps - 2.8/4/6/8 mm fixed lens - Color: 0.01 Lux @ (F1.2, AGC ON), 0.018 Lux @ (F1.6, AGC ON), 0 Lux with IR - H.265+, H.265, H.265+ - 120dB WDR - 2 Behavior analyses, and face detection - BLC/3D DNR/ROI - IP67-Up to 40 m IR range - Built-in micro SD/SDHC/SDXC card slot, up to 256 GB  | IRR 61,240,000  |
| 250622                    | 200622 | <a href="#">DS-2CD2027G2-L ColorVu Lite</a> |  | 2 MP IR Fixed Bullet Network Camera - 1/2.8" Progressive Scan CMOS - 1920 x 1080@30fps - 2.8/4/6 mm fixed lens - Color: 0.01 Lux @ (F1.2, AGC ON), 0.018 Lux @ (F1.6, AGC ON), 0 Lux with IR - H.265, H.265+ - 120dB WDR - BLC/3D DNR/ROI - IP67-Up to 40 m IR range - Built-in micro SD/SDHC/SDXC card slot, up to 256 GB  | IRR 71,040,000  |
| 250503                    | 200503 | <a href="#">DS-2CD2043G2-I</a>              |  | 4 MP IR Fixed Bullet Network Camera - 1/3" Progressive Scan CMOS - 2560 x 1440@30fps - 2.8/4/6/8 mm fixed lens - Color: 0.01 Lux @ (F1.2, AGC ON), 0.018 Lux @ (F1.6, AGC ON), 0 Lux with IR - H.265+ - Three streams - 120dB WDR - 2 Behavior analyses, and face detection - BLC/HLC/3D DNR/ROI - IP67 - Built-in micro SD/SDHC/SDXC card slot, up to 256 GB   | IRR 66,560,000  |
|                           |        | <a href="#">DS-2CD2043G2-IU</a>             |  | 4 MP AcuSense Fixed Bullet Network Camera<br>High quality imaging with 4 MP resolution<br>Clear imaging against strong backlight due to 120 dB WDR technology<br>Efficient H.265+ compression technology<br>-U: Built-in microphone for real-time audio security<br>Water and dust resistant (IP67)   | IRR 79,110,000  |
| 250505                    | 200505 | <a href="#">DS-2CD2047G2-L ColorVu Lite</a> |  | 4 MP IR Fixed Bullet Network Camera - 1/1.8" Progressive Scan CMOS - 1920 x 1080@30fps - 2.8/4/6 mm fixed lens - Color: 0.01 Lux @ (F1.2, AGC ON), 0.018 Lux @ (F1.6, AGC ON), 0 Lux with IR - H.265, H.265+ - 130dB WDR - BLC/3D DNR/ROI - IP67-Up to 40 m IR range - Built-in micro SD/SDHC/SDXC card slot, up to 256 GB  | IRR 77,730,000  |
| 250108                    | 200108 | <a href="#">DS-2CD2063G0-I</a>              |  | 6 MP IR Fixed Bullet Network Camera - 1/2.8" Progressive Scan CMOS - 3072 x 2048@20 fps - 2.8/4/6/8 mm fixed lens - Color: 0.01 lux @ (F1.2, AGC ON), 0.028 lux @ (F2.0, AGC ON), 0 lux with IR - H.265+, H.265, H.264+, H.264 - 2 Behavior analyses and face detection - 120dB WDR - BLC/3D DNR/ROI - IP67 - Built-in micro SD/SDHC/SDXC card slot, up to 128 GB   | call            |


















|                    |        |  |   |  |                 |
|--------------------|--------|--|---|--|-----------------|
| 250558             | 200558 | <a href="#">DS-2CD2063G2-I</a>               |    | 6 MP IR Fixed Bullet Network Camera - 1/2.9" Progressive Scan CMOS - 3072 x 2048@20 fps - 2.8/4/6/8 mm fixed lens - Color: 0.01 lux @(F1.2, AGC ON), 0.028 lux @(F2.0, AGC ON), 0 lux with IR - H.265+, H.265, H.264+, H.264 - 2 Behavior analyses and face detection - 120dB WDR - BLC/3D DNR/ROI - IP67 - Built-in micro SD/SDHC/SDXC card slot, up to 128 GB  | IRR 73,050,000  |
| 250503             | 200503 | <a href="#">DS-2CD2043G2-I</a>               |    | 6 MP IR Fixed Bullet Network Camera - 1/2.8" Progressive Scan CMOS - 3072 x 2048@20 fps - 2.8/4/6/8 mm fixed lens - Color: 0.01 lux @(F1.2, AGC ON), 0.028 lux @(F2.0, AGC ON), 0 lux with IR - H.265+ - 2 Behavior analyses and face detection - 120dB WDR - BLC/3D DNR/ROI - IP67 - Built-in micro SD/SDHC/SDXC card slot, up to 256 GB  | IRR 66,460,000  |
|                    |        | <a href="#">DS-2CD2046G2-I</a>               |    | 4 MP AcuSense Fixed Mini Bullet Network Camera<br>High quality imaging with 4 MP resolution<br>Excellent low-light performance with powered-by-DarkFighter technology<br>Clear imaging against strong backlight due to 120 dB true WDR technology<br>Efficient H.265+ compression technology<br>Focus on human and vehicle targets classification based on deep learning   | IRR 72,370,000  |
|                    |        | <a href="#">DS-2CD2066G2-I</a>               |    | 6 MP AcuSense Fixed Bullet Network Camera<br>High quality imaging with 6 MP resolution<br>Excellent low-light performance with powered-by-DarkFighter technology<br>Efficient H.265+ compression technology<br>Clear imaging against strong backlight due to 120 dB true WDR technology<br>Focus on human and vehicle targets classification based on deep learning  | IRR 80,220,000  |
|                    |        | <a href="#">DS-2CD2086G2-I</a>               |    | 4K AcuSense Fixed Mini Bullet Network Camera<br>High quality imaging with 8 MP resolution<br>Excellent low-light performance with powered-by-DarkFighter technology<br>Efficient H.265+ compression technology<br>Clear imaging against strong backlight due to 120 dB true WDR technology<br>Focus on human and vehicle targets classification based on deep learning   | IRR 101,040,000 |
|                    |        | <a href="#">DS-2CD2025FHWI-I</a>             |    | High quality imaging with 2 MP resolution<br>Excellent low-light performance via powered-by-DarkFighter technology<br>Efficient H.265+ compression technology<br>Clear imaging against strong backlight due to 120 dB true WDR technology<br>High frame rate video to illustrate smooth movement<br>Water and dust resistant (IP67)  | IRR 70,060,000  |
|                    |        | <a href="#">DS-2CD2045FWD-I</a>              |    | 4 MP Powered-by-DarkFighter Fixed Mini Bullet Network Camera<br>High quality imaging with 4 MP resolution<br>Excellent low-light performance via powered-by-DarkFighter technology<br>Efficient H.265+ compression technology<br>Clear imaging against strong backlight due to 120 dB true WDR technology<br>Water and dust resistant (IP67)   | IRR 44,380,000  |
| 250596             | 200596 | <a href="#">DS-2CD2083G2-I</a>               |    | 8 MP IR Fixed Bullet Network Camera - 1/2.8" Progressive Scan CMOS - 3840 x 2160 @15 fps - 2.8/4/6/8 mm fixed lens - Color: 0.01 lux @(F1.2, AGC ON), 0.028 lux @(F2.0, AGC ON), 0 lux with IR - H.265+<br>Up to 40 m IR range - 2 Behavior analyses and face detection - 120dB WDR - BLC/3D DNR/ROI/HLC - IP67 - Built-in micro SD/SDHC/SDXC card slot, up to 256 GB  | IRR 79,190,000  |
|                    |        | <a href="#">DS-2CD2085G1-I</a>               |    | 4K Powered-by-DarkFighter Fixed Mini Bullet Network Camera<br>High quality imaging with 8 MP resolution<br>Excellent low-light performance via powered-by-DarkFighter technology<br>Efficient H.265+ compression technology<br>Clear imaging against strong backlight due to 120 dB true WDR technology<br>Water and dust resistant (IP67)   | IRR 117,160,000 |
| 250724             | 200724 | <a href="#">DS-2CD2087G2-LU ColorVu Lite</a> |    | 8 MP IR Fixed Bullet Network Camera - 1/1.2" Progressive Scan CMOS - 2.8/4/6/8 mm fixed lens - Color: 0.01 lux @(F1.2, AGC ON), 0.028 lux @(F2.0, AGC ON), 0 lux with IR - H.265+<br>Up to 40 m IR range - 2 Behavior analyses and face detection - 130dB WDR - BLC/3D DNR/ROI/HLC - IP67 - Built-in micro SD/SDHC/SDXC card slot, up to 256 GB, Built-in microphone   | IRR 156,550,000 |
| <b>Dome Series</b> |        |  |   |  |                 |
| 250110             | 200110 | <a href="#">DS-2CD2123G0-IS</a>              |   | 2 MP IR Fixed Dome Network Camera - 1/2.8" Progressive Scan CMOS - 1920 x 1080@30fps - 2.8/4/6/8mm fixed lens - Color: 0.01 Lux @ (F1.2, AGC ON), 0.028 Lux @ (F2.0, AGC ON), 0 Lux with IR - H.265+, H.265, H.264+, H.264 - Three streams - 120dB WDR - 2 Behavior analyses, and face detection - BLC/3D DNR/ROI/HLC - IP67 - IK10 - Built-in micro SD/SDHC/SDXC card slot, up to 128GB S; Audio/Alarm IO connectors  | call            |
| 250690             | 200690 | <a href="#">DS-2CD2123G2-I</a>               |  | 2 MP IR Fixed Dome Network Camera - 1/2.8" Progressive Scan CMOS - 1920 x 1080@30fps - 2.8/4mm-fixed lens - Color: 0.01 Lux @ (F1.2, AGC ON), 0.028 Lux @ (F2.0, AGC ON), 0 Lux with IR - H.265+ - Three streams - 120dB WDR - 2 Behavior analyses, and face detection - BLC/3D DNR/ROI/HLC - IP67 - IK10 - Built-in micro SD/SDHC/SDXC card slot, up to 256GB S; Audio/Alarm IO connectors, Up to 30 m IR range   |                 |
|                    |        | <a href="#">DS-2CD2123G2-IU</a>              |  | High quality imaging with 2 MP resolution<br>Clear imaging against strong backlight due to 120 dB WDR technology<br>Efficient H.265+ compression technology<br>Built-in microphone for real-time audio security<br>Focus on human and vehicle targets classification based on deep learning<br>Water and dust resistant (IP67) and vandal proof (IK10)   | IRR 62,810,000  |
|                    |        | <a href="#">DS-2CD2125FHWI-IS</a>            |  | 2 MP High Frame Rate Fixed Dome Network Camera, High quality imaging with 2 MP resolution<br>Excellent low-light performance via powered-by-DarkFighter technology<br>Efficient H.265+ compression technology<br>Clear imaging against strong backlight due to 120 dB true WDR technology<br>High frame rate video to illustrate smooth movement, S: audio and alarm interface available<br>Water and dust resistant (IP67) and vandal proof (IK10), Robust structure design with full metal materials.<br>www.hikvision.com | IRR 49,060,000  |
|                    |        | <a href="#">DS-2CD2H25FWD-I2S</a>            |  | High quality imaging with 2 MP resolution<br>Excellent low-light performance via powered-by-DarkFighter technology<br>Efficient H.265+ compression technology<br>Clear imaging against strong backlight due to 120 dB true WDR technology<br>Water and dust resistant (IP66) and vandal proof (IK10)<br>Motorized varifocal lens for easy installation and monitoring  | IRR 138,870,000 |
| 250387             | 200387 | <a href="#">DS-2CD2143G2-IU</a>              |  | 4 MP Vandal Built-in Mic Fixed Dome Network Camera<br>High quality imaging with 4 MP resolution<br>Clear imaging against strong backlight due to 120 dB WDR technology, Efficient H.265+ compression technology, Built-in microphone for real-time audio security<br>Water and dust resistant (IP67) and vandal resistant (IK10)<br>Focus on human and vehicle targets classification based on deep learning   | IRR 66,890,000  |
| 250274             | 200274 | <a href="#">DS-2CD2143G0-IU</a>              |  | 4 MP IR Fixed Dome Network Camera - 1/3" Progressive Scan CMOS, 2688 x 1520@30fps, 2.8/4/6/8mm fixed lens - Color: 0.01 Lux @ (F1.2, AGC ON), 0.018 Lux @ (F1.6, AGC ON), 0 Lux with IR - H.265+, H.265, H.264+, H.264 - Three streams - 120dB WDR - 2 Behavior analyses, and face detection - BLC/3D DNR/ROI - IP66 - IK10 - Built-in micro SD/SDHC/SDXC card slot, up to 128 GB - Built-in microphone  | call            |
|                    |        | <a href="#">DS-2CD2145FWD-IS</a>             |  | 4 MP Powered-by-DarkFighter Fixed Dome Network Camera<br>High quality imaging with 4 MP resolution<br>Excellent low-light performance via powered-by-DarkFighter technology<br>Efficient H.265+ compression technology<br>Clear imaging against strong backlight due to 120 dB true WDR technology<br>S: audio and alarm interface available<br>Water and dust resistant (IP67) and vandal proof (IK10)  | IRR 49,060,000  |
|                    |        | <a href="#">DS-2CD2146G2-I</a>               |  | 4 MP AcuSense Fixed Dome Network Camera<br>High quality imaging with 4 MP resolution<br>Excellent low-light performance with powered-by-DarkFighter technology<br>Clear imaging against strong backlight due to 120 dB true WDR technology<br>Efficient H.265+ compression technology<br>Focus on human and vehicle targets classification based on deep learning<br>Built-in microphone for real-time audio security (SU)   | IRR 49,240,000  |
|                    |        | <a href="#">DS-2CD2147G2-LSU (2.8mm)</a>     |  | 4 MP ColorVu Fixed Dome Network Camera, High quality imaging with 4 MP resolution<br>Efficient H.265+ compression technology<br>Clear imaging against strong backlight due to 130 dB WDR technology<br>24/7 colorful imaging<br>Focus on human and vehicle targets classification based on deep learning<br>-SU: Built-in microphone for real-time audio security, audio and alarm interface available<br>Water and dust resistant (IP67) and vandal resistant (IK10)  | IRR 86,980,000  |

|                      |        |  |   |   |                 |
|----------------------|--------|--|---|---|-----------------|
| 250554               | 200554 | <a href="#">DS-2CD2163G2-IU (2.8mm)</a>  |    | 6 MP AcuSense Vandal Fixed Dome Network Camera<br>High quality imaging with 6 MP resolution<br>Clear imaging against strong backlight due to 120 dB true WDR technology<br>Efficient H.265+ compression technology<br>Focus on human and vehicle targets classification based on deep learning<br>Built-in microphone for real-time audio security<br>Water and dust resistant (IP67) and vandal resistant (IK10)   | IRR 71,920,000  |
|                      |        | <a href="#">DS-2CD2166G2-I (2.8mm)</a>   |    | 6 MP AcuSense Fixed Dome Network Camera<br>High quality imaging with 6 MP resolution<br>Excellent low-light performance with powered-by-DarkFighter technology<br>Efficient H.265+ compression technology<br>Clear imaging against strong back light due to 120 dB true WDR technology<br>Focus on human and vehicle targets classification based on deep learning<br>Built-in microphone for real-time audio security (SU)   | IRR 53,050,000  |
|                      |        | <a href="#">DS-2CD2166G2-ISU (2.8mm)</a> |    | 6 MP AcuSense Fixed Dome Network Camera<br>High quality imaging with 6 MP resolution<br>Excellent low-light performance with powered-by-DarkFighter technology<br>Efficient H.265+ compression technology<br>Clear imaging against strong back light due to 120 dB true WDR technology<br>Focus on human and vehicle targets classification based on deep learning<br>Built-in microphone for real-time audio security (SU)   | IRR 87,390,000  |
| 250114               | 200114 | <a href="#">DS-2CD2183G0-IS</a>          |    | 8 MP IR Fixed Dome Network Camera - BLC/3D DNR/ROI - IP67, IK10 - Built-in micro SD/SDHC/SDXC card slot, up to 128 GB - 1/2.5" Progressive Scan CMOS - 3840 x 2160 @15 fps - 2.8/4/6/8 mm fixed lens - Color: 0.01 lux @ (F1.2, AGC ON), 0.028 lux @ (F2.0, AGC ON), 0 lux with IR - H.265+, H.265, H.264+, H.264 - 2 Behavior analyses and face detection -120dB WDR - S: Audio/Alarm IO connectors  | IRR 48,790,000  |
| 250611               | 200611 | <a href="#">DS-2CD2183G2-IU</a>          |    | 8 MP IR Fixed Dome Network Camera - BLC/3D DNR/ROI - IP67, IK10 - Built-in micro SD/SDHC/SDXC card slot, up to 256 GB - 1/2.5" Progressive Scan CMOS - 3840 x 2160 @15 fps - 2.8/4 mm fixed lens - Color: 0.01 lux @ (F1.2, AGC ON), 0.028 lux @ (F2.0, AGC ON), 0 lux with IR - H.265+ - 2 Behavior analyses and face detection -120dB WDR - Built-in microphone, Up to 30 m IR range  | IRR 74,280,000  |
|                      |        | <a href="#">DS-2CD2185FWD-I</a>          |    | 4K Fixed Dome Network Camera<br>High quality imaging with 8 MP resolution, Efficient H.265+ compression technology<br>Clear imaging against strong back light due to 120 dB true WDR technology<br>S: audio and alarm interface available<br>Water and dust resistant (IP67) and vandal proof (IK10)<br>Robust structure design with full metal materials.  | IRR 108,460,000 |
|                      |        | <a href="#">DS-2CD2186G2-I (2.8mm)</a>   |    | 4K AcuSense Fixed Dome Network Camera, High quality imaging with 8 MP resolution<br>Excellent low-light performance via powered-by-DarkFighter technology<br>Efficient H.265+ compression technology<br>Clear imaging against strong back light due to 120 dB true WDR technology<br>Focus on human and vehicle targets classification based on deep learning<br>Built-in microphone for real-time audio security (SU)<br>Audio and alarm interface available (SU)<br>Water and dust resistant (IP67) and vandal resistant (IK10) | IRR 65,930,000  |
| <b>Bullet Series</b> |        |  |   |   |                 |
| 250564               | 200564 | <a href="#">DS-2CD2T43G2-2I (2.8mm)</a>  |    | 1/3" Progressive Scan CMOS, 2688 x 1520 @30fps, 2.8mm fixed lens - Color: 0.01 Lux @ (F1.2, AGC ON), 0.018 Lux @ (F1.6, AGC ON), 0 Lux with IR, H.265+, Three streams, 120dB WDR, Focus on human and vehicle targets classification based on deep learning, BLC/3D DNR/ROI - IP67 - Built-in micro SD/SDHC/SDXC card slot, up to 256 GB-up to 60m IR range  | IRR 66,970,000  |
|                      |        | <a href="#">DS-2CD1T43G2-LIU</a>         |    | High quality imaging with 4 MP resolution<br>Support Human and Vehicle Detection<br>Smart Dual-Light: advanced technology with long range<br>Built-in microphone for real-time audio security<br>Water and dust resistant (IP67)<br>Efficient H.265+ compression technology   | IRR 48,010,000  |
| 250564               | 200564 | <a href="#">DS-2CD2T43G2-2I (4mm)</a>    |  | 1/3" Progressive Scan CMOS, 2688 x 1520 @30fps, 2.8mm fixed lens - Color: 0.01 Lux @ (F1.2, AGC ON), 0.018 Lux @ (F1.6, AGC ON), 0 Lux with IR, H.265+, Three streams, 120dB WDR, Focus on human and vehicle targets classification based on deep learning, BLC/3D DNR/ROI - IP67 - Built-in micro SD/SDHC/SDXC card slot, up to 256 GB-up to 60m IR range  | IRR 66,970,000  |
| 250507               | 200507 | <a href="#">DS-2CD2T43G2-4I</a>          |  | 1/3" Progressive Scan CMOS, 2688 x 1520 @30fps, 4mm fixed lens - Color: 0.01 Lux @ (F1.2, AGC ON), 0.018 Lux @ (F1.6, AGC ON), 0 Lux with IR, H.265+, Three streams, 120dB WDR, Focus on human and vehicle targets classification based on deep learning, BLC/3D DNR/ROI - IP67 - Built-in micro SD/SDHC/SDXC card slot, up to 256 GB-up to 80m IR range  | IRR 72,380,000  |
|                      |        | <a href="#">DS-2CD2T45FWD-I5</a>         |  | 4 MP Powered-by-DarkFighter Fixed Bullet Network Camera<br>High quality imaging with 4 MP resolution<br>Excellent low-light performance via powered-by-DarkFighter technology<br>Efficient H.265+ compression technology<br>Clear imaging against strong back light due to 120 dB true WDR technology<br>Water and dust resistant (IP67)  | IRR 52,170,000  |
|                      |        | <a href="#">DS-2CD2T45FWD-I8</a>         |  | 4 MP Powered-by-DarkFighter Fixed Bullet Network Camera<br>High quality imaging with 4 MP resolution<br>Excellent low-light performance via powered-by-DarkFighter technology<br>Efficient H.265+ compression technology<br>Clear imaging against strong back light due to 120 dB true WDR technology<br>Water and dust resistant (IP67)  | IRR 124,000,000 |
|                      |        | <a href="#">DS-2CD2T46G2-4I (2.8mm)</a>  |  | 4 MP AcuSense Fixed Bullet Network Camera<br>High quality imaging with 4 MP resolution<br>Excellent low-light performance with powered-by-DarkFighter technology<br>Clear imaging against strong backlight due to 120 dB true WDR technology<br>Efficient H.265+ compression technology<br>Focus on human and vehicle targets classification based on deep learning   | IRR 57,190,000  |
|                      |        | <a href="#">DS-2CD2T46G2-ISU/SL2.8mm</a> |  | 4 MP AcuSense Fixed Bullet Network Camera<br>High quality imaging with 4 MP resolution<br>Excellent low-light performance with powered-by-DarkFighter technology<br>Clear imaging against strong backlight due to 120 dB true WDR technology<br>Efficient H.265+ compression technology<br>Focus on human and vehicle targets classification based on deep learning<br>Active strobe light and audio alarm to warn intruders off<br>Provides real-time security via built-in two-way audio  | IRR 60,360,000  |
| 250685               | 200685 | <a href="#">DS-2CD2T47G2-L</a>           |  | 4 MP ColorVu Fixed Bullet Network Camera<br>High quality imaging with 4 MP resolution<br>Efficient H.265+ compression technology<br>Clear imaging against strong backlight due to 130 dB WDR technology<br>Focus on human and vehicle targets classification based on deep learning<br>24/7 colorful imaging<br>Water and dust resistant (IP67)   | IRR 95,580,000  |
| 250623               | 200623 | <a href="#">DS-2CD2T63G2-4I 4mm</a>      |  | High quality imaging with 6 MP resolution<br>Efficient H.265+ compression technology<br>Clear imaging against strong backlight due to 120 dB WDR technology<br>Focusing on human and vehicle classification based on deep learning<br>Water and dust resistant (IP67)   | IRR 82,330,000  |
|                      |        | <a href="#">DS-2CD2T66G2-2I</a>          |  | 6 MP AcuSense Fixed Bullet Network Camera<br>High quality imaging with 6 MP resolution<br>Excellent low-light performance with powered-by-DarkFighter technology<br>Efficient H.265+ compression technology<br>Clear imaging against strong back light due to 120 dB true WDR technology<br>Focus on human and vehicle targets classification based on deep learning  | IRR 58,980,000  |
| 250475               | 200475 | <a href="#">DS-2CD2T66G2-4I</a>          |  | 6 MP AcuSense Fixed Bullet Network Camera<br>High quality imaging with 6 MP resolution<br>Excellent low-light performance with powered-by-DarkFighter technology<br>Efficient H.265+ compression technology<br>Clear imaging against strong back light due to 120 dB true WDR technology<br>Focus on human and vehicle targets classification based on deep learning  | IRR 94,210,000  |
|                      |        | <a href="#">DS-2CD2T87G2-LK</a>          |  | 4 K ColorVu Fixed Bullet Network Camera<br>• High quality imaging with 8 MP resolution<br>• Efficient H.265+ compression technology<br>• Clear imaging against strong back light due to 130 dB WDR technology<br>• Focus on human and vehicle classification based on deep learning<br>• 24/7 colorful images   | IRR 113,860,000 |





















|  |        |   |   |   |                 |
|--|--------|---|---|---|-----------------|
| 250636   | 200636 | <a href="#">DS-2CD2683G2-I2S</a>        |    | 8 MP AcuSense Motorized Varifocal Bullet Network Camera<br>High quality imaging with 8 MP resolution<br>Motorized varifocal lens for easy installation and monitoring<br>Efficient H.265+ compression technology<br>Clear imaging against strong backlight due to 120 dB true WDR technology<br>Focus on human and vehicle targets classification based on deep learning<br>Audio and alarm interface available<br>Water and dust resistant (IP67) and vandal-resistant (IK10)              | IRR 142,680,000 |
| 250680   | 200680 | <a href="#">DS-2CD2T83G2-4I</a>         |    | High quality imaging with 8 MP resolution<br>Efficient H.265+ compression technology<br>Clear imaging against strong backlight due to 120 dB WDR technology<br>Focusing on human and vehicle classification based on deep learning<br>Water and dust resistant (IP67)   | IRR 93,900,000  |
|  |        | <a href="#">DS-2CD2T85G1-I6</a>         |    | 4K Powered-by-DarkFighter Fixed Bullet Network Camera<br>High quality imaging with 8 MP resolution<br>Excellent low-light performance via powered-by-DarkFighter technology<br>Efficient H.265+ compression technology<br>Clear imaging against strong back light due to 120 dB true WDR technology<br>Water and dust resistant (IP67)  | IRR 123,220,000 |
|  |        | <a href="#">DS-2CD2T85G1-I8</a>         |    | 4K Powered-by-DarkFighter Fixed Bullet Network Camera<br>High quality imaging with 8 MP resolution<br>Excellent low-light performance via powered-by-DarkFighter technology<br>Efficient H.265+ compression technology<br>Clear imaging against strong back light due to 120 dB true WDR technology<br>Water and dust resistant (IP67)  | IRR 134,730,000 |
| 250538   | 200538 | <a href="#">DS-2CD2T86G2-4I (2.8mm)</a> |    | 4K AcuSense Fixed Bullet Network Camera<br>High quality imaging with 8 MP resolution<br>Excellent low-light performance via powered-by-DarkFighter technology<br>Efficient H.265+ compression technology<br>Clear imaging against strong back light by 120 dB true WDR technology<br>Focus on human and vehicle targets classification based on deep learning   | IRR 100,420,000 |
| 250538   | 200538 | <a href="#">DS-2CD2T86G2-4I</a>         |    | 4K AcuSense Fixed Bullet Network Camera<br>High quality imaging with 8 MP resolution<br>Excellent low-light performance with powered-by-DarkFighter technology<br>Efficient H.265+ compression technology<br>Clear imaging against strong back light by 120 dB true WDR technology<br>Focus on human and vehicle targets classification based on deep learning<br>Water and dust resistant (IP67)   | IRR 120,150,000 |
| <b>Exir Dome Series</b>                        |        |   |   |   |                 |
|  |        | <a href="#">DS-2CD2327WD-I</a>          |    | Up to 2 megapixel high resolution - Full HD1080p video - Dual stream - 2.8mm/4mm/6mm fixed lens - 120dB Wide Dynamic Range - 3D Digital Noise Reduction - Backlight Compensation - DC12V & PoE - Support H.264+ - High performance EXIR LED - Up to 30m IR range - IP67 weather proof protection - 3-axis adjustment - Mobile Monitoring via EZVIZ P2P or Hik-Connect   | IRR 35,500,000  |
|  |        | <a href="#">DS-2CD2345FWD-I</a>         |    | 4MP Powered by DarkFighter Fixed Turret Network Camera<br>High quality imaging with 4 MP resolution<br>Excellent low-light performance via powered-by-DarkFighter technology<br>Efficient H.265+ compression technology<br>Clear imaging against strong back light due to 120 dB true WDR technology<br>Water and dust resistant (IP67)   | IRR 45,950,000  |
| <b>Mini Dome Series</b>                        |        |   |   |   |                 |
| 250121   | 200121 | <a href="#">DS-2CD2523G0-IS</a>         |    | 1/2.7" Progressive Scan CMOS - 1920 x 1080@30fps - H.265+/H.265/H.264+/H.264/MJPEG - IR: up to 10 m 120dB WDR - Built-in Micro SD/SDHC/SDXC slot, up to 128 GB - PoE - EXIR - Color: 0.01 Lux @ (F1.2, AGC ON), 0.028 lux @ (F2.0, AGC ON), 0 lux with IR - S: Built-in MIC, audio/alarm IO   | call            |
|  |        | <a href="#">DS-2CD2525FWD-I</a>         |    | 2 MP Powered-by-DarkFighter Fixed Mini Dome Network Camera, High quality imaging with 2 MP resolution<br>Excellent low-light performance via powered-by-DarkFighter technology, Efficient H.265+ compression technology<br>Clear imaging against strong back light due to 120 dB true WDR technology, -W: Wi-Fi connection<br>-S: built-in microphone, audio and alarm interface available<br>Water and dust resistant (IP66) and vandal proof (IK08), Mini size suitable for limited space | IRR 49,840,000  |
| 250122   | 200122 | <a href="#">DS-2CD2542FWD-IS</a>        |  | 1/3" Progressive CMOS, ICR, 0lux with IR, 2688x1520-20fps, 4mm/F2.0 lens (2.8mm, 6mm optional), H.264+/H.264/MJPEG, VCA functions, 3 streams, IP67, DC12V & PoE, 120dB WDR, 3D DNR, BLC, IR: up to 10m, support on-board storage up to 128GB(SD card not included), Hik-Connect cloud service-S: Built-in MIC, audio/alarm IO   | call            |
| 250123   | 200123 | <a href="#">DS-2CD2543G0-IS</a>         |  | 1/3" Progressive Scan CMOS - Color: 0.01 Lux @ (F1.2, AGC ON), 0.018 lux @ (F1.6, AGC ON), 0 lux with IR - 2688 x 1520@30fps - IR: up to 10 m - H.265+/H.265/H.264+/H.264/MJPEG - 120dB WDR - Built-in Micro SD/SDHC/SDXC slot, up to 128 GB - PoE - EXIR - S: Built-in MIC, audio/alarm IO   | call            |
| 250322   | 200322 | <a href="#">DS-2CD2563G0-IS</a>         |  | 1/3" Progressive Scan CMOS - Color: 0.01 Lux @ (F1.2, AGC ON), 0.018 lux @ (F1.6, AGC ON), 0 lux with IR - 3072 x 2048@20fps - IR: up to 10 m - H.265+/H.265/H.264+/H.264/MJPEG - 120dB WDR - Built-in Micro SD/SDHC/SDXC slot, up to 128 GB - PoE - EXIR - S: Built-in MIC, audio/alarm IO   | call            |
| <b>Lite Bullet Vari-Facal Motorized Series</b> |        |   |   |   |                 |
| 250125   | 200125 | <a href="#">DS-2CD1623G0-I2</a>         |  | 2MP Bullet Network camera - 2.8-12mm varifocal lens - EXIR - 1/2.8" progressive scan CMOS - BLC/3D DNR/ROI/1920 x 1080@30fps - Up to 30 m IR range - IP67 - Digital WDR - H.265+, H.265, H.264+, H.264/Color: 0.01 Lux @ (F1.2, AGC ON), 0.018 Lux - Built-in micro SD/SDHC/SDXC card slot, up to 128 GB - Z: Motorized VF lens   | call            |
| 250312   | 200312 | <a href="#">DS-2CD1643G0-I2</a>         |  | 4 MP EXIR VF Bullet Network Camera, 1/3" progressive scan CMOS - BLC/3D DNR/ROI - 2560 x 1440@20fps, Up to 30 m IR range, 2.8 mm to 12 mm varifocal lens - IP67 - H.265+, H.265, H.264+, H.264 - 120dB True WDR - Color: 0.01 Lux @ (F1.2, AGC ON), 0.018 Lux @ (F1.6, AGC ON) - Built-in micro SD/SDHC/SDXC card slot, up to 128 GB - Z: Motorized VF lens   | IRR 81,350,000  |
| <b>Lite Dome Vari-Facal Series</b>             |        |   |   |   |                 |
| 250344   | 200344 | <a href="#">DS-2CD1743G0-I2</a>         |  | 4.0 MP VF Network Dome Camera-1/3" progressive scan CMOS - 3D DNR (Digital Noise Reduction) 2560 x 1440@20fps @ Up to 30 m IR range- 2.8 mm to 12 mm manual/motorized (with - PoE (Power over Ethernet)- IP67 H.265+, H.265, H.264+, H.264- Dual stream- 120 dB WDR (Wide Dynamic Range) - Z: Motorized VF lens   | IRR 91,340,000  |
| 250618   | 200618 | <a href="#">DS-2CD1753G0-I2</a>         |  | 5 MP Varifocal Dome Network Camera<br>High quality imaging with 5 MP resolution, Efficient H.265+ compression technology<br>Clear imaging even with strong back lighting due to 120 dB WDR, Up to 256 GB memory card slot for storage, 2.8 to 12 mm motorized varifocal lens for easy installation and monitoring, Water and dust resistant (IP67) and vandal proof (IK10), EXIR 2.0: advanced infrared technology with long IR range   | IRR 98,470,000  |
| <b>Bullet Vari-Facal Motorized Series</b>      |        |   |   |   |                 |
| 250347   | 200347 | <a href="#">DS-2CD2625FWD-I2S</a>       |  | 2MP Powered by DarkFighter Varifocal Bullet Network Camera<br>High quality imaging with 2 MP resolution, Excellent low-light performance via powered-by-DarkFighter technology, Efficient H.265+ compression technology, Clear imaging against strong back light due to 120 dB true WDR technology, Water and dust resistant (IP66) and vandal proof (IK10), Motorized varifocal lens for easy installation and monitoring full metal materials.  | IRR 110,210,000 |
| 250130   | 200130 | <a href="#">DS-2CD2632F-I</a>           |  | 3 MP IR VF Bullet Network Camera - 1/3" Progressive CMOS, ICR, 0lux with IR, 2048x1536:25fps(P)/30fps(N), 2.8"-12mm VF lens, H.264/MJPEG/H.264+, dual-stream, IP66, DC12V & PoE, DWDR, 3D DNR, BLC, IR: up to 30m, Support on-board card slot (SD card not included), Support Mobile Monitoring via EZVIZ P2P   | IRR 60,500,000  |
| 250395   | 200395 | <a href="#">DS-2CD2643G2-I2S</a>        |  | 4 MP WDR Motorized Varifocal Bullet Network Camera, High quality imaging with 4 MP resolution<br>Motorized varifocal lens for easy installation and monitoring<br>Clear imaging against strong backlight due to 120 dB WDR technology<br>Efficient H.265+ compression technology, (IP67) and vandal resistant (IK10)<br>Focus on human and vehicle targets classification based on deep learning  | IRR 124,710,000 |












|   |        |                                   |   |  |                 |
|---|--------|-----------------------------------|---|--|-----------------|
|   |        | DS-2CD2645FWD-IZS                 |    | 4 MP Powered-by-DarkFighter Varifocal Bullet Network Camera<br>High quality imaging with 4 MP resolution<br>Excellent low-light performance via powered-by-DarkFighter technology<br>Efficient H.265+ compression technology<br>Clear imaging against strong back light due to 120 dB true WDR technology<br>Water and dust resistant (IP66) and vandal proof (IK10)   | IRR 92,660,000  |
| 250132                                  | 200132 | DS-2CD2663FG0-IZS                 |    | 6 MP IR VF Bullet Network Camera - BLC/3D DNR/ROI - IP67, IK10 - Built-in micro SD/SDHC/SDXC card slot, up to 128 GB - 1/2.9" Progressive Scan CMOS - 3072 x 2048@20fps - 2.8 to 12 mm varifocal lens - Color: 0.01 Lux @ (F1.2, AGC ON), 0.018 Lux @ (F1.6, AGC ON), 0 Lux with IR - H.265+, H.265, H.264+, H.264 - IR Range up to 50m - 120dB WDR - 2 Behavior analyses, and face detection - 2-Motorized VF lens  | call            |
|   |        | DS-2CD2666G2-IZS                  |    | High quality imaging with 6 MP resolution<br>Motorized varifocal lens for easy installation and monitoring<br>Excellent low-light performance with powered-by-DarkFighter technology<br>Efficient H.265+ compression technology<br>Clear imaging against strong back light due to 120 dB true WDR technology<br>Focus on human and vehicle targets classification based on deep learning   | IRR 152,640,000 |
|   |        | DS-2CD2685G1-IZS                  |    | 4K Powered-by-DarkFighter Varifocal Bullet Network Camera<br>High quality imaging with 8 MP resolution<br>Excellent low-light performance via powered-by-DarkFighter technology<br>Efficient H.265+ compression technology<br>Clear imaging against strong back light due to 120 dB true WDR technology<br>Water and dust resistant (IP67) and vandal proof (IK10)   | IRR 150,320,000 |
| 250133                                  | 200133 | DS-2CD2683G2-IZS                  |    | 8 MP(4K) IR Vari-focal Bullet Network Camera - 1/2.5" Progressive Scan CMOS - 3840 x 2160@15fps - 2.8 to 12 mm varifocal lens - Color: 0.01 Lux @ (F1.2, AGC ON), 0.018 Lux @ (F1.6, AGC ON), 0 Lux with IR - H.265+, H.265, H.264+, H.264 - IR Range up to 50m - 120dB WDR - 2 Behavior analyses, and face detection - BLC/3D DNR/ROI - IP67, IK10 - 2-Motorized VF lens  | IRR 139,300,000 |
|   |        | <a href="#">DS-2CD2685FWD-IZS</a> |    | 1/2.5" Progressive Scan CMOS 3840 x 2160 resolution H.265, H.265+ 120dB WDR IP67, IK10 BLC/3D DNR/ROI Smart encoding; Support low bit rate, low latency 4 behavior analyses and face detection   | IRR 124,080,000 |
| 250601                                  | 200601 | <a href="#">DS-2CD2686G2-IZS</a>  |    | 4K AcuSense Varifocal Bullet Network Camera, High quality imaging with 8 MP resolution<br>Motorized varifocal lens for easy installation and monitoring<br>Excellent low-light performance via powered-by-DarkFighter technology<br>Efficient H.265+ compression technology<br>Clear imaging against strong back light due to 120 dB true WDR technology<br>Focus on human and vehicle targets classification based on deep learning<br>Audio and alarm interface available<br>Water and dust resistant (IP66) and vandal proof (IK10)   | IRR 181,590,000 |
| <b>Dome Vari-Facal Motorized Series</b> |        |                                   |   |  |                 |
| 250268                                  | 200268 | <a href="#">DS-2CD2743G2-IZS</a>  |    | 4 MP Outdoor WDR Motorized Varifocal Dome Network Camera<br>High quality imaging with 4 MP resolution<br>Clear imaging against strong back light due to 120 dB true WDR technology-S: audio and alarm interface available-Water and dust resistant (IP67) and vandal proof (IK10)-Motorized varifocal lens for easy installation and monitoring-Robust structure design with full metal materials  | IRR 149,000,000 |
|   |        | <a href="#">DS-2CD2745FWD-IZS</a> |    | 4 MP Powered-by-DarkFighter varifocal dome network camera<br>High quality imaging with 4 MP resolution<br>Excellent low-light performance via powered-by-DarkFighter technology<br>Efficient H.265+ compression technology<br>Clear imaging against strong back light due to 120 dB true WDR technology<br>Water and dust resistant (IP66) and vandal proof (IK10)<br>Motorized varifocal lens for easy installation and monitoring  | IRR 92,660,000  |
|   |        | DS-2CD2746G2-IZS                  |    | High quality imaging with 4 MP resolution<br>Excellent low-light performance with powered-by-DarkFighter technology<br>Clear imaging against strong back light due to 120 dB true WDR technology, Efficient H.265+ compression technology<br>False alarm reduction through human and vehicle target classification based on deep learning, S: audio and alarm interface available  | IRR 152,400,000 |
| 250137                                  | 200137 | DS-2CD2763G0-IZS                  |   | 6 MP IR Vari-focal Dome Network Camera - 1/2.9" Progressive Scan CMOS - 3072 x 2048@20fps - 2.8 to 12 mm varifocal lens - Max IR distance: 30 meters - Color: 0.01 Lux @ (F1.2, AGC ON), 0.018 Lux @ (F1.6, AGC ON), 0 Lux with IR - H.265+, H.265, H.264+, H.264 - 120dB WDR - 2 Behavior analyses, and face detection - BLC/3D DNR/ROI - IP67, IK10 - Built-in micro SD/SDHC/SDXC card slot, up to 128 GB - 2: Motorized VF lens   | call            |
|   |        | DS-2CD2763G1-IZS                  |  | High quality imaging with 6 MP resolution<br>Efficient H.265+ compression technology<br>Clear imaging against strong back light due to 120 dB true WDR technology<br>S: audio and alarm interface available<br>Water and dust resistant (IP67) and vandal proof (IK10)<br>Motorized varifocal lens for easy installation and monitoring  | IRR 142,160,000 |
| 250138                                  | 200138 | DS-2CD2783G2-IZS                  |  | 8 MP(4K) IR Vari-focal Dome Network Camera - 1/2.5" Progressive Scan CMOS - 3840 x 2160@15fps - Max IR distance: 30 meters - 2.8 to 12 mm varifocal lens - Color: 0.01 Lux @ (F1.2, AGC ON), 0.018 Lux @ (F1.6, AGC ON), 0 Lux with IR - H.265+, H.265, H.264+, H.264 - 120dB WDR - 2 Behavior analyses, and face detection - BLC/3D DNR/ROI - IP67 - IK10 - Built-in micro SD/SDHC/SDXC card slot, up to 128 GB - 2: Motorized VF lens  | IRR 139,720,000 |
|   |        | DS-2CD2785G1-IZS                  |  | 4K Powered-by-DarkFighter Varifocal Dome Network Camera<br>High quality imaging with 8 MP resolution<br>Excellent low-light performance via powered-by-DarkFighter technology<br>Efficient H.265+ compression technology<br>Clear imaging against strong back light due to 120 dB true WDR technology<br>Water and dust resistant (IP67) and vandal proof (IK10)   | IRR 150,320,000 |
| 250753                                  | 200753 | <a href="#">DS-2CD2786G2-IZS</a>  |  | 4K AcuSense Varifocal Dome Network Camera, High quality imaging with 8 MP resolution<br>Motorized varifocal lens for easy installation and monitoring<br>Excellent low-light performance via powered-by-DarkFighter technology<br>Efficient H.265+ compression technology<br>Clear imaging against strong back light due to 120 dB true WDR technology<br>Focus on human and vehicle targets classification based on deep learning<br>Audio and alarm interface available, Water and dust resistant (IP66) and vandal proof (IK10)   | IRR 195,970,000 |
| <b>Fish Eye Series</b>                  |        |                                   |   |  |                 |
| 250713                                  | 200713 | <a href="#">DS-2CD2955FWD-I</a>   |  | 5 MP Network Fisheye Camera, Up to 5 megapixel high resolution, 2560 x 1920 @ 30fps, H.265, H.265+, H.264+, H.264, Support 14 display modes, FOV: horizontal FOV 180°, vertical FOV 180°, Dual video streams, DC12V & PoE (802.3af), Digital Noise Reduction, Support on-board storage, up to 128 GB, Up to 8m IR range  | IRR 126,380,000 |
| 250139                                  | 200139 | <a href="#">DS-2CD2955FWD-IS</a>  |  | 5 MP Network Fisheye Camera, Up to 5 megapixel high resolution, 2560 x 1920 @ 30fps, H.265, H.265+, H.264+, H.264, Support 14 display modes, FOV: horizontal FOV 180°, vertical FOV 180°, Dual video streams, DC12V & PoE (802.3af), Digital Noise Reduction, Support on-board storage, up to 128 GB, Up to 8m IR range, S: Audio/Alarm IO   | IRR 102,960,000 |
|   |        | <a href="#">DS-2CD6332FWD-IS</a>  |  | 1/3" Progressive Scan CMOS<br>Max. 2048 x 1536 @ 30fps<br>Up to 15 live view display modes, 120dB WDR<br>Up to 15m IR range, Built-in microphone and speaker<br>2 behavior analyses, 1 statistic   | IRR 178,300,000 |
| <b>people counting</b>                  |        |                                   |   |  |                 |
|   |        | IDS-2CD6412FWD/C                  |  | 1.3MP, 2.1mm 115degree Fixed Lens<br>1/3" CMOS, 30 fps at 1280 x 960, People Counting, WDR 120dB, 3D DNR<br>Electronic Day/Night, H.264, MJPEG, MPEG4, Alarm I/O<br>ONVIF, PSIA, CGI, ISAPI, Support real-time people entering/exiting data.<br>Support statistical traffic report based on configurable time interval (day/week/month/year).<br>Support Smart Codec, high bandwidth efficiency, low time delay and optimized bit rate.<br>Support on-board storage, Micro SD/SDHC/SDXC up to 128GB, card not included.<br>Defog, Electronic Image Stabilization, various BLC modes.<br>Support Smart Detection, including: Intrusion Detection, Audio Exception Detection, etc.<br>Main unit: 107.6mm x 78mm x 33.5mm<br>Lens: 48.7mm x 30.7mm x 31.5mm | IRR 224,880,000 |

| Cube Smart Series |        |                                    |   |  |                   |  |
|-------------------|--------|------------------------------------|---|--|-------------------|--|
| 250335            | 200335 | <a href="#">DS-2CD2420F-I(W)</a>   |    | Up to 2 megapixel (1920 x 1080 @ 30 fps) resolution - Standard video compression with high compression ratio, ROI (region of interest) encoding - Progressive scan CMOS - Built-in Micro SD/SDHC/SDXC card slot, up to 128 GB- IR range approx. 10 meters - Two-way audio - Built-in microphone and speaker -Support Wi-Fi, support WPS configuration with one touch - Support PIR(Active Infrared Detection) - IR cut filter with auto switch - Integrated mount for easy installation, Digital Wide Dynamic Range, Auto-electronic shutter | call              |  |
| 250351            | 200351 | <a href="#">DS-2CD2421G0-IW</a>    |    | 1/2.7" Progressive Scan CMOS - 1920 x 1080@30fps - IR: 10 m - PIR: 10m - H.265, H.265+ D-WDR - Built-in Micro SD/SDHC/SDXC slot, up to 128 GB - PoE - EXIR - Wi-Fi (Optional) - Color: 0.01 Lux @ (F1.2, AGC ON), 0.028 lux @ (F2.0, AGC ON), 0 lux with IR -W: Built-in Wi-Fi with WPS  | IRR 28,480,000    |  |
| 250140            | 200140 | <a href="#">DS-2CD2423G0-IW</a>    |    | 1/2.7" Progressive Scan CMOS - 1920 x 1080@30fps - IR: 10 m - PIR: 10m - H.265, H.265+ 120dB WDR - Built-in Micro SD/SDHC/SDXC slot, up to 128 GB - PoE - EXIR - Wi-Fi (Optional) - Color: 0.01 Lux @ (F1.2, AGC ON), 0.028 lux @ (F2.0, AGC ON), 0 lux with IR -W: Built-in Wi-Fi with WPS  | call              |  |
| 250141            | 200141 | <a href="#">DS-2CD2443G0-IW</a>    |    | 1/3" Progressive Scan CMOS - 2688 x 1520@30fps - IR: 10 m - PIR: 10m - 120dB WDR -Video Compression: H.265+/H.265/H.264+/H.264/MJPEG - Built-in Micro SD/SDHC/SDXC slot, up to 128 GB - Lens 2.8 mm, horizontal FOV: 98°, vertical FOV: 55° -W: Built-in Wi-Fi with WPS  | IRR 62,470,000    |  |
| Pin Hole Series   |        |                                    |   |  |                   |  |
| 250142            | 200142 | DS-2CD2D14WD                       |    | 1 MP Pin Hole Camera - 1/4" Progressive CMOS, Electronic Day/night, Color: 0.01lux/F1.2, B/W: 0.001lux/F1.2, 1280x720: 25fps(P)/30fps(N), 3.6mm/F1.2 lens, H.264/MJPEG, dual-stream, DC12V, 100dB WDR, 3D DNR, BLC, Support Mobile Monitoring via EZVIZ P2P  | call              |  |
| 2Q Smart Series   |        |                                    |   |  |                   |  |
| 250144            | 200144 | <a href="#">DS-2CD2Q10FD-IW</a>    |    | 1 MP CMOS PT Camera - 1/4" Progressive Scan CMOS - Up to 1.0 megapixel resolution - Support motorized Pan & Tilt - Digital WDR - 3D DNR - IR range approx. 10 meters - Support Wi-Fi, support WPS configuration with one touch (W) - Two-way audio - Built-in microphone and speaker - Support 128G on-board storage - 5V DC±10% - Pan & Tilt Control Pan: 0° - 355°, Tilt: -20° - 90  | IRR 31,300,000    |  |
| 2U Smart Series   |        |                                    |   |  |                   |  |
| 250146            | 200146 | <a href="#">DS-2CV2U21FD-IW</a>    |    | 2.0 MP Network Cube Camera - 1/2.8" Progressive CMOS, ICR, 0lux with IR, 1920x1080: 25fps(P)/30fps(N), 2.8mm lens, H.264/MJPEG, dual-stream, 3D DNR, 5m IR, support on-board storage up to 128GB, Hik-Connect cloud service, Built-in microphone and speaker, support two-way audio. Built-in Wi-Fi, 12VDC power supply - 32GB-T: Include 32GB sd card.  | IRR 21,790,000    |  |
| IP PTZ Camera     |        |                                    |   |  |                   |  |
| 250547            | 200547 | DS-2DE4A225IW-DE                   |    | 4-inch 2 MP 25X Powered by DarkFighter IR Network Speed Dome<br>High quality imaging with 2 MP resolution, Excellent low-light performance via powered-by, DarkFighter technology. Clear imaging against strong back lighting due to 120 dB WDR technology, Pan and tilt ability enables camera to monitor zones of interest, 25x optical zoom allows for closer viewing of subjects in expansive areas, Up to 50m IR range ensures safety at night (IP66)   | IRR 124,900,000   |  |
|                   |        | <a href="#">DS-2DE4A320IW-DE</a>   |    | 1/2.8" Progressive Scan CMOS • Up to 2048 x 1536 Resolution • 20x Optical Zoom, 16x Digital Zoom • WDR, 3D DNR, HLC, Smart IR • Basic Smart Suite Analytics • Up to 165 ft (50 m) IR Distance • H.265+ Video Compression Supported • IP66 Protection • 12 VDC and PoE+ (802.3at, class 4)  | IRR 274,170,000   |  |
| 250150            | 200150 | DS-2DE4Z25IW-DE-S6                 |  | 4-inch 2 MP 25X Powered by DarkFighter IR Network Speed Dome<br>1/2.8" progressive scan CMOS, High quality imaging with 2 MP resolution<br>Excellent low-light performance with powered-by-DarkFighter technology<br>25x optical zoom and 16x digital zoom provide close up views over expansive areas<br>WDR, HLC, BLC, 3D DNR, defog, regional exposure, regional focus<br>Expansive night view with up to 100 m IR distance<br>Support H.265+/H.265 video compression   |                   |  |
|                   |        | DS-2DE4Z25IW-DE-TS                 |  | 2MP 25x Network IR Speed Dome - 1/2.8" progressive scan CMOS up to 1920 x 1080@30fps resolution-Min. illumination: Color: 0.005 Lux @ (F1.6, AGC ON) B/W: 0.001 Lux @ (F1.6, AGC ON) 0 Lux with IR 25x optical zoom Focal Length 4.8 mm to 120 mm - 16x digital zoom - WDR, HLC, BLC, 3D DNR, Defog, EIS, Regional Exposure, Regional Focus - Up to 100 m IR distance - 12 VDC & PoE+ (802.3 at, class 4) Support H.265+/H.265 video compression - Excellent low-light performance with powered-by-DarkFighter technology                    | IRR 219,620,000   |  |
| 250310            | 200310 | <a href="#">DS-2DE4425IW-DE-T8</a> |  | 4MP 25x Network IR Speed Dome - 1/2.8" progressive scan CMOS up to 2560 x 1440@30fps resolution-Min. illumination: Color: 0.005 Lux @ (F1.6, AGC ON) B/W: 0.001 Lux @ (F1.6, AGC ON) 0 Lux with IR 25x optical zoom Focal Length 4.8 mm to 120 mm - 16x digital zoom - WDR, HLC, BLC, 3D DNR, Defog, EIS, Regional Exposure, Regional Focus - Up to 100 m IR distance - 12 VDC & PoE+ (802.3 at, class 4) Support H.265+/H.265 video compression - Excellent low-light performance with powered-by-DarkFighter technology                    | IRR 252,150,000   |  |
|                   |        | <a href="#">DS-2DF8236ISW-AELW</a> |  | Optical Defog<br>2MP (1920*1080) Full HD<br>36X Optical Zoom<br>Ultra-low illumination, 120db True WDR<br>Smart Tracking, Smart Detection<br>EIS (Electronic Image Stabilization)<br>500m IR distance<br>Optional wiper(-W)  | IRR 1,143,020,000 |  |
| 250152            | 200152 | <a href="#">DS-2DE5220IW-AE</a>    |  | 2.54cm(1/2.8") Progressive Scan CMOS<br>Up to 1920 x 1080 resolution<br>20x Optical Zoom, 16x Digital Zoom, Digital WDR<br>3D intelligent positioning function, Up to 150 m IR distance<br>Hi-PoE/24 VAC power supply, Support H.265 video compression   | IRR 338,660,000   |  |
| 250639            | 200639 | <a href="#">DS-2DE5432IW-AE-S6</a> |  | 1/2.8" Progressive Scan CMOS<br>High quality imaging with 4 MP resolution<br>Excellent low-light performance with powered-by-DarkFighter technology<br>32x optical zoom, 16x digital zoom<br>WDR, HLC, BLC, 3D DNR, Defog, Regional Exposure, Regional Focus, Rapid Focus<br>Up to 150 m IR distance<br>Accurate human and vehicle target classification, alarm, and linked tracking based on deep learning algorithm, Face capture: Up to 5 faces captured at the same time   | IRR 229,040,000   |  |
|                   |        | <a href="#">DS-2DF5276-AEL</a>     |  | 1/3" progressive Scan CMOS<br>30x / 20x optical zoom, 16x digital zoom<br>Smart tracking, eis, defog<br>True day/Night, D wdr, 3D DNR<br>3D Intelligent positioning, Connectivity Technology: Wireless   | IRR 447,450,000   |  |
|                   |        | <a href="#">DS-2DF5276-AE3</a>     |  | 1/3" Progressive Scan CMOS<br>30X optical zoom, 16X digital zoom, ONVIF<br>Smart Tracking, EIS, Defog, True Day/Night, D WDR, 3D DNR<br>3D intelligent positioning, Triple stream<br>24VAC / High-PoE power supply, Outdoor / Indoor   | IRR 562,530,000   |  |
|                   |        | DS-2DF6A236X-AEL                   |  | 6-inch 2 MP 36X DarkFighter Network Speed Dome<br>High quality imaging with 2 MP resolution<br>Excellent low-light performance via DarkFighter technology<br>36x optical zoom provides close up views over expansive areas<br>Intelligent functions based on deep learning<br>Water and dust resistant (IP67) and vandal proof (IK10).   | IRR 520,800,000   |  |

|                      |        |                                   |   |   |                 |
|----------------------|--------|-----------------------------------|---|---|-----------------|
|                      |        | DS-2CDE5432IW-AE                  |    | 3-in-1 IR 32X Powered by DarkFighter IR Network Speed Dome<br>1/2.8" Progressive Scan CMOS<br>High quality imaging with 4 MP resolution<br>Excellent low-light performance with powered-by-DarkFighter technology<br>32x optical zoom, 16x digital zoom<br>WDR, HLC, BLC, 3D DNR, Defog, Regional Exposure, Regional Focus, Rapid Focus<br>Up to 150 m IR distance  | IRR 229,040,000 |
|                      |        | DS-2SE4C225MWG-E                  |    | Captures a large area and great details at the same time<br>High quality imaging with 2 MP resolution<br>Excellent low-light performance with powered-by-DarkFighter technology and ColorVu technology<br>Secures an expansive area with 25x optical zoom and 16x digital zoom<br>Supports WDR, HLC, BLC, 3D DNR, defog, regional exposure, regional focus<br>Expansive night view with up to 100 m IR distance & 30 m white light<br>Supports 12V DC & PoE+<br>Focuses on human and vehicle targets classification based on deep learning  | IRR 288,340,000 |
|                      |        | DS-2SE4C425MWG-E (14F0)           |    | Captures a large area and great details at the same time<br>High quality imaging with 4 MP resolution<br>Excellent low-light performance with powered-by-DarkFighter technology and ColorVu technology<br>Secures an expansive area with 25x optical zoom and 16x digital zoom<br>Supports WDR, HLC, BLC, 3D DNR, defog, regional exposure, regional focus<br>Expansive night view with up to 100 m IR distance & 30 m white light<br>Supports 12V DC & PoE+<br>Focuses on human and vehicle targets classification based on deep learning  | IRR 329,000,000 |
|                      |        | DS-2DE7A432IW-AE(T5)              |    | 1/1.8" progressive scan CMOS<br>High quality imaging with 4 MP resolution<br>Excellent low-light performance with powered-by-DarkFighter technology<br>Audio visual alarm: The white flashing light and audible warning can be triggered by certain events<br>32x optical zoom and 16x digital zoom provide close up views over expansive areas<br>Expansive night view with up to 200 m IR distance<br>Focuses on human and vehicle targets classification based on deep learning<br>Face capture: Up to 5 faces captured at the same time | IRR 420,980,000 |
|                      |        | DS-2CDS220IW-AE                   |    | 2MP 20X Network IR PTZ Dome Camera<br>1920 x 1080, 1/2.8" Progressive Scan CMOS<br>20X Optical Zoom<br>DWDR, 3D intelligent positioning function<br>Support cloud P2P<br>Up to 150m IR distance<br>Hi-PoE / 24VAC power supply, Support BNC output  | IRR 231,170,000 |
| 250157               | 200157 | <a href="#">DS-2DE7232IW-AE</a>   |    | 2MP 32x Network IR Speed Dome, Up to 1920 x 1080@60fps resolution, Min. illumination: Color: 0.005 Lux @(F1.6, AGC ON), B/W: 0.001 Lux @(F1.6, AGC ON)<br>0 Lux with IR, 32x optical zoom, 16x digital zoom, WDR, HLC, BLC, 3D DNR, Defog, EIS, Regional Exposure, Regional Focus, Up to 150 m IR distance, 24 VAC & Hi-PoE, Support H.265+/H.265 video compression   | call            |
| <b>NVR-Monitor</b>   |        |                                   |   |   |                 |
| 250164               | 200164 | DS-7600NI-E1/A                    |   | Advertising files import and preview, The output resolution of LCD is up to 1080P, Third party network cameras supported, Up to 8-ch synchronous playback at 720P resolution, Up to 8 network cameras can be connected, Smart search and smart playback 1TB HDD WD1010UJCT pre-installed  | IRR 164,300,000 |
| <b>NVR 4 Channel</b> |        |                                   |   |   |                 |
| 250165               | 200165 | <a href="#">DS-7104NI-Q1/M</a>    |  | IP video input : 4-ch Up to 4 MP resolution - Decoding format : H.265+/H.265/ H.264+/H.264 - Incoming bandwidth : 40 Mbps - HDMI output : 1920 x 1080p/60Hz - Capacity : 1 SATA interface Up to 6TB capacity  | IRR 26,860,000  |
|                      |        | <a href="#">DS-7104NI-Q1</a>      |  | 4-ch Mini iU NVR<br>H.265+/H.265/H.264+/H.264 video compression<br>Up to 40 Mbps incoming bandwidth, and 60 Mbps outgoing bandwidth<br>Up to 4-ch network camera inputs<br>Up to 4-ch 1080p decoding capability<br>HDMI and VGA simultaneous output   | IRR 20,290,000  |
| 250166               | 200166 | <a href="#">DS-7104NI-Q1/4P/M</a> |  | IP video input : 4-ch / 4-ch POE Up to 4 MP resolution - Decoding format : H.265+/H.265/ H.264+/H.264 - Incoming bandwidth : 40 Mbps - HDMI output : 1920 x 1080p/60Hz - Capacity : 1 SATA interface Up to 6TB capacity   | call            |
|                      |        | <a href="#">DS-7604NI-Q1</a>      |  | IP video input : 4-ch Up to 8 MP resolution - Decoding format : H.265+/H.265/ H.264+/H.264 - Incoming bandwidth : 40 Mbps - HDMI output : 4K (3840 x 2160)/30Hz - Capacity : 1 SATA interface Up to 6TB capacity  | call            |
| 250169               | 200169 | <a href="#">DS-7604NI-Q1/4P</a>   |  | IP video input : 4-ch / 4-ch POE Up to 8 MP resolution - Decoding format : H.265+/H.265/ H.264+/H.264 - Incoming bandwidth : 40 Mbps - HDMI output : 4K (3840 x 2160)/30Hz - Capacity : 1 SATA interface Up to 6TB capacity   | call            |
| 250170               | 200170 | <a href="#">DS-7604NI-K1</a>      |  | IP video input : 4-ch Up to 8 MP resolution - Decoding format : H.265+/H.265/ H.264+/H.264 - Incoming bandwidth : 40 Mbps - HDMI output : 4K (3840 x 2160)/30Hz - Capacity : 1 SATA interface Up to 6TB capacity  | IRR 61,560,000  |
| 250171               | 200171 | <a href="#">DS-7604NI-K1/4P</a>   |  | IP video input : 4-ch / 4-ch POE Up to 8 MP resolution - Decoding format : H.265+/H.265/ H.264+/H.264 - Incoming bandwidth : 40 Mbps - HDMI output : 4K (3840 x 2160)/30Hz - Capacity : 1 SATA interface Up to 6TB capacity   | IRR 82,740,000  |
| <b>NVR 8 Channel</b> |        |                                   |   |   |                 |
| 250101               | 200101 | <a href="#">DS-7108NI-Q1/M</a>    |  | IP video input : 8-ch Up to 4 MP resolution - Decoding format : H.265+/H.265/ H.264+/H.264 - Incoming bandwidth : 60 Mbps - HDMI output : 1920 x 1080p/60Hz - Capacity : 1 SATA interface Up to 6TB capacity  | IRR 49,380,000  |
| 250172               | 200172 | <a href="#">DS-7108NI-Q1/8P/M</a> |  | IP video input : 8-ch / 8-ch POE Up to 4 MP resolution - Decoding format : H.265+/H.265/ H.264+/H.264 - Incoming bandwidth : 60 Mbps - HDMI output : 1920 x 1080p/60Hz - Capacity : 1 SATA interface Up to 6TB capacity   | call            |
| 250340               | 200340 | <a href="#">DS-7608NI-Q2/8P</a>   |  | IP video input : 8-ch / 8-ch POE Up to 8 MP resolution - Decoding format : H.265+/H.265/ H.264+/H.264 - Incoming bandwidth : 80 Mbps - HDMI output : 4K (3840 x 2160)/30Hz - Capacity : 2 SATA interface Up to 6TB capacity for each disk   | call            |



|  |        |                                   |   |  |                 |
|--|--------|-----------------------------------|---|--|-----------------|
| 250175                                       | 200175 | <a href="#">DS-7608NI-Q1</a>      |    | Up to 8-ch IP camera inputs<br>H.265+/H.265/H.264+/H.264 video formats<br>Up to 1-ch@8 MP/3-ch@4 MP/6-ch@1080p decoding capacity<br>Up to 80 Mbps incoming bandwidth   | IRR 35,500,000  |
| 250177                                       | 200177 | <a href="#">DS-7608NI-Q2</a>      |    | Up to 8-ch IP camera inputs<br>H.265+/H.265/H.264+/H.264 video formats<br>Up to 1-ch@8 MP/3-ch@4 MP/6-ch@1080p decoding capacity<br>Up to 80 Mbps incoming bandwidth   | IRR 61,800,000  |
| 250015                                       | 200015 | <a href="#">DS-7608NI-K1</a>      |    | IP video input : 8-ch Up to 8 MP resolution - Decoding format : H.265+/H.265/ H.264+/H.264 - Incoming bandwidth : 80 Mbps - HDMI output : 4K (3840 × 2160)/30Hz - Capacity : 1 SATA interface Up to 6TB capacity   | IRR 68,340,000  |
| 250689                                       | 200689 | <a href="#">DS-7608NI-K1/8P</a>   |    | 8-ch 1U 8 PoE 4K NVR<br>Up to 8-ch IP camera inputs<br>H.265+/H.265/H.264+/H.264 video formats<br>Up to 1-ch@8 MP/3-ch@4 MP/6-ch@1080p decoding capacity<br>Up to 80 Mbps incoming bandwidth   | IRR 126,190,000 |
| 250541                                       | 200541 | <a href="#">DS-7608NI-K2</a>      |    | 8-ch 1U 4K NVR<br>Up to 8-ch IP camera inputs<br>H.265+/H.265/H.264+/H.264 video formats<br>Up to 2-ch@8 MP or 4-ch@4 MP or 8-ch@1080p decoding capacity<br>1 HDMI and 1 VGA interfaces, both interfaces support independent video output<br>2 SATA interfaces for HDD connection (up to 10 TB capacity per HDD)<br>Up to 80 Mbps incoming bandwidth   | IRR 71,200,000  |
| 250178                                       | 200178 | <a href="#">DS-7608NI-K2/8P</a>   |    | IP video input : 8-ch / 8-ch POE Up to 8 MP resolution - Decoding format : H.265+/H.265/ H.264+/H.264 - Incoming bandwidth : 80 Mbps - HDMI output : 4K (3840 × 2160)/30Hz - Capacity : 2 SATA interface Up to 6TB capacity for each disk  | call            |
| <b>NVR 16 Channel</b>                        |        |                                   |   |  |                 |
| 250182                                       | 200182 | <a href="#">DS-7616NI-Q1</a>      |    | IP video input : 16-ch Up to 8 MP resolution - Decoding format : H.265+/H.265/ H.264+/H.264 - Incoming bandwidth : 160 Mbps - HDMI output : 4K (3840 × 2160)/30Hz - Capacity : 1 SATA interface Up to 6TB capacity   | IRR 48,200,000  |
| 250183                                       | 200183 | <a href="#">DS-7616NI-Q2</a>      |    | IP video input : 16-ch Up to 8 MP resolution - Decoding format : H.265+/H.265/ H.264+/H.264 - Incoming bandwidth : 160 Mbps - HDMI output : 4K (3840 × 2160)/30Hz - Capacity : 2 SATA interface Up to 6TB capacity for each disk   | IRR 89,810,000  |
| 250184                                       | 200184 | <a href="#">DS-7616NI-Q2/16P</a>  |    | IP video input : 16-ch / 16-ch POE Up to 8 MP resolution - Decoding format : H.265+/H.265/ H.264+/H.264 - Incoming bandwidth : 160 Mbps - HDMI output : 4K (3840 × 2160)/30Hz - Capacity : 2 SATA interface Up to 6TB capacity for each disk   | IRR 107,470,000 |
| 250464                                       | 200464 | <a href="#">DS-7616NI-K1</a>      |    | Up to 16-ch IP camera inputs<br>H.265+/H.265/H.264+/H.264 video formats<br>Up to 1-ch @ 8MP or 5-ch @ 1080P decoding capacity<br>Up to 160 Mbps incoming bandwidth   | IRR 74,000,000  |
| 250185                                       | 200185 | <a href="#">DS-7616NI-K2</a>      |   | IP video input : 16-ch Up to 8 MP resolution - Decoding format : H.265+/H.265/ H.264+/H.264 - Incoming bandwidth : 160 Mbps - HDMI output : 4K (3840 × 2160)/30Hz - Capacity : 2 SATA interface Up to 6TB capacity for each disk   | IRR 82,970,000  |
| 250186                                       | 200186 | <a href="#">DS-7616NI-K2/16P</a>  |  | IP video input : 16-ch / 16-ch POE Up to 8 MP resolution - Decoding format : H.265+/H.265/ H.264+/H.264 - Incoming bandwidth : 160 Mbps - HDMI output : 4K (3840 × 2160)/30Hz - Capacity : 2 SATA interface Up to 6TB capacity for each disk   | IRR 187,860,000 |
| 250189                                       | 200189 | <a href="#">DS-7716NI-Q4</a>      |  | IP video input : 16-ch Up to 8 MP resolution - Decoding format : H.265+/H.265/ H.264+/H.264 - Incoming bandwidth : 160 Mbps - HDMI output : 4K (3840 × 2160)/30Hz - Capacity : 4 SATA interface Up to 6TB capacity for each disk   | IRR 178,100,000 |
| 250337                                       | 200337 | <a href="#">DS-7716NI-Q4/16P</a>  |  | IP video input : 16-ch / 16-ch POE Up to 8 MP resolution - Decoding format : H.265+/H.265/ H.264+/H.264 - Incoming bandwidth : 160 Mbps - HDMI output : 4K (3840 × 2160)/30Hz - Capacity : 4 SATA interface Up to 6TB capacity for each disk   | IRR 255,140,000 |
| 250190                                       | 200190 | <a href="#">DS-7716NI-K4</a>      |  | IP video input : 16-ch Up to 8 MP resolution - Decoding format : H.265+/H.265/ H.264+/H.264 - Incoming bandwidth : 160 Mbps - HDMI output : 4K (3840 × 2160)/30Hz - Capacity : 4 SATA interface Up to 6TB capacity for each disk   | IRR 189,980,000 |
| 250191                                       | 200191 | <a href="#">DS-7716NI-K4/16P</a>  |  | IP video input : 16-ch / 16-ch POE Up to 8 MP resolution - Decoding format : H.265+/H.265/ H.264+/H.264 - Incoming bandwidth : 160 Mbps - HDMI output : 4K (3840 × 2160)/30Hz - Capacity : 4 SATA interface Up to 6TB capacity for each disk   | call            |
| <b>Network Video Recorders- Ultra Series</b> |        |                                   |   |  |                 |
|  |        | <a href="#">DS-8616NI-K8</a>      |  | 16-ch 2U 4K NVR, Up to 16 channel IP cameras can be connected. Supports decoding H.265+/H.265/H.264+/H.264/MPEG4 video formats<br>Up to 4K high-definition live view, storage and playback, Up to 160 Mbps high incoming bandwidth ensures IP cameras can be connected, 2 HDMI (different source) and 2 VGA (different source) interfaces, 8 HDD can be used for continuous video recording. Supports some specialist cameras, including people counting camera/ANPR (automatic number plate recognition) camera | IRR 147,000,000 |
| <b>NVR 32 Channel</b>                        |        |                                   |   |  |                 |
|  |        | <a href="#">DS-7732NI-Q4</a>      |  | IP video input : 32-ch Up to 8 MP resolution - Decoding format : H.265+/H.265/ H.264+/H.264 - Incoming bandwidth : 200 Mbps - HDMI output : 1920 × 1080/60Hz - Capacity : 4 SATA interface Up to 6TB capacity for each disk  | IRR 119,500,000 |
|  |        | <a href="#">IDS-7732NXI-I4/8S</a> |  | 32-ch 1.5U 4K DeepMind NVR, H.265+/H.265/H.264+/H.264 video formats<br>Intelligent analytics based on deep learning algorithm<br>Up to 16-ch perimeter protection<br>Up to 8-ch facial recognition for video stream, or up to 16-ch facial recognition for face picture<br>Up to 8-ch video structuralization, Up to 32-ch IP cameras can be connected<br>Up to 16-ch 1080p decoding capability  | IRR 719,160,000 |
| 250336                                       | 200336 | <a href="#">DS-7732NI-Q4/16P</a>  |  | IP video input : 32-ch / 16-ch POE Up to 8 MP resolution - Decoding format : H.265+/H.265/ H.264+/H.264 - Incoming bandwidth : 200 Mbps - HDMI output : 1920 × 1080/60Hz - Capacity : 4 SATA interface Up to 6TB capacity for each disk  | IRR 170,000,000 |

|        |        |                                  |  |   |                   |
|--------|--------|----------------------------------|--|---|-------------------|
| 250014 | 200014 | <a href="#">DS-7732NKH4</a>      |   | IP video input : 32-ch Up to 8 MP resolution - Decoding format : H.265+/H.265/ H.264+/H.264 - Incoming bandwidth : 256 Mbps - HDMI output : 4K (3840 x 2160)/30Hz - Capacity : 4 SATA interface Up to 6TB capacity for each disk  | IRR 210,450,000   |
| 250194 | 200194 | <a href="#">DS-7732NKH4/16P</a>  |   | IP video input : 32-ch - 16-ch POE Up to 8 MP resolution - Decoding format : H.265+/H.265/ H.264+/H.264 - Incoming bandwidth : 256 Mbps - HDMI output : 4K (3840 x 2160)/30Hz - Capacity : 4 SATA interface Up to 6TB capacity for each disk  | IRR 334,310,000   |
|        |        | <a href="#">DS-7732NXIH4</a>     |   | Up to 32-ch IP camera inputs<br>H.265+/H.265/H.264+/H.264 video formats<br>Up to 2-ch@12 MP or 3-ch@8 MP or 6-ch@4 MP or 12-ch@1080p decoding capacity<br>Up to 256 Mbps incoming bandwidth<br>Adopt Hikvision AcuSense technology to minimize manual effort and security costs   | IRR 231,100,000   |
|        |        | <a href="#">DS-8632NI-K8</a>     |   | Up to 32 channel IP cameras can be connected<br>Supports decoding H.265+/H.265/H.264+/H.264/MPEG4 video formats<br>Up to 4K high-definition live view, storage and playback<br>Up to 160 Mbps high incoming bandwidth ensures IP cameras can be connected<br>2 HDMI (different source) and 2 VGA (different source) interfaces<br>8 HDD can be used for continuous video recording<br>Supports some specialist cameras, including people counting camera/ANPR (automatic number plate recognition) camera   | IRR 218,820,000   |
|        |        | <a href="#">DS-8664NI-H8</a>     |   | Up to 64 channel IP cameras can be connected<br>Up to 12 MP high-definition live view, storage and playback<br>Up to 320 Mbps (or 200 Mbps when RAID is enabled) high incoming bandwidth ensures IP cameras can be connected<br>2 HDMI (different source) and 2 VGA (different source) interfaces<br>8 HDD can be used for continuous video recording<br>Supports some specialist cameras, including people counting camera/ANPR (automatic number plate recognition) camera/fisheye camera<br>Advanced streaming technology enables smooth live view in poor network conditions  | IRR 500,000,000   |
|        |        | <a href="#">DS-9632NI-H8</a>     |   | 32-ch 2U 4K NVR, Up to 32 channel IP cameras can be connected, Up to 12 MP high-definition live view, storage and playback<br>Up to 320 Mbps (or 200 Mbps when RAID is enabled) high incoming bandwidth ensures IP cameras can be connected, 2 HDMI (different source) and 2 VGA (different source) interfaces<br>8 HDD can be used for continuous video recording<br>Supports some specialist cameras, including people counting camera/ANPR (automatic number plate recognition) camera/fisheye camera<br>Advanced streaming technology enables smooth live view in poor network conditions<br>Supports RAID 0, 1, 5, 6, 10 and N+1 hot spare for even more reliable data storage, effectively avoids data loss risks   | IRR 626,320,000   |
|        |        | <a href="#">DS-9632NI-H16</a>    |   | 32-ch 3U 4K NVR<br>Up to 32 channel IP cameras can be connected<br>Up to 320 Mbps (or 200 Mbps when RAID is enabled) high incoming bandwidth ensures IP cameras can be connected<br>2 HDMI (different source) and 2 VGA (different source) interfaces<br>16 HDD can be used for continuous video recording<br>Supports some specialist cameras, including people counting camera/ANPR (automatic number plate recognition) camera/fisheye camera<br>Advanced streaming technology enables smooth live view in poor network conditions<br>Supports RAID 0, 1, 5, 6, 10 and N+1 hot spare for even more reliable data storage, effectively avoids data loss risks   | IRR 715,640,000   |
|        |        | <a href="#">IDS-9632NXIH8/4F</a> |   | <ul style="list-style-type: none"> <li>Facial Recognition and Comparison, * Face Picture Library, 16 Libraries, 100,000 Pictures</li> <li>Face Capture Analysis, Classification and Comparison and Alarm, * 4-ch Face Pictures Comparison Alarm, Alarm Linkage Actions: Recording, Audio Warning, Notify Surveillance Center, Send E-mail, * Face Picture Search, False Alarm Filtering</li> <li>Up to 32 Channel IP Video Input * Incoming Bandwidth 256 Mbps, Outgoing Bandwidth 200 Mbps</li> <li>Recording Resolution up to 12 MP, * Synchronous 2-ch HDMI, 2-ch VGA and HDMI 1.4 K (3840 x 2160) Resolution</li> <li>H.265+/H.265/H.264+/H.264/MPEG4, Self-Adaptive Video Formatting</li> <li>HDD Hot Swap with RAID0, RAID1, RAID5, RAID6, and RAID10 Storage Configurations * 1 eSATA interface</li> </ul> | IRR 3,213,890,000 |
| 250341 | 200341 | <a href="#">DS-9664NI-H8</a>     |   | 64-ch 2U 4K NVR<br>Up to 64 channel IP cameras can be connected<br>Up to 12 MP high-definition live view, storage and playback<br>Up to 320 Mbps (or 200 Mbps when RAID is enabled) high incoming bandwidth ensures IP cameras can be connected<br>2 HDMI (different source) and 2 VGA (different source) interfaces<br>8 HDD can be used for continuous video recording<br>Supports some specialist cameras, including people counting camera/ANPR (automatic number plate recognition) camera/fisheye camera<br>Advanced streaming technology enables smooth live view in poor network conditions<br>Supports RAID 0, 1, 5, 6, 10 and N+1 hot spare for even more reliable data storage, effectively avoids data loss risks   | IRR 682,530,000   |
| 250341 | 200341 | <a href="#">DS-9664NXIH8/S</a>   |   | 64-ch 2U 4K NVR<br>Up to 64 channel IP cameras can be connected<br>Up to 12 MP high-definition live view, storage and playback<br>Up to 320 Mbps (or 200 Mbps when RAID is enabled) high incoming bandwidth ensures IP cameras can be connected<br>2 HDMI (different source) and 2 VGA (different source) interfaces<br>8 HDD can be used for continuous video recording<br>Supports some specialist cameras, including people counting camera/ANPR (automatic number plate recognition) camera/fisheye camera<br>Advanced streaming technology enables smooth live view in poor network conditions<br>Supports RAID 0, 1, 5, 6, 10 and N+1 hot spare for even more reliable data storage, effectively avoids data loss risks   | IRR 968,630,000   |
|        |        | <a href="#">DS-9664NI-H16</a>    |  | 64-ch 3U 4K NVR<br>Up to 64 channel IP cameras can be connected<br>Up to 320 Mbps (or 200 Mbps when RAID is enabled) high incoming bandwidth ensures IP cameras can be connected<br>2 HDMI (different source) and 2 VGA (different source) interfaces<br>16 HDD can be used for continuous video recording<br>Supports some specialist cameras, including people counting camera/ANPR (automatic number plate recognition) camera/fisheye camera<br>Advanced streaming technology enables smooth live view in poor network conditions<br>Supports RAID 0, 1, 5, 6, 10 and N+1 hot spare for even more reliable data storage, effectively avoids data loss risks   | IRR 1,029,160,000 |