

# PRICE LIST

# Tiandy



















01111111111  
 WWW.RADIS-CO.COM  
 RADIS.NET

## Network Camera - NVR

SKU(M)	Items	Description	User Price
<b>spark</b>			
1	<b>TC-C32QN</b> Spec: I3/E/Y/2.8mm/V5.0	 <p>                         KEY FEATURES                          -Metal+Plastic Housing                          -Up to 1920x1080@25fps                          -S+265/H.265/H.264                          -Min. illumination Color: 0.02Lux@F2.0                          -Smart IR, IR Range: 30m -Built-in Mic                          -Operating Conditions -30°-60°, 0-95% RH                          -POE, IP67                     </p>	IRR 20,000,000
2	<b>TC-C32XN</b> Spec: I3/E/Y/2.8mm/V5.0	 <p>                         -Up to 1920x1080@30fps                          -S+265/H.265/H.264                          -Min. illumination Color: 0.02Lux@F2.0                          -Smart IR, IR Range: 30m                          -Operating Conditions -30°-60°, 0-95% RH-POE                     </p>	IRR 20,000,000
3	<b>TC-C34QN</b> Spec: I3/E/Y/4mm/V5.0	 <p>                         KEY FEATURES                          -Metal+Plastic Housing                          -Upto2560x1440@20fps                          -S+265/H.265/H.264                          -Min. illumination Color: 0.02Lux@F2.0                          -Smart IR, IR Range: 30m -Built-in Mic                          -Operating Conditions -30°-60°, 0-95% RH                          -POE, IP67                     </p>	IRR 29,900,000
4	<b>TC-C34XN</b> Spec: I3/E/Y/2.8mm/V5.0	 <p>                         -Upto2560x1440@20fps                          -S+265/H.265/H.264                          -Min. illumination Color: 0.02Lux@F2.0                          -Smart IR, IR Range: 30m                          -Operating Conditions -30°-60°, 0-95% RH-POE                     </p>	IRR 28,600,000
5	<b>TC-R3105 SPEC: I/B/L/S/EU</b>	 <p>5-ch, 50Mbps/40Mbps, recording resolution up to 6MP, decoding ability 116MP, 3*1080p, 4*720p, video output: 1 HDMI &amp; 1VGA simultaneous output, USB interface: 2xUSB 2.0</p>	IRR 34,270,000
6	<b>TC-R3105 SPEC: I/B/P/L/S</b>	 <p>                         5CH 1HDD 1U NVR, 5 IP camera input + 2 CH expansion = 7CH                          S+265/H.265/H.264 video formats                          Max 50/40 Mbps incoming/outgoing bandwidth, Up to 6M Resolution Recording                          Synchronous Decode: 1x8MP, 3x1080P, VCA detection alarm is supported                          HDMI and VGA simultaneous output, HDMI Video output at up to 1080P (1920 x 1080)                          1 SATA interface, up to 10TB for 1 HDD                          1CH Audio output, 2 USB Ports                          1*10/100 Mbps Network Card, P2P support                     </p>	IRR 52,910,000
7	<b>TC-R3110 SPEC: I/B/L/S/EU</b>	 <p>                         • S+265/H.265/H.264 video formats                          • Connectable to the third-party network cameras                          • Support live view, storage, and playback of the connected camera at up to 6MP resolution                          • 1xHDMI and 1xVGA simultaneous outputs                          • HDMI Video output at up to 4K resolution, HD Storage                          • 1 SATA interface, up to 8TB for 1 HDD                          • S+265 compression effectively reduces the storage space and costs by up to 75%                          • 1xRJ45 self-adaptive 10/100 Mbps network interface/Various Applications                     </p>	IRR 39,100,000
8	<b>TC-R3110 SPEC: I/B/P8/L/S</b>	 <p>                         • HD Input                          • Plug and play                          • S+265/H.265/H.264 video formats                          • Connectable to the third-party network cameras                          • Up to 10-channel input                          • 8 PoE ports Supports live view, storage, and playback of the connected camera at up to 8MP resolution/HD Output                          • 1xHDMI and 1xVGA simultaneous output                          • HDMI Video output at up to 4K (3840 x 2160) resolution                          HD Storage- 1 SATA interface, up to 10TB for 1 HDD                          • Support 250m long-distance transmission                     </p>	IRR 63,745,000
9	<b>TC-C32KN I3/Y/WIFI/2.8MM</b>	 <p>                         -Metal+Plastic Housing                          -Up to 1920x1080@30fps                          -S+265/H.265/H.264                          -Min. illumination Color: 0.02Lux@F2.0                          -Smart IR, IR Range: 30m                          -Operating Conditions -35°C-65°C, 0-95% RH                          -Built-in Mic, SD Card Slot, Reset Button                          -Support Wi-Fi                          -IP67, IK10                     </p>	IRR 46,095,000
10	<b>TC-C32WN</b> I5/Y/WIFI/4MM/V4.0	 <p>                         -Metal+Plastic Housing                          -Up to 1920x1080@30fps                          -S+265/H.265/H.264                          -Min. illumination Color: 0.02Lux@F2.0                          -Smart IR, IR Range: 50m                          -Operating Conditions -35°C-65°C, 0-95% RH                          -Built-in Mic, SD Card Slot, Reset Button                          -Support Wi-Fi                          -IP67                     </p>	IRR 46,095,000

11	TC-H334S 15W/C/WIFI/4MM/4.1		<ul style="list-style-type: none"> <li>-Metal+Plastic Housing</li> <li>-Up to 2304x1296@25fps</li> <li>-S+265/H.265/H.264</li> <li>-Min. illumination Color: 0.02Lux@F1.6</li> <li>-Smart IR, IR Range: 50m</li> <li>-White Light : 20-30m</li> <li>-Operating Conditions -30°C-60°C, 0-95% RH</li> <li>-Built-in Mic, SD Card Slot, Reset Button</li> <li>-Support Wi-Fi</li> </ul>	IRR 65,550,000
<b>super lite series</b>				
12	TC-C32GN Spec:15/E/Y/C/2.8mm/V4.2		<ul style="list-style-type: none"> <li>1920x1080@30fps, Metal+Plastic</li> <li>1/2.8", 0.002Lux, WDR 120dB, 50m IR</li> <li>FOV: 99.7°, S+265/H.265/H.264, IP67</li> <li>Mic-in, No Power Cable, No Reset Button, 512GB SD-Card</li> </ul>	IRR 25,300,000
13	TC-C32HN Spec:13/E/Y/C/2.8mm/V4.2		<ul style="list-style-type: none"> <li>Metal+Plastic Housing</li> <li>Up to 1920x1080@30fps</li> <li>S+265/H.265/H.264</li> <li>Min. illumination Color: 0.02Lux@F2.0</li> <li>Smart IR, IR Range: 30m-Built-in Mic -Support tripwire and perimeter</li> <li>Operating Conditions -30°C-60°C, 0-95% RH</li> <li>-POE, IP66</li> </ul>	IRR 25,300,000
14	TC-C32GN Spec:15/E/Y/C/2.8mm/V4.1		<ul style="list-style-type: none"> <li>1920x1080@30fps, Metal+Plastic</li> <li>1/2.8", 0.002Lux, WDR 120dB, 50m IR</li> <li>FOV: 99.7°, S+265/H.265/H.264, IP67</li> <li>Mic-in, No Power Cable, No Reset Button, 512GB SD-Card</li> </ul>	IRR 28,762,800
15	TC-C32HN Spec: 13/E/Y/C/2.8mm/V4.1		1/2.8" CMOS, F2.0, Fixed Iris, Digital WDR, 30m IR, 0.02Lux, 1920x1080@30fps, Built-in Mic, IP67, PoE, Metal+Plastic housing, No Power Cable	IRR 28,762,800
16	TC-C32GN 15/E/Y/C/SD/2.8mm/V4.1		<ul style="list-style-type: none"> <li>2MP Fixed IR Bullet Camera</li> <li>1920x1080@30fps, Metal+Plastic, 1/2.8", 0.002Lux, Digital WDR, 50m IR</li> <li>FOV: 99.7°, S+265/H.265/H.264, IP67</li> <li>Mic-in, No Power Cable, No Reset Button,</li> </ul>	IRR 31,240,000
17	TC-C34GN Spec:15/E/Y/C/2.8mm/V4.2		<ul style="list-style-type: none"> <li>2560x1440@25fps, Metal+Plastic, 1/2.7", 0.002Lux, Digital WDR, 50m IR</li> <li>FOV: 103.4°, S+265/H.265/H.264, IP67, Mic-in, No Power Cable, No Reset Button, No SD-Card</li> </ul>	IRR 36,800,000
18	TC-C34HN Spec:13/E/Y/C/2.8mm/V4.2		4MP Fixed IR Turret Camera 2560x1440@25fps, Metal+Plastic 1/2.7", 0.002Lux, Digital WDR, 30m IR FOV: 99.7°, S+265/H.265/H.264, IP66 Mic-in, No Power Cable, No Reset Button, No SD-Card	IRR 35,200,000
19	TC-C34GS Spec: 15/E/Y/C/2.8MM/V4.0		<ul style="list-style-type: none"> <li>4MP Fixed Starlight IR Bullet Camera</li> <li>2560x1440@25fps, Metal+Plastic</li> <li>1/2.7", 0.002Lux, Digital WDR, 50m IR, FOV: 103.4°, S+265/H.265/H.264, IP67</li> <li>Mic-in, No Power Cable, No Reset Button, 512GB SD-Card</li> </ul>	IRR 43,585,000
20	TC-C34GS Spec:15/E/Y/C/SD/2.8mm/V4.0		<ul style="list-style-type: none"> <li>4MP Fixed Starlight IR Bullet Camera</li> <li>Metal+Plastic Housing</li> <li>Upto 2688x1520@25fps, S+265/H.265/H.264</li> <li>Built-in Mic, POE, DC 12V, Smart IR, IR Range: 50m</li> <li>Support tripwire and perimeter, Support SD Card upto 512GB</li> <li>Min. illumination Color: 0.02Lux@F2.0</li> <li>Operating Conditions: -30°-60°, 0-95% RH, IP67</li> </ul>	IRR 45,500,000
21	TC-C34HS Spec 13/E/Y/C/2.8mm/V4.0		2560x1440@25fps, Metal+Plastic 1/2.7", 0.002Lux, WDR 120dB, 30m IR FOV: 103.4°, S+265/H.265/H.264, IP66 Mic-in, No Reset Button, No SD-Card	IRR 41,690,000
22	TC-C34HS Spec 13/E/Y/C/SD/2.8mm/V4.0		<ul style="list-style-type: none"> <li>4MP Fixed Starlight IR Turret Camera</li> <li>2560x1440@25fps, Metal+Plastic, 1/2.7", 0.002Lux, Digital WDR, 30m IR</li> <li>FOV: 99.7°, S+265/H.265/H.264, IP66</li> <li>Mic-in, No Power Cable, No Reset Button</li> <li>512GB SD-Card</li> </ul>	IRR 43,230,000
<b>lite series</b>				
23	TC-C35XS 13/E/Y/2.8MM/V4.0		<ul style="list-style-type: none"> <li>KEY FEATURES</li> <li>-Default: Metal+Plastic, M: Metal Housing</li> <li>-Up to 2592x1944@20fps</li> <li>-S+265/H.265/H.264</li> <li>-Min. illumination Color: 0.002Lux@F1.6</li> <li>-120dB WDR</li> <li>-Smart IR, IR Range: 30m</li> <li>-Support tripwire and perimeter</li> <li>-Built-in Mic, SD Card Slot, Reset Button</li> <li>-Operating Conditions -40°C-60°C, 0-95% RH</li> <li>-POE, IP67</li> </ul>	IRR 59,500,000
24	TC-C34KS Spec:13/E/Y/2.8mm/V4.0		<ul style="list-style-type: none"> <li>-Metal+Plastic Housing -Up to 2560x1440@25fps</li> <li>-S+265/H.265/H.264 -Min. illumination Color: 0.002Lux@F1.6</li> <li>-120dB WDR</li> <li>-Smart IR, IR Range: 30m</li> <li>-Support tripwire and perimeter</li> <li>-Built-in Mic, SD Card Slot, Reset Button</li> <li>-Operating Conditions -40°C-60°C, 0-95% RH</li> <li>-POE, IP67, IK10</li> </ul>	IRR 72,450,000
25	TC-C35KS Spec:13/E/Y/C/H/2.8mm/V4.0		<ul style="list-style-type: none"> <li>- Full Metal Housing</li> <li>- Up to 2592x1944@30fps, 1920x1080@60fps; S+265/H.265/H.264/M-JPEG</li> <li>- Min. illumination Color: 0.002Lux@F1.6</li> <li>Smart IR, IR Range: 30m - Support Video Analytics</li> <li>- Support Human/Vehicle Classification</li> <li>- Support Face Capture Mode</li> <li>- Built-in Mic, audio I/O 1/1, alarm I/O 1/1 - Plugin Free</li> <li>- Operating Conditions -40°C-65°C, 0-95% RH</li> <li>POE, IP67, IK10</li> </ul>	IRR 72,500,000

26	TC-C35WS I5/E/Y/C/H/2.8/V4.0		<ul style="list-style-type: none"> <li>-Up to 2592x1944@30fps, 1920x1080@60fps</li> <li>-S+265/H.265/H.264/H.264H-JPEG</li> <li>-Min. illumination Color: 0.002Lux@F1.6</li> <li>-Smart IR, IR Range: 50m</li> <li>-Support Video Analytics</li> <li>-Support Human/Vehicle Classification</li> <li>-Support Face Capture Mode</li> <li>-Built-in Mic, audio I/O 1/1, alarm I/O 1/1</li> <li>-PoE, Edge</li> </ul>	IRR 67,000,000
27	TC-C35WS Spec:I5/E/Y/M/4mm/V4.0		<ul style="list-style-type: none"> <li>.5MPPixedStarlightIRBulletCamera .Metalhousing</li> <li>.Up toMax Resolution</li> <li>.IRRange50m.S+in-flic:IP67</li> <li>SupportSDCardupto512GB</li> <li>.POE802.3af.MAX7W</li> <li>SupportSmartsurveillance</li> <li>S+265/H.265/H.264B/H.264M/H.264H</li> <li>.OperatingConditions-40°-65°,0-95% RH</li> <li>.Color:0.002Lux@(F1.6,AGCCON),B/W:0LuxwithIR</li> </ul>	IRR 72,500,000
28	TC-C38KS SPEC: I3/E/Y/2.8mm/V4.0		<ul style="list-style-type: none"> <li>8MP Fixed Starlight IR Dome Camera</li> <li>-Metal+Plastic Housing -Up to 3840x2160@20fps</li> <li>-S+265/H.265/H.264 -Min. illumination Color: 0.003Lux@F1.6</li> <li>-120dB WDR</li> <li>Smart IR, IR Range: 30m</li> <li>-Support tripwire and perimeter</li> <li>-Built-in Mic, SD Card Slot, Reset Button</li> <li>-Operating Conditions -35°-65°, 0-95% RH</li> <li>-POE, IP67, IK10</li> </ul>	IRR 97,000,000
29	TC-C38WS SPEC: I5/E/Y/M/2.8mm/V4.0		<ul style="list-style-type: none"> <li>8MP Fixed Starlight IR Bullet Camera</li> <li>Full Metal Housing</li> <li>-Up to 3840x2160@20fps</li> <li>-S+265/H.265/H.264</li> <li>-Min. illumination Color: 0.003Lux@F1.6</li> <li>-120dB WDR Smart IR, IR Range: 50m</li> <li>-Support tripwire and perimeter</li> <li>-Built-in Mic, SD Card Slot, Reset Button</li> <li>-Operating Conditions -40°C-65°C, 0-95% RH</li> <li>-POE, IP67</li> </ul>	IRR 108,000,000
30	TC-C38WS SPEC: I5/E/Y/M/4mm/V4.0		<ul style="list-style-type: none"> <li>8MP Fixed Starlight IR Bullet Camera</li> <li>Full Metal Housing</li> <li>-Up to 3840x2160@20fps</li> <li>-S+265/H.265/H.264</li> <li>-Min. illumination Color: 0.003Lux@F1.6</li> <li>-120dB WDR Smart IR, IR Range: 50m</li> <li>-Support tripwire and perimeter</li> <li>-Built-in Mic, SD Card Slot, Reset Button</li> <li>-Operating Conditions -40°C-65°C, 0-95% RH</li> <li>-POE, IP67</li> </ul>	IRR 108,000,000
31	TC-C38XS Spec: I3/E/Y/M/2.8mm/V4.0		<ul style="list-style-type: none"> <li>8MP Fixed Starlight IR Turret Camera</li> <li>-Full Metal Housing-Up to 3840x2160@20fps</li> <li>-S+265/H.265/H.264</li> <li>-Min. illumination Color: 0.003Lux@F1.6 -120dB WDR</li> <li>Smart IR, IR Range: 30m</li> <li>-Support tripwire and perimeter</li> <li>-Built-in Mic, SD Card Slot, Reset Button</li> <li>-Operating Conditions -40°C-65°C, 0-95% RH</li> <li>-POE, IP67</li> </ul>	IRR 98,500,000
32	TC-R3105 I/B/L/EU		<ul style="list-style-type: none"> <li>Video Input 5-ch</li> <li>Max Resolution 6MP</li> <li>Two-way Audio Input N/A</li> <li>Bandwidth Income 50Mbps; Outgoing 40Mbps</li> </ul>	IRR 37,950,000
33	TC-R3105 SPEC:I/B/P/L		<ul style="list-style-type: none"> <li>S+265/H.265/H.264 video formats</li> <li>• 1xHDMI and 1xVGA simultaneous outputs</li> <li>• HDMI Video output at up to 4K resolution</li> <li>• Connectable to the third-party network cameras</li> <li>• 1 SATA interface, up to 8TB for 1 HDD</li> <li>• S+265 compression effectively reduces the storage space and costs by up to 75%</li> <li>• 1xRJ45 self-adaptive 10/100 Mbps network interface</li> </ul>	IRR 57,750,000
34	TC-R3108 SPEC: I/B		<ul style="list-style-type: none"> <li>S+265/H.265/H.264 video formats</li> <li>• Up to 8-channel input 8 PoE ports</li> <li>• Supports live view, storage, and playback of the connected camera at up to 6MP resolution</li> <li>• HDMI Video output at up to 4K resolution</li> <li>• 1 SATA interfaces, up to 8TB for each HDD</li> <li>• S+265 compression effectively reduces the storage space and costs by up to 75%</li> <li>• 1xRJ45 self-adaptive 10/100 Mbps network interface</li> <li>• PoE Port: 8xRJ45 self-adaptive 10/100 Mbps network</li> </ul>	IRR 42,525,000
35	TC-R3110 SPEC : I/B/L/EU		<ul style="list-style-type: none"> <li>10-ch, 50Mbps/40Mbps, recording resolution up to 6MP, decoding ability 1*6MP, 3*1080p, 4*720p, video output: 1 HDMI &amp; 1VGA simultaneous output, USB interface: 2xUSB 2.0</li> </ul>	IRR 42,550,000
36	TC-R3110 SPEC : I/B/V.03		<ul style="list-style-type: none"> <li>S+265/H.265/H.264 video formats</li> <li>• HDMI and VGA simultaneous output</li> <li>• HDMI Video output at up to 4K (3840 x 2160) resolution</li> <li>• 1 SATA interface, up to 10TB for 1 HDD</li> <li>• S+265 compression effectively reduces the storage space and costs by up to 75%</li> </ul>	IRR 47,850,000
37	TC-R3120 Spec: I/B/K/V3.0		<ul style="list-style-type: none"> <li>20-ch, 80Mbps/80Mbps, recording resolution up to 8MP, decoding ability 1*8MP, 4*1080p, 8*720p, video output: 1 HDMI &amp; 1VGA simultaneous output, USB interface: 2xUSB 2.0, N+M</li> </ul>	IRR 98,785,000
38	TC-R3220 Spec:I/B/K		<ul style="list-style-type: none"> <li>20-ch, 120Mbps/100Mbps, recording resolution up to 8MP, decoding ability 1*8MP, 4*1080p, 8*720p, video output: 1 HDMI &amp; 1VGA simultaneous output, alarm I/O 4/1, USB interface: 2xUSB 2.0, ANR, N+M</li> </ul>	IRR 130,900,000

39	TC-R3232 I/B/K/V3.1		<p>Video Input 32-ch Max Resolution 8MP Two-way Audio Input 1-ch, 3.5mm Bandwidth Income 160Mbps, Outgoing 48Mbps Output HDMI 1-ch, 3840x2160, 1920x1080, 1280x720, 1024x768, 1366x768, 1440x900, 1280x800 VGA 1-ch, 1920x1080, 1280x720, 1024x768, 1366x768, 1440x900, 1280x800 Screen Split 1/3/4/5/6/7/8/9/10/12/13/16/20A/20B/25/32 Audio Output 1xRCA</p>	IRR 159,850,000
40	TC-R3432 I/B/K/V3.1		<p>Video Input 32-ch Max Resolution 8MP Two-way Audio Input 1-ch, 3.5mm Bandwidth Income 160Mbps, Outgoing 48Mbps Output HDMI 1-ch, 3840x2160, 1920x1080, 1280x720, 1024x768, 1366x768, 1440x900, 1280x800 VGA 1-ch, 1920x1080, 1280x720, 1024x768, 1366x768, 1440x900, 1280x800 Screen Split 1/3/4/5/6/7/8/9/10/12/13/16/20A/20B/25/32 Audio Output 1xRCA</p>	IRR 209,300,000
41	TC-R3440 I/B/N/H/C		<p>HD Input: S-265/H.265/H.264 video formats • Connectable to the third-party network cameras • Up to 40-channel input • Supports live view, storage, and playback of the connected camera at up to 12MP resolution HD Output • HDMI and VGA simultaneous output • HDMI Video output at up to 4K (3840x2160) resolution HD Storage • 4 SATA interfaces, up to 10TB for each HDD • S+265 compression effectively reduces the storage space and costs by up to 75% HD Transmission • 2xRJ45 self-adaptive 10/100/1000 Mbps network interfaces, Various Applications • Centralized management of IP cameras, including configuration, information import/export, real-time information display, upgrade, etc. • Connectable to smart IP cameras from Tiandy and the recording, playing back, and backing up of VGA</p>	IRR 281,750,000

### color maker series

42	TC-C32XP I3W/E/Y/2.8MM/V4.2		<p>-Default: Metal+Plastic, M: Metal Housing -Up to 1920x1080@30fps -S+265/H.265/H.264 -Min. illumination Color: 0.0008Lux@F1.6 -Smart IR, IR Range: 30m -Support tripwire and perimeter -Built-in Mic, SD Card Slot, Reset Button -Operating Conditions -40°C-65°C, 0-95% RH -POE, IP67</p>	IRR 41,796,000
43	TC-C32XP W/E/Y/2.8MM/V4.2		<p>-Default: Metal+Plastic -Up to 1920x1080@30fps -S+265/H.265/H.264 -Min. illumination Color: 0.0008Lux@F1.6 -2 Warm lights, 15-20m -Support tripwire and perimeter -Built-in Mic, SD Card Slot, Reset Button -POE, IP66</p>	IRR 39,600,000
44	TC-C34XP W/E/Y/M/2.8MM/V4.0		1/2.8" CMOS, F1.6, Fixed Iris, Digital WDR, 0.0008Lux, 1920x1080@30fps, 512 GB SD card slot, Built-in Mic, Reset Button, IP67, PoE Metal model: cost added 4USD	IRR 60,375,000
45	TC-C34UP W/E/Y/M/4MM/V4.0		<p>-Full Metal Housing -Up to 2560x1440@25fps -S+265/H.265/H.264 -Min. illumination Color: 0.0002Lux@F1.0 -120dB WDR -4 Warmlights, 20-30m -Support tripwire and perimeter -Built-in Mic, SD Card Slot, Reset Button -Operating Conditions -40°C-60°C, 0-95% RH -POE, IP67</p>	IRR 97,405,000
46	TC-C32WP I5/E/Y/2.8MM/V4.0		<p>-Up to 1920x1080@30fps -S+265/H.265/H.264 -Min. illumination Color: 0.0008Lux@F1.6 -2 Warm lights, 15-20m -Support tripwire and perimeter -Built-in Mic, SD Card Slot, Reset Button -POE, IP67</p>	IRR 43,870,000
47	TC-C32WP Spec:I5W/E/Y/2.8mm/V4.2		<p>-Up to 1920x1080@30fps -S+265/H.265/H.264 -Min. illumination Color: 0.0008Lux@F1.6 -2 Warm lights, 15-20m -Support tripwire and perimeter -Built-in Mic, SD Card Slot, Reset Button -POE, IP67</p>	IRR 52,416,000

### eco pro

48	TC-C32MS SPEC:I3/A/E/Y/M/C/H/2.7-13.5MM/V4.0		<p>-Full Metal Housing -Motorized Lens 2.7-13.5mm -Up to 1920x1080@30fps -S+265/H.265/H.264/M-JPEG -Min. illumination Color: 0.001Lux@F1.6 -Smart IR, IR Range: 50m -Support Video Analytics</p>	IRR 79,000,000
49	TC-C32KS Spec: I3/E/Y/C/H/2.8mm/V4.0		<p>-Full Metal Housing -Up to 1920x1080@30fps -S+265/H.265/H.264/M-JPEG -Min. illumination Color: 0.001Lux@F1.6 -Smart IR, IR Range: 30m -Support Video Analytics</p>	IRR 58,937,500
50	TC-C32KS Spec: I3/E/Y/C/H/2.8mm		<p>-Full Metal Housing -Up to 1920x1080@30fps -S+265/H.265/H.264/M-JPEG -Min. illumination Color: 0.001Lux@F1.6 -Smart IR, IR Range: 30m -Support Video Analytics</p>	IRR 58,937,500

51	TC-C35KS Spec:13/E/Y/2.8mm/V4.0		<ul style="list-style-type: none"> <li>5MP Fixed Starlight IR Dome Camera</li> <li>-Metal+Plastic Housing</li> <li>-Up to Max Resolution</li> <li>-IR Range: 30m</li> <li>-Built-in Mic, IP67, DC12V, POE</li> <li>-Support Smart Surveillance</li> <li>-Support SD Card up to 512GB</li> <li>-S+265/H.265/H.264B/H.264M/H.264H</li> <li>-Operating Conditions: -40°C ~ 65°C, 0~95% RH</li> <li>-Color: 0.002Lux@F1.6, AGCON, B/W: 0Lux with IR</li> </ul>	IRR 71,585,000
52	TC-C32WS Spec:15/E/Y/C/H/4mm/V4.		<ul style="list-style-type: none"> <li>2MP Fixed Starlight IR Bullet Camera</li> <li>-Metal+Plastic Housing</li> <li>-Up to 1920x1080@30fps</li> <li>-Smart IR, IR Range: 50m</li> <li>-S+265/H.265/H.264_POE, IP67</li> <li>-Support tripwire and perimeter</li> <li>-Audio I/O 1/1, Alarm I/O 1/1</li> <li>-Built-in Mic, SD Card Slot, Reset Button</li> <li>-Operating Conditions: -35° ~ 65° C, 0~95% RH</li> <li>-Min. illumination Color: 0.002Lux@F1.6</li> </ul>	IRR 51,250,000
53	TC-C34LP Spec:15/A/E/M/H/2.7-13.5mm		<ul style="list-style-type: none"> <li>-Full Metal Housing</li> <li>-Motorized Lens 2.7-13.5mm</li> <li>-Up to 2560x1440@30fps, 1920x1080@60fps</li> <li>-S+265/H.265/H.264M-JPEG</li> <li>-Min. illumination Color: 0.0004Lux@F1.2</li> <li>-Support Video Analytics</li> <li>-Support Human/Vehicle Classification</li> </ul>	IRR 156,200,000
54	TC-C35MS 13/A/E/Y/M/2.8-12MM		<ul style="list-style-type: none"> <li>-Full Metal Housing</li> <li>-Motorized Lens 2.7-13.5mm</li> <li>-Up to 2592x1944@20fps</li> <li>-S+265/H.265/H.264</li> <li>-Min. illumination Color: 0.002Lux@F1.6</li> <li>-Smart IR, IR Range: 30m</li> <li>-Support tripwire and perimeter</li> <li>-Built-in Mic, SD Card Slot, Reset Button</li> <li>-Audio I/O 1/1, Alarm I/O 1/1</li> <li>-POE, IP66, IK10</li> </ul>	IRR 99,960,000
55	TC-C35MS Spec:13/A/E/Y/M/C/H/2.7-13.5mm		<ul style="list-style-type: none"> <li>5MP Motorized Starlight IR Dome Camera</li> <li>-Full Metal Housing</li> <li>-Motorized Lens 2.8-12mm</li> <li>-Up to 2592x1944@20fps</li> <li>-S+265/H.265/H.264</li> <li>-POE, IP67, IK10</li> </ul>	IRR 99,960,000
56	TC-C35MS Spec:13/A/E/Y/M/C/H/2.7-13.5mm/V4.0		<ul style="list-style-type: none"> <li>TC-C35MS Spec:13/A/E/Y/M/C/H/2.7-13.5mm/V4.0</li> <li>64 IRR 99,960,000</li> <li>5MP</li> <li>5MP Motorized Starlight IR Dome Camera</li> <li>-Full Metal Housing</li> <li>-Motorized Lens 2.8-12mm</li> <li>-Up to 2592x1944@20fps</li> <li>-S+265/H.265/H.264</li> <li>-POE, IP67, IK10</li> </ul>	IRR 99,960,000
57	TC-C35US 18/A/E/Y/M/C/H/2.7-13.5MM/V4.0		<ul style="list-style-type: none"> <li>-Full Metal Housing</li> <li>-Motorized Lens 2.7-13.5mm</li> <li>-Up to 2592x1944@30fps, 1920x1080@60fps</li> <li>-S+265/H.265/H.264M-JPEG</li> <li>-Min. illumination Color: 0.001Lux@F1.6</li> <li>-Smart IR, IR Range: 80m</li> <li>-Support Video Analytics</li> <li>-Support Human/Vehicle Classification</li> <li>-Support Face Capture Mode</li> <li>-Built-in Mic, Audio I/O 1/1, alarm I/O 2/1</li> <li>-POE, IP67</li> </ul>	IRR 99,960,000
58	TC-C35TS Spec: 18/A/E/Y/M/H/2.7-13.5mm		<ul style="list-style-type: none"> <li>-Full Metal Housing -Motorized Lens 2.7-13.5mm -Up to 2592x1944@30fps, 1920x1080@60fps</li> <li>-S+265/H.265/H.264M-JPEG -Min. illumination Color: 0.001Lux@F1.6 -Smart IR, IR Range: 80m -Support Video Analytics</li> </ul>	IRR 149,100,000
<b>PRO-LPR series</b>				
59	TC-C34WS 15W/E/Y/2.8MM/V4.2		<ul style="list-style-type: none"> <li>1/2.8" CMOS, F1.6, Fixed Iris, 120dB, 50m IR, 0.002Lux, 2560x1440@25fps, 512 GB SD card slot, Built-in Mic, Reset Button, IP67, PoE</li> <li>Metal model: cost added 4USD</li> </ul>	IRR 56,350,000
60	TC-C34WS 15W/E/Y/M/2.8MM/V4.2		<ul style="list-style-type: none"> <li>1/2.8" CMOS, F1.6, Fixed Iris, 120dB, 50m IR, 0.002Lux, 2560x1440@25fps, 512 GB SD card slot, Built-in Mic, Reset Button, IP67, PoE</li> <li>Metal model: cost added 4USD</li> </ul>	IRR 59,290,000
61	TC-C34XS 13W/E/Y/2.8MM/V4.2		<ul style="list-style-type: none"> <li>Default: Metal+Plastic</li> <li>-Up to 2560x1440@25fps</li> <li>-S+265/H.265/H.264</li> <li>-Min. illumination Color: 0.002Lux@F1.6-120dB WDR</li> <li>-Smart IR, IR Range: 30m</li> <li>-Support tripwire and perimeter</li> <li>-Built-in Mic, SD Card Slot, Reset Button</li> <li>-POE, IP67</li> </ul>	IRR 53,900,000
<b>NVR-PRO</b>				
62	TC-R3440 Spec:1/B/N		<ul style="list-style-type: none"> <li>Supports up to 32 channels</li> <li>-Connectable to the third-party network cameras</li> <li>-Up to 40 IP cameras can be connected</li> <li>-Supports live view, storage, and playback of the connected camera at up to 12MP resolution</li> <li>-HDMI and VGA independent outputs</li> <li>-HDMI Video output at up to 4K (3840 x 2160) resolution</li> <li>-HD Storage</li> <li>-4 SATA interfaces connectable for recording and backup, up to 10TB for each HDD</li> </ul>	IRR 446,775,000

63	TC-R3220 Spec:1/B/P16/K/V3.0		<p>HD Input Plug and play -&gt; 200m/200m/200m video formats</p> <ul style="list-style-type: none"> <li>• Connectable to the third-party network cameras</li> <li>• Up to 20-channel input • 16 PoE ports</li> <li>• Supports live view, storage, and playback of the connected camera at up to 8MP resolution</li> <li>• HD Output</li> <li>• 1xHDMI and 1xVGA simultaneous outputs</li> <li>• HDMI Video output at up to 4K (3840 x 2160) resolution</li> <li>• HD Storage - 2 SATA interfaces, up to 10TB for each HDD</li> <li>• S+265 compression effectively reduces the storage space and costs by up to 75%</li> <li>• HD Transmission</li> <li>• 1xRJ45 self-adaptive 10/100/1000 Mbps network interface</li> </ul>	IRR 229,400,000
64	TC-R3840 Spec:1/B/N		<ul style="list-style-type: none"> <li>• Upto40IPcamerascanbeconnected</li> <li>• S+265/H.265/H.264videoformats</li> <li>• Upto12MPresolution</li> <li>• HDMIandVGA</li> <li>• HDMIVideooutputupto4K(3840x2160)resolution</li> <li>• 8SATAinterfaces,upto10TBforeachHDD</li> <li>• 2xRJ45self-adaptive10/100/1000Mbpsnetworkinterfaces-2xRJ45self-adaptive10/100/1000Mbpsnetworkinterfaces</li> </ul>	IRR 498,250,000
<b>SPEED DOM -SMD</b>				
65	TC-H324S 23X/I/E/C/V3.0		PoE+, 1/2.8" Starlight sensor, 1080P@30fps, 150m IR, 25x optical zoom, Speed 0.1"-200"/s, Heater, TVS 6000V protection; Low Illumination: 0.002Lux	IRR 200,100,000
66	TC-H324S 25X/I/E		<ul style="list-style-type: none"> <li>• Up to 1920X1080@30fps</li> <li>• Min. illumination Color: 0.001Lux@F1.5</li> <li>• Optical zoom: 25x, digital zoom 16x</li> <li>• Support Human/Vehicle Classification</li> <li>• Smart IR, IR Range: 150m</li> <li>• S+265/H.265/H.264/M-JPEG</li> <li>• Plugin Free</li> <li>• IP66</li> </ul>	IRR 321,195,000
67	TC-H326S Spec:33X/I/E++/A		<ul style="list-style-type: none"> <li>• 2MP33xStarlightIRPOEAIPTZCamera</li> <li>• Upto1920x1080@60fps</li> <li>• SmartIR,IRRange:200m .S+265/H.265/H.264/M-JPEG</li> <li>• IP66,PluginFree .SupportAuto-tracking</li> <li>• Opticalzoom:33x,digitalzoom 16x</li> <li>• SupportHuman/VehicleClassification</li> <li>• Min.illuminationColor:0.001Lux@F1.5</li> <li>• Intelligentmonitoring/FaceCapturemode</li> </ul>	IRR 693,600,000
68	TC-H356S Spec:30X/I/E++/A/V3.0		<ul style="list-style-type: none"> <li>• 5MP30xStarlightIRPOEAIPTZCamera</li> <li>• SupportAuto-tracking</li> <li>• Upto2880x1620@30fps - SmartIR,IRRange:200m</li> <li>• S+265/H.265/H.264/M-JPEG - PluginFree,IP66</li> <li>• Min.illuminationColor:0.001Lux@F1.5</li> <li>• Opticalzoom:30x,digitalzoom 16x</li> <li>• Intelligentmonitoring/FaceCapturemode</li> <li>• SupportHuman/VehicleClassification</li> </ul>	IRR 748,000,000
69	TC-H354S 23X/I/E/V3.0		<ul style="list-style-type: none"> <li>• 5MP 23x Starlight IR</li> <li>• PoE AI PTZ Camera- Up to 2880x1620@30fps</li> <li>• Optical zoom: 23x, digital zoom 16x</li> <li>• Smart IR, IR Range: 150m</li> <li>• S+265/H.265/H.264/M-JPEG</li> <li>• Intelligent monitoring</li> <li>• Support Human/Vehicle Classification-Plugin Free-IP66</li> </ul>	IRR 351,750,000